



- 1 FLAME RETARDANT THERMOPLASTIC, COLOR; BLACK
- 2 COPPER ALLOY
- 3 .00076[.000030] GOLD OVER .00127[.000050] NICKEL AT AREA "M"  
.00254[.000100]-.00508[.000200] BRIGHT TIN-LEAD OVER  
.00127[.000050] NICKEL AT AREA 'H'
- 4 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 5 RECESSED DATE CODE AND CSA LOGO.
- 6 .00076[.000030] GOLD OVER .00127[.000050] NICKEL AT AREA "M"  
.00254[.000100]-.00508[.000200] MATTE TIN OVER  
.00127[.000050] NICKEL AT AREA 'H'
- 7 ROHS 2002/95/EC COMPLIANT

6	CURCUIT 11,12 ROW M	8.13 [.320]	10.41 [.410]	6.35 [.250]	70.36 [2.770]	60.96 [2.400]	24	71.12 [2.800]	73.15 [2.880]	50	5-146701-1
3	CURCUIT 11,12 ROW M	8.13 [.320]	10.41 [.410]	6.35 [.250]	70.36 [2.770]	60.96 [2.400]	24	71.12 [2.800]	73.15 [2.880]	50	146701-1
FINISH	SELECT LOAD .410 HIGH	J	G	F	E	D	C	B	A	NO. OF POSITIONS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	DIN T. HOFFMAN 10/19/95	tyco Tyco Electronics Corporation Harrisburg, Pa 17105-3608
0 PLC ± -	1 PLC ± -	CHK H. PALEY 11/22/95	ASSEMBLY, HEADER, MOD II, DOUBLE ROW, .100 X .100 CL, .025 SQ. ACTION PIN POSTS, SELECT LOAD
2 PLC ± -	3 PLC ± -	APVD H. PALEY 11/22/95	SIZE CAGE CODE DRAWING NO RESTRICTED TO
4 PLC ± -	ANGLES ± -	WEIGHT -	A1 00779 C=146701 -
MATERIAL 1	FINISH 3 6	CUSTOMER DRAWING	SCALE 4:1 SHEET 1 OF 1 REV A