THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19
© COPYRIGHT 19 BY AMP INCORPORATED. ALL INTERNATIONAL RIGHTS RESERVED.

REVISIONS				
LTR	DESCRIPTION	DATE	APPD
N	REV & REDWN PER ECN CM-11	10-29-93	



RECOMMENDED MOUNTING HOLE PATTERN
FOR 3.18 [.125] THICK P.C. BOARD





SECTION A–A

1. PARTS MUST COMPLY WITH AMP SOLDERABILITY SPECIFICATION 109-11-3.
2. CONTACT IS PLATED OVERALL WITH 0.00127 [.000050] NICKEL, THEN 0.00076 [.00030] GOLD OVER CONTACT LENGTH INDICATED AND MATTE TIN ON SOLDERTAIL END.
3. DIMENSIONS IN BRACKETS ARE IN INCHES.

PART NO	HOUSING MATERIAL AND COLOR	PIN CONTACT MATERIAL AND FINISH
350427-2	NYLON, 6/6, NATURAL	COPPER ALLOY, GOLD 2
350427-1	NYLON, 6/6, NATURAL	COPPER ALLOY, PRE-TIN

METRIC

DO NOT SCALE PRINT.
UNLESS SPECIFIED DIMENSIONS IN mm [INCHES]
TOLERANCES ON .
2 PLC DEC ± 0.13 [.005]
3 PLC DEC ± -
ANGLES ± -

MATERIAL: SEE TABLE
FINISH: SEE TABLE

DR 10-29-93 K. SALMON
CHK 10-29-93 R. SWING
APPD 11-9-93 C. MARTIN
APPD 11-9-93 C. MARTIN
PRODUCT SPEC -
APPLICATION SPEC -
WEIGHT -

AMP Incorporated
Harrisburg, PA 17105-3608

NAME: HEADER ASSEMBLY, 16 CIRCUIT, COMMERCIAL MATE-N-LOK™

SIZE	CAGE CODE	DRAWING NO
D	00779	C-350427

SCALE 4:1 SHEET 1 OF 1

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

CUSTOMER DRAWING

29 OCT 1993 15:58:07 AMP2000 <C0279D-REPT3923-AMP2000-W.PROD-05