



RECOMMENDED HOLE LAYOUT

- ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
- BREAKAWAY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- .000100-.000200 MATTE TIN-LEAD OVER .000050 NICKEL.
- .000100-.000200 BRIGHT TIN OVER .000050 NICKEL.
- PRELIMINARY PART - NOT RELEASED FOR PRODUCTION.
- HOUSING MATERIAL: FLAME RETARDANT THERMOPLASTIC; COLOR-BLACK. POSTS: PHOS BRONZE
- .000100-.000200 MATTE TIN OVER .000050 NICKEL.

3.984	3.900	39	40	9-103323-0
3.884	3.800	38	39	8-103328-9
3.784	3.700	37	38	8-103328-8
3.684	3.600	36	37	8-103328-7
3.584	3.500	35	36	8-103328-6
3.484	3.400	34	35	8-103328-5
3.384	3.300	33	34	8-103328-4
3.284	3.200	32	33	8-103328-3
3.184	3.100	31	32	8-103328-2
3.084	3.000	30	31	8-103328-1
2.984	2.900	29	30	8-103328-0
2.884	2.800	28	29	7-103323-9
2.784	2.700	27	28	7-103323-8
2.684	2.600	26	27	7-103323-7
2.584	2.500	25	26	7-103323-6
2.484	2.400	24	25	7-103323-5
2.384	2.300	23	24	7-103323-4
2.284	2.200	22	23	7-103323-3
2.184	2.100	21	22	7-103323-2
2.084	2.000	20	21	7-103323-1
1.984	1.900	19	20	7-103323-0
1.884	1.800	18	19	6-103323-9
1.784	1.700	17	18	6-103323-8
1.684	1.600	16	17	6-103323-7
1.584	1.500	15	16	6-103323-6
1.484	1.400	14	15	6-103323-5
1.384	1.300	13	14	6-103323-4
1.284	1.200	12	13	6-103323-3
1.184	1.100	11	12	6-103323-2
1.084	1.000	10	11	6-103323-1
.984	.900	9	10	6-103323-0
.884	.800	8	9	5-103323-9
.784	.700	7	8	5-103323-8
.684	.600	6	7	5-103323-7
.584	.500	5	6	5-103323-6
.484	.400	4	5	5-103323-5
.384	.300	3	4	5-103323-4
.284	.200	2	3	5-103323-3
.184	.100	1	2	5-103323-2
.084	—	—	1	5-103323-1

.184	.100	1	2	4-103323-2
3.984	3.900	39	40	4-103323-1
3.984	3.900	39	40	4-103323-0
3.884	3.800	38	39	3-103323-9
3.784	3.700	37	38	3-103323-8
3.684	3.600	36	37	3-103323-7
3.584	3.500	35	36	3-103323-6
3.484	3.400	34	35	3-103323-5
3.384	3.300	33	34	3-103323-4
3.284	3.200	32	33	3-103323-3
3.184	3.100	31	32	3-103323-2
3.084	3.000	30	31	3-103323-1
2.984	2.900	29	30	3-103323-0
2.884	2.800	28	29	2-103323-9
2.784	2.700	27	28	2-103323-8
2.684	2.600	26	27	2-103323-7
2.584	2.500	25	26	2-103323-6
2.484	2.400	24	25	2-103323-5
2.384	2.300	23	24	2-103323-4
2.284	2.200	22	23	2-103323-3
2.184	2.100	21	22	2-103323-2
2.084	2.000	20	21	2-103323-1
1.984	1.900	19	20	2-103323-0
1.884	1.800	18	19	1-103323-9
1.784	1.700	17	18	1-103323-8
1.684	1.600	16	17	1-103323-7
1.584	1.500	15	16	1-103323-6
1.484	1.400	14	15	1-103323-5
1.384	1.300	13	14	1-103323-4
1.284	1.200	12	13	1-103323-3
1.184	1.100	11	12	1-103323-2
1.084	1.000	10	11	1-103323-1
.984	.900	9	10	1-103323-0
.884	.800	8	9	103323-9
.784	.700	7	8	103323-8
.684	.600	6	7	103323-7
.584	.500	5	6	103323-6
.484	.400	4	5	103323-5
.384	.300	3	4	103323-4
.284	.200	2	3	103323-3
.184	.100	1	2	103323-2
.084	—	—	1	103323-1

PLATING	C	B	A	NO OF POSN	PART NUMBER
---------	---	---	---	------------	-------------

PLATING	C	B	A	NO OF POSN	PART NUMBER
---------	---	---	---	------------	-------------

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PL	± .005
1 PL	± .005
2 PL	± .005
3 PL	± .005
4 PL	± .005
ANGLES	± .005
FINISH	SEE TABLE

MATERIAL: SEE TABLE

APPROVED: JOHN KNITTLE

DATE: 23NOV92

DESIGNED BY: B. FLINCHBAUGH

DATE: 23NOV92

NAME: HEADER ASSY, MOD II, BREAKAWAY, SINGLE ROW, .100, RIGHT ANGLE, WITH .025 SQUARE POSTS

SIZE: A1

SCALE: 4:1

SHEET: 1 OF 1

REV: K

DRAWING NO: 00779

PART NO: 103323

CUSTOMER DRAWING