

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△				..	△				..
△				..	△				..

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C (NOTE1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C	
	VOLTAGE	250 V AC	APPLICABLE CONTACT		
	CURRENT	3 A AC	APPLICABLE CONNECTOR		
			APPLICABLE CABLE		

### SPECIFICATIONS


ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	<input type="checkbox"/>	<input type="checkbox"/>
MARKING	CONFIRMED VISUALLY.		<input type="checkbox"/>	<input type="checkbox"/>

ELECTRICAL CHARACTERISTICS				
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).	30 mΩ MAX.	<input type="checkbox"/>	<input type="checkbox"/>
CONTACT RESISTANCE MILLIVOLT LEVEL METHOD.	20 mV MAX. mA (DC OR 1000 Hz).	mΩ MAX.	<input type="checkbox"/>	<input type="checkbox"/>
INSULATION RESISTANCE	500 V DC	1000 MΩ MIN.	<input type="checkbox"/>	<input type="checkbox"/>
VOLTAGE PROOF	650 V AC FOR 1 min	NO FLASHOVER OR BREAKDOWN.	<input type="checkbox"/>	<input type="checkbox"/>

MECHANICAL CHARACTERISTICS				
CONTACT INSERTION AND EXTRACTION FORCES	□0.635 ± 0.002 BY STEEL GAUGE.	INSERTION FORCE 4.4 N MAX. EXTRACTION FORCE 0.4 N MIN.	<input type="checkbox"/>	<input type="checkbox"/>
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE N MAX. EXTRACTION FORCE N MIN.	<input type="checkbox"/>	<input type="checkbox"/>
MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS	① CONTACT RESISTANCE: 30 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 1.5 mm, 98 m/s <sup>2</sup> AT 2 h FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE: 30 mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 μs AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 10 μs. ② CONTACT RESISTANCE: — mΩ MAX. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>

ENVIRONMENTAL CHARACTERISTICS				
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90~95% RH, 96 h.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 ± 3 - 5 ~ 35 - 85 ± 2 - 5 ~ 35 °C TIME 30 → 5 → 30 → 5 min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: MΩ. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	<input type="checkbox"/>	<input type="checkbox"/>
RESISTANCE TO SOLDERING HEAT	SOLDER TEMPERATURE, IMMERSION, DURATION. °C FOR s.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	<input type="checkbox"/>	<input type="checkbox"/>
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE, FOR IMMERSION DURATION, °C s.	A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95% OF THE SURFACE BEING IMMersed.	<input type="checkbox"/>	<input type="checkbox"/>

REMARKS	NOTE1 INCLUDE THE TEMPERATURE RISING BY CURRENT.	DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED
	Unless otherwise specified, refer to MIL-STD-1344.	M. Tanaka	M. Tanaka	J. Omi	H. Yamamoto	
		'95.5.31	'95.5.31	'95.5.31	'95.6.1	

Note QT: Qualification Test AT: Assurance Test ○: Applicable Test






<b>HRS</b> HIROSE ELECTRIC CO., LTD.	SPECIFICATION SHEET	PART NO.
		DF1B- <del>X</del> DP-2.5DSA

CODE NO. (OLD)	DRAWING NO.	CODE NO.	
CL	ELC4-71800-04	0616-4	1/1
		CL541-0653-0	1/1

FOR REFERENCE ONLY  
Subject to change without notice

TO

COUNT DESCRIPTION OF REVISIONS BY CHGD		COUNT DESCRIPTION OF REVISIONS BY CHGD		COUNT DESCRIPTION OF REVISIONS BY CHGD		COUNT DESCRIPTION OF REVISIONS BY CHGD		COUNT DESCRIPTION OF REVISIONS BY CHGD	
NO.	DATE	NO.	DATE	NO.	DATE	NO.	DATE	NO.	DATE



HRS NO.	PART NO.	A	B	C
541-0651-5	DF1B-4DP-2.5DSA	7.5	2.5	5.6
541-0652-8	DF1B-6DP-2.5DSA	10.0	5.0	8.1
541-0653-0	DF1B-8DP-2.5DSA	12.5	7.5	10.6
541-0616-4	DF1B-10DP-2.5DSA	15.0	10.0	13.1
541-0617-7	DF1B-12DP-2.5DSA	17.5	12.5	15.6
541-0618-0	DF1B-14DP-2.5DSA	20.0	15.0	18.1
541-0619-2	DF1B-16DP-2.5DSA	22.5	17.5	20.6
541-0620-1	DF1B-18DP-2.5DSA	25.0	20.0	23.1
541-0621-4	DF1B-20DP-2.5DSA	27.5	22.5	25.6
541-0622-7	DF1B-22DP-2.5DSA	30.0	25.0	28.1
541-0623-0	DF1B-24DP-2.5DSA	32.5	27.5	30.6
541-0624-2	DF1B-26DP-2.5DSA	35.0	30.0	33.1
541-0625-5	DF1B-28DP-2.5DSA	37.5	32.5	35.6
541-0626-8	DF1B-30DP-2.5DSA	40.0	35.0	38.1
541-0628-3	DF1B-34DP-2.5DSA	45.0	40.0	43.1
541-0629-6	DF1B-36DP-2.5DSA	47.5	42.5	45.6
541-0631-8	DF1B-40DP-2.5DSA	52.0	47.5	50.6

NOTE1: HRS MARK.  
 NOTE2: WHEN THE NUMBERS OF CONTACTS OF FIRST ROW IS ODD, THE STAND-OFF SHIFTS 1.25 RIGHTWARD. (STAND-OFF AVAILABLE FROM 8 POSITIONS UP.)  
 NOTE3: MARK OF THE NUMBER OF PIN \*(#=NO. OF PIN)  
 NOTE4: 4 POSITIONS AND 6 POSITIONS HEADERS HAVE ONE POLARIZING SLOT AT CENTER. OTHER POSITIONS HAVE 2 POLARIZING SLOTS AS PER DRAWING.

**FOR REFERENCE ONLY**  
 Subject to change without notice

NO. MATERIAL	FINISH, REMARKS	NO. MATERIAL	FINISH, REMARKS
2 BRASS	TIN PLATED	1 POLYAMIDE	NATURAL, UL94V-0
DRAWN		DESIGNED	
M. Sood		M. Sood	
DATE: 94.6.28		DATE: 94.6.28	
SCALE: 2:1		PART NO. DF1B-*DP-2.5DSA	
UNITS: m/m		CODE NO. 0651	
DRAWING NO. EDC3-160182		APPROVED	
HRS		J. D. ...	
HITROSE ELECTRIC CO., LTD.		CL541-0631-8	
FORM NO. 225		1/1	