



SULLINS ELECTRONICS CORP
SAN MARCOS, CA 760-744-0125 FAX 760-744-6081



| | | | |
|---|---|--------------|---------------|
| A | = | 0.300+-0.020 | [7.62+-0.51] |
| B | = | 0.200+-0.008 | [5.08+-0.20] |
| C | = | 0.100+-0.003 | [2.54+-0.08] |
| D | = | 0.100+-0.005 | [2.54+-0.13] |
| E | = | 0.050+-0.005 | [1.27+-0.13] |
| F | = | 0.230+-0.015 | [5.84+-0.38] |
| G | = | 0.100+-0.005 | [2.54+-0.13] |
| H | = | 0.520+-0.015 | [13.21+-0.38] |



.025[0.64] SQUARE POSTS FIT .040[1.02] MINIMUM DIAMETER HOLE



- 1.0 SPECIFICATIONS FOR A SINGLE ROW 3 POSITION HEADER
- 2.0 INSULATOR MATERIAL: BLACK THERMOPLASTIC POLYESTER
- 3.0 CONTACT MATERIAL: CA510, PHOSPHOR BRONZE GRADE A
- 4.0 PLATING: .000100" TIN OVERALL, .000050" NICKEL UNDERPLATE
- 5.0 TEMPERATURE: TO 125 DEGREES C CONTINUOUS
- 6.0 UL FLAMMABILITY RATING: 94V-0
- 7.0 VOLTAGE RATING: 600 VDC MINIMUM AT SEA LEVEL
- 8.0 CURRENT RATING: 3 AMPERES
- 9.0 INSULATION RESISTANCE: 5,000 MEGA OHMS
- 10.0 SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
- 11.0 NOT DRAWN TO SCALE

SULLINS PART NUMBER: PTC03SAEN

DATE: 1-29-03

[Print PDF](#)