



基板取付穴推奨寸法

(基板厚: t=1~1.6mm)
RECOMMENDED PC BOARD
HOLE DIMENSION
(THICKNESS: t=1~1.6mm)

注記
NOTE

△ 適合ターミナル: 50034-8*00
APPLICABLE TERMINAL: 50034-8*00

28	30.4	51015-1500	15
26	28.4	↑ -1400	14
24	26.4	-1300	13
22	24.4	-1200	12
20	22.4	-1100	11
18	20.4	-1000	10
16	18.4	-0900	9
14	16.4	-0800	8
12	14.4	-0700	7
10	12.4	-0600	6
8	10.4	-0500	5
6	8.4	-0400	4
4	6.4	↓ -0300	3
2	4.4	51015-0200	2
B	A	ENG.NO.	種数 NO. OF CKT

材料 MATERIAL ナイロン66, UL94V-0 NYLON66, UL94V-0		仕上げ FINISH —		適用電線範囲 WIRE RANGE —		被覆外径 INS. RANGE —		DRAWN BY '96/05/28 H.I.IJIMA		CHK'D BY '96/05/28 M.FUKUSHIMA	
角度 ANGLE ±3°		30以上 OVER ±0.3		10以上 30未満 UNDER ±0.25		10未満 UNDER ±0.2		DRAWN BY '96/05/28 M.ENOMOTO		CHK'D BY '96/05/28 M.FUKUSHIMA	
再作図 REDRAWN		変更内容 REVISION RECORD		DR. CHK.		日付 DATE		REVISION RECORD		DATE	

molex MOLEX-JAPAN CO.,LTD. 日本モレックス株式会社	
REVISE ONLY ON CAD SYSTEM	
TITLE 名称 2.0 BOARD IN CONN. HSG.	
DWG. NO. SD-51015-**-00	REV B