



基板取付穴推奨寸法

(基板厚: t=1~1.6mm)  
 RECOMMENDED PC BOARD  
 HOLE DIMENSION  
 (THICKNESS: t=1~1.6mm)

注記  
 NOTE

△ 適合ターミナル: 50034-8\*00  
 APPLICABLE TERMINAL: 50034-8\*00

28	30.4	51015-1500	15
26	28.4	↑ -1400	14
24	26.4	-1300	13
22	24.4	-1200	12
20	22.4	-1100	11
18	20.4	-1000	10
16	18.4	-0900	9
14	16.4	-0800	8
12	14.4	-0700	7
10	12.4	-0600	6
8	10.4	-0500	5
6	8.4	-0400	4
4	6.4	↓ -0300	3
2	4.4	51015-0200	2
B	A	ENG.NO.	種数 NO. OF CKT

材料 MATERIAL ナイロン66, UL94V-0 NYLON66, UL94V-0		仕上げ FINISH —		適用電線範囲 WIRE RANGE —		被覆外径 INS. RANGE —		DRAWN BY '96/05/28 H.I.IJIMA		CHK'D BY '96/05/28 M.FUKUSHIMA	
角度 ANGLE ±3°		30以上 OVER ±0.3		10以上 30未満 UNDER ±0.25		10未満 UNDER ±0.2		DRAWN BY '96/05/28 M.ENOMOTO		CHK'D BY '96/05/28 M.FUKUSHIMA	
再作図 REDRAWN		変更内容 REVISION RECORD		DR. CHK.		日付 DATE		REVISION RECORD		DATE	

MOLEX JAPAN CO., LTD. 日本モレックス株式会社	
REVISE ONLY ON CAD SYSTEM	
TITLE 名称 2.0 BOARD IN CONN. HSG.	
DWG. NO. SD-51015-**-00	REV B