



- NOTES:
1. MATERIAL : 66 NYLON (UL94V-0)
 2. PRODUCT SPEC.: 108-5408
 3. APPLICATION SPEC.: 114-5179
 4. 7-179228-3 WAS OBSOLETE.

7-179228-5	5-179228-5	3-179228-5	1-179228-5	15	28	30.8	32.0
7-4	5-4	3-4	1-4	14	26	28.8	30.0
7-3	5-3	3-3	1-3	13	24	26.8	28.0
7-2	5-2	3-2	1-2	12	22	24.8	26.0
7-1	5-1	3-1	1-1	11	20	22.8	24.0
7-0	5-0	3-0	1-0	10	18	20.8	22.0
6-9	4-9	2-9	0-9	9	16	18.8	20.0
6-8	4-8	2-8	0-8	8	14	16.8	18.0
6-7	4-7	2-7	0-7	7	12	14.8	16.0
6-6	4-6	2-6	0-6	6	10	12.8	14.0
6-5	4-5	2-5	0-5	5	8	10.8	12.0
6-4	4-4	2-4	0-4	4	6	8.8	10.0
6-3	4-3	2-3	0-3	3	4	6.8	8.0
6-179228-2	4-179228-2	2-179228-2	179228-2	2	2	4.8	6.0
BLACK	YELLOW	BLUE	NATURAL	PDS	A	B	C

Copyright ©9		Copyright ©9		AMP (AMP) LTD.		ALL RIGHTS RESERVED.	
WIRE RANGE		INSULATION DIA		NAME		CRIMP TYPE II RECEPTACLE HOUSING	
mm ² (AWG)		mm φ				(AMP CT CONNECTOR 2mm PITCH)	
B	REVISIED ECR-07-000873	C.Z	S.Y	17 JAN '97			
A1	REVISIED F J00-1213-94	T.F	S.K	8/4 '94			
A	REVISIED F J00-0073-94	T.F	S.K	3/4 '94			
0	RELEASED F J00-0861-93	T.F	S.K	11/16 '93			
LTR	REVISION RECDRD	DR	CHK	DATE	DR	CHK	DATE
					SKUBOUCHI		
MATERIAL NOTE		FINISH		GENERAL TOLERANCE		SIZE	
mm ² (AWG)		mm φ		0.15 ± 0.10 ; ±0.2		A3	
11/12/93		11/12/93		10.0 ± 0.30 ; ±0.25		J	
11/15/93		11/15/93		30.0 ± 1.00 ; ±0.3		C-179228	
11/15/93		11/15/93		ANGLES : ±3°		SCALE	
11/15/93		11/15/93				5 - 1	
11/15/93		11/15/93				REV. B	
11/15/93		11/15/93				SHEET 1 OF 1	

CUSTOMER DRAWING

AMP-J
REV.10/93