

13

4

$\frown$
( )
( )

А

В

FClconnect, com

PRODUCT		NBR	DIM "J"	DIM "K"				
NUMBER		OF POS						
76308-X02(	(LF)	1×02	(2.54	) (5.08)				
76308-X03(	(LF)	1x03	(5.08	) (7.62)				
76308-X04(	(LF)	1×04	(7.62	) (10.16)				
76308-X05(	(LF)	1×05	(10.16	) (12.70)				
76308-X06(	(LF)	1×06	(12.70	) (15.24)				
76308-X07(	(LF)	1x07	(15.24	) (17.78)				
76308-X08(	(LF)	1×08	(17.78	) (20.32)				
76308-X09(	(LF)	1×09	(20.32	) (22.86)				
76308-X10(	(LF)	1×10	(22.86	) (25.40)				
76308-X11(	(LF)	1×11	(25.40	) (27.94)				
76308-X12(	(LF)	1×12	(27.94	) (30.48)				
76308-X13(	(LF)	1x13	(30.48	) (33.02)				
76308-X14(	(LF)	1×14	(33.02	) (35.56)				
76308-X15(	(LF)	1×15	(35.56	) (38.10)				
76308-X16(	(LF)	1×16	(38.10	) (40.64)				
76308-X17(	(LF)	1×17	(40.64	) (43.18)				
76308-X18(	(LF)	1×18	(43.18	) (45.72)				
76308-X19(	(LF)	1x19	(45.72	) (48.26)				
76308-X20(	(LF)	1×20	(48.26	) (50.80)				
76308-X21(	(LF)	1×21	(50.80	) (53.34)				
76308-X22(	(LF)	1×22	(53.34	) (55.88)				
76308-X23(	(LF)	1×23	(55.88	) (58.42)				
76308-X24(	(LF)	1×24	(58.42	) (60.96)				
76308-X25(	(LF)	1x25	(60.96	) (63.50)				
76308-X26(	(LF)	1x26	(63.50	) (66.04)				
76308-X27(	(LF)	1×27	(66.04	) (68.58)				
76308-X28(	(LF)	1×28	(68.58	) (71.12)				
76308-X29(	(LF)	1×29	(71.12	) (73.66)				
76308-X30(	(LF)	1×30	(73.66	) (76.20)				
9	5 j	ım SnPb		1.25 µm SnPb				

1.0 µm Au

0.76 µm Au

CONTACT AREA

PLATING THICKNESS

1

1

PRODUCT	NBR	DIM "J"	DIM "K"
NUMBER	OF POS		
76308-X31(LF)	1x31	(76.20)	(78.74)
76308-X32(LF)	1x32	(78.74)	(81.28)
76308-X33(LF)	1x33	(81.28)	(83.82)
76308-X34(LF)	1x34	(83.82)	(86.36)
76308-X35(LF)	1x35	(86.36)	(88.90)
76308-X36(LF)	1x36	(88.90)	(91.44)
76308-X37(LF)	1x37	(91.44)	(93.98)
76308-X38(LF)	1x38	(93.98)	(96.52)
76308-X39(LF)	1x39	(96.52)	(99.06)
76308-X40(LF)	1×40	(99.06)	(101.60)
76308-X41(LF)	1×41	(101.60)	(104.14)
76308-X42(LF)	1x42	(104.14)	(106.68)
76308-X43(LF)	1x43	(106.68)	(109.22)
76308-X44(LF)	1×44	(109.22)	(111.76)
76308-X45(LF)	1×45	(111.76)	(114.30)
76308-X46(LF)	1x46	(114.30)	(116.84)
76308-X47(LF)	1x47	(116.84)	(119.38)
76308-X48(LF)	1x48	(119.38)	(121.92)
76308-X49(LF)	1x49	(121.92)	(124.46)
76308-X50(LF)	1x50	(124.46)	(127.00)

	mat'l. code					surface /			tolerance			рго	
	SEE TABLE			.E		ISO 1302 🗸			150	406	150 °	101	
	ltr	ecn	Πū	dr	date	2	tolera	Inces	unless	otherv	vise sp	oecified	Т
	Е	V41	799	PNZ	94.1	2.07	angles						
	F	F60	062	ÔМА	96.0	1.30	ung	Ľ	inear				-
	G	V60	456	OMA	96.0	3.11							SEC
	н	F80	325	PNZ	<del>9</del> 8.0	5.06	dr	٥.	MATHE	<b>VON</b>	96.0	1.30	
	J	F05-	0235	DLE	05.0	8.25	engr	AES	CHBAC	CHER	96.0	1.30	
	к	F05-	0282	DLE	05.1	1.03	chr	0.	MATHE	IVON	96.0	01.30	
	لـ	-06-	0216	DLE	076.0	07.11	арра		M. AE	-	96.0	01.30	
	sheet revisio index sheet		гечі	sion									
			et 🗌										
Э							4						

٢

Copyright FCI

(

D

form: A3

2

1

PLATING

CODE X

0.2 µm Au

REMAINDER

0.05 µm Au

PLATING THICKNESS

2

1.3 µm Ni

1.3 µm Ni

1.3 µm Ni

THICKNESS

UNDER PLATING

