



162.56	[6.400]	165.10	[6.500]	65	6-535676-4
160.02	[6.300]	162.56	[6.400]	64	6-535676-3
157.48	[6.200]	160.02	[6.300]	63	6-535676-2
154.94	[6.100]	157.48	[6.200]	62	6-535676-1
152.40	[6.000]	154.94	[6.100]	61	6-535676-0
149.86	[5.900]	152.40	[6.000]	60	5-535676-9
147.32	[5.800]	149.86	[5.900]	59	5-535676-8
144.78	[5.700]	147.32	[5.800]	58	5-535676-7
142.24	[5.600]	144.78	[5.700]	57	5-535676-6
139.70	[5.500]	142.24	[5.600]	56	5-535676-5
137.16	[5.400]	139.70	[5.500]	55	5-535676-4
134.62	[5.300]	137.16	[5.400]	54	5-535676-3
132.08	[5.200]	134.62	[5.300]	53	5-535676-2
129.54	[5.100]	132.08	[5.200]	52	5-535676-1
127.00	[5.000]	129.54	[5.100]	51	5-535676-0
124.46	[4.900]	127.00	[5.000]	50	4-535676-9
121.92	[4.800]	124.46	[4.900]	49	4-535676-8
119.38	[4.700]	121.92	[4.800]	48	4-535676-7
116.84	[4.600]	119.38	[4.700]	47	4-535676-6
114.30	[4.500]	116.84	[4.600]	46	4-535676-5
111.76	[4.400]	114.30	[4.500]	45	4-535676-4
109.22	[4.300]	111.76	[4.400]	44	4-535676-3
106.68	[4.200]	109.22	[4.300]	43	4-535676-2
104.14	[4.100]	106.68	[4.200]	42	4-535676-1
101.16	[4.000]	104.14	[4.100]	41	4-535676-0
99.06	[3.900]	101.16	[4.000]	40	3-535676-9
96.52	[3.800]	99.06	[3.900]	39	3-535676-8
93.98	[3.700]	96.52	[3.800]	38	3-535676-7
91.44	[3.600]	93.98	[3.700]	37	3-535676-6
88.90	[3.500]	91.44	[3.600]	36	3-535676-5
86.36	[3.400]	88.90	[3.500]	35	3-535676-4
83.82	[3.300]	86.36	[3.400]	34	3-535676-3
81.28	[3.200]	83.82	[3.300]	33	3-535676-2
78.74	[3.100]	81.28	[3.200]	32	3-535676-1
76.20	[3.000]	78.74	[3.100]	31	3-535676-0
73.66	[2.900]	76.20	[3.000]	30	2-535676-9
71.12	[2.800]	73.66	[2.900]	29	2-535676-8
68.58	[2.700]	71.12	[2.800]	28	2-535676-7
66.04	[2.600]	68.58	[2.700]	27	2-535676-6
63.50	[2.500]	66.04	[2.600]	26	2-535676-5
60.96	[2.400]	63.50	[2.500]	25	2-535676-4
58.42	[2.300]	60.96	[2.400]	24	2-535676-3
55.88	[2.200]	58.42	[2.300]	23	2-535676-2
53.34	[2.100]	55.88	[2.200]	22	2-535676-1
50.80	[2.000]	53.34	[2.100]	21	2-535676-0
48.26	[1.900]	50.80	[2.000]	20	1-535676-9
45.72	[1.800]	48.26	[1.900]	19	1-535676-8
43.18	[1.700]	45.72	[1.800]	18	1-535676-7
40.64	[1.600]	43.18	[1.700]	17	1-535676-6
38.10	[1.500]	40.64	[1.600]	16	1-535676-5
35.56	[1.400]	38.10	[1.500]	15	1-535676-4
33.02	[1.300]	35.56	[1.400]	14	1-535676-3
30.48	[1.200]	33.02	[1.300]	13	1-535676-2
27.94	[1.100]	30.48	[1.200]	12	1-535676-1
25.40	[1.000]	27.94	[1.100]	11	1-535676-0
22.86	[.900]	25.40	[1.000]	10	535676-9
20.32	[.800]	22.86	[.900]	9	535676-8
17.78	[.700]	20.32	[.800]	8	535676-7
15.24	[.600]	17.78	[.700]	7	535676-6
12.70	[.500]	15.24	[.600]	6	535676-5
10.16	[.400]	12.70	[.500]	5	535676-4
7.62	[.300]	10.16	[.400]	4	535676-3
5.08	[.200]	7.62	[.300]	3	535676-2
2.54	[.100]	5.08	[.200]	2	535676-1

- 1 HOUSING MATERIAL: GLASS FILLED POLYESTER, COLOR- BLACK
- 2 CONTACT MATERIAL: PHOSPHOR BRONZE
- 3 CONTACT FINISH: 0.00076[.000030] THK DUPLEX PLATED GOLD ON CONTACT AREA, 0.00127[.000050] MIN THK BRIGHT TIN-LEAD OR TIN ON SOLDERLEADS, ALL OVER 0.00127[.000050] NICKEL
- 4 MOLDED IN ARROW DESIGNATES THE MATING FACE OF THE CONNECTOR
- 5 POINT OF MEASUREMENT FOR PLATING THICKNESS OF CONTACT AREA
- 6 DIMENSIONS PERTAIN TO HOUSING CAVITY CENTERLINES
- 7 DATE CODE AND PART NUMBER MARKED IN APPROXIMATE LOCATION SHOWN.
- 8 ALTERNATE LOCATION FOR DATE CODE FOR 2 AND 3 POSITION.
- 9 NO PART NUMBER MARKING REQUIRED FOR THIS PART.

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: MM 	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± 0.1%(.005) 4 PLC ± - ANGLES ± -	THIS DRAWING IS A CONTROLLED DOCUMENT. DWG: R BROWN CHK: J OLSON APVD: J OLSON DATE: 03JUN02 NAME: AMPMODU MOD II RECEPTACLE ASSEMBLY, HORIZONTAL, .100 CL, SINGLE ROW, CLOSED-ENTRY, SHORT POINT OF CONTACT, END-TO-END STACKABLE SIZE: A1 CAGE CODE: 00779 DRAWING NO: 535676 WEIGHT: - CUSTOMER DRAWING	Tyco Electronics Corporation Harrisburg, PA 17105 NO. OF POSN: 2 ASSEMBLY PART NUMBER: 535676-1 SCALE: 5:1 SHEET: 1 OF 1 REV: L
-----------------------	--	--	---