



For RoHS compliance  
 select plating code.

- Single row interconnects having an even number of pins are now available with a left or right hand footprint.
- Headers (850 & 852) use MM# 4006 pins. See page 166 for details.
- Sockets (851 & 853) use MM# 4890-0 receptacles and accept pin diameters from .015-.021. See page 129 for details.
- Coplanarity .005" (Single Row max 20 pins; Double Row max 40 pins) for higher pin counts contact tech support .
- Insulators are high temp. thermoplastic.



**Ordering Information**

<b>Fig. 1L</b>	<b>Single Row Header, Left Hand Footprint</b> <b>Odd or Even # of pins</b>	850-XX-0__-30-001000			
	<b>Specify # of pins</b>	01-50			
<b>Fig. 1R</b>	<b>Single Row Header, Right Hand Footprint</b> <b>Even # of pins</b>	850-XX-0__-30-002000			
	<b>Specify even # of pins</b>	02-50			
<b>Fig. 2</b>	<b>Double Row Header, Even # of pins</b>	852-XX-__-30-001000			
	<b>Specify even # of pins</b>	004-100			
SPECIFY PLATING CODE XX=		10	90	40	
Pin Plating		10µ" Au	200µ" Sn/Pb	200µ" Sn	
<b>Fig. 3L</b>	<b>Single Row Socket, Left Hand Footprint</b> <b>Odd or Even # of pins</b>	851-XX-0__-30-001000			
	<b>Specify # of pins</b>	01-50			
<b>Fig. 3R</b>	<b>Single Row Socket, Right Hand Footprint</b> <b>Even # of pins</b>	851-XX-0__-30-002000			
	<b>Specify even # of pins</b>	02-50			
<b>Fig. 4</b>	<b>Double Row Socket, Even # of pins</b>	853-XX-__-30-001000			
	<b>Specify even # of pins</b>	004-100			
SPECIFY PLATING CODE XX=		13	93	99	43  44
Sleeve (Pin)		10µ" Au	200µ" Sn/Pb	200µ" Sn/Pb	200µ" Sn 200µ" Sn
Contact (Clip)		30µ" Au	30µ" Au	200µ" Sn/Pb	30µ" Au 200µ" Sn