


RoHS COMPLIANT

REVISIONS				
REV	ECN NO.	DESCRIPTION	APPROVED BY	DATE
A			ELTON MENG	2006-05-22

Product Specification

Material
 Insulator :Glass-Filled Thermoplastic
 PBT,UL94V-0 rates
 Contact :Brass
 Plated full gold or selected gold in mating area, 100u" min. tin-lead on termination area, with entire contact under-plated 50u" min. Nickel


Electrical
 Contact Resistance :30 milliohms
 Max at 1 AMP DC.
 Insulation Resistance :1000 megohms at 500 VDC
 Dielectric Withstanding Voltage : 500 VAC/rms 60Hz for 1 minute
 Current Rating :1 AMP
 Voltage Rating :250 VAC/rms 60Hz



A Type

AKSG-200-X-R

Contact Plating
G Gold Contact
Z Tinned



B Type

AKSO-200-X-R

Contact Plating
G Gold Contact
Z Tinned

DO NOT SCALE DRAWING

DIMENSIONS: <input type="checkbox"/> MM [INCH] <input type="checkbox"/> INCH [MM] <input checked="" type="checkbox"/> MM ONLY	CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE	
	UNLESS OTHERWISE SPECIFIED, GENERAL TOLERANCE: DECIMALS ANGLES .X ±0.38 [0.015] X° ±3° .X ±0.25 [0.010] .X° ±1.0° .XX ±0.13 [0.005]	
MATERIAL	CHECKED BY AND DATE JUSTIN XING 03-07-06	APPROVED BY AND DATE ELTON MENG 06-09-06
FINISH	THIRD ANGLE PROJECTION 	SCALE: 5 : 1
FILE NO.:		SIZE: A3
SHEET 1 OF 1		REV