

SKBI 64/F48

Order No.: 2264093

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2264093>

Plug-in card block, indirect connection in accordance with IEC 603/DIN 41612, with guide rails, engagement catches and ejector, standardized marking on both connection sides, fixing screws M 4, cross section 0.2 - 4 mm² rigid / 0.2 - 2.5 mm² flexible, 1 A, 125 V, 64-pos.

Commercial data	
EAN	4017918053918
Pack	1 Pcs.
Customs tariff	85369010
Weight/Piece	0.3219 KG
Catalog page information	Page 489 (CC-2007)

Product notes

WEEE/RoHS-compliant since:
06/22/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

Dimensions / positions

Length	66 mm
Height	162 mm
Width	118 mm

Pitch	5.08 mm
Number of positions	64
Hole diameter	4.2 mm
Screw thread	M 3
Tightening torque, min	0.5 Nm

Technical data

Connection in acc. with standard	EN-VDE
Nominal current I_N	4 A
Nominal voltage U_N	250 V (in acc. with DIN VDE 0110/Gr.B)
Stripping length	8 mm

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

Certificates / Approvals

Approval logo

**requested approbations**

Certification	GOST
---------------	------

Accessories


Item	Designation	Description
------	-------------	-------------

Assembly


2263007	SF-SKBI 64	Snap foot, for horizontal or vertical mounting of the SKBI plug-in card blocks, on the NS 35/7.5 mounting rail
---------	------------	--

Drawings

Dimensioned drawing



Schematic diagram



SKBI 64/F48 Order No.: 2264093

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2264093>

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2008 Phoenix Contact
Technical modifications reserved;