

Tightening torque/thread: 1.0 Nm/M 3  
Inspection Test Pattern Size: A 4

| Type            | Cat.-No. |       | Qty.p.pck. |
|-----------------|----------|-------|------------|
| <b>SR 4 DRL</b> | 41211.2  | beige | 100        |
| <b>SR 4 DRL</b> | 41211.5  | blue  | 100        |


### Ratings:

|               | UL          | CSA   | DIN-VDE | IEC   |
|---------------|-------------|-------|---------|-------|
| Rated Voltage | 600 V       | 600 V | 500 V   | 500 V |
| Rated Current | 20 A AWG 12 | 26 A  | 26 A    | 24 A  |

### Max Rated Cross Section

|                          |                         |
|--------------------------|-------------------------|
| Single Wire (solid)      | 0.2-4 mm <sup>2</sup>   |
| Stranded Wire (flexible) | 0.2-2.4 mm <sup>2</sup> |
| Wire Size                | AWG 22-12               |

| Dimensions      | TS 32   | TS 35   |
|-----------------|---------|---------|
| Lx B x H (mm)   | 67x6x52 | 67x6x47 |
| Stripped Length | 9 mm    |         |



Tightening torque/thread: 2.0 Nm/M 4  
Inspection Test Pattern Size: A 5

| Type         | Cat.-No. |       | Qty.p.pck. |
|--------------|----------|-------|------------|
| <b>SR 10</b> | 41005.2  | beige | 100        |
| <b>SR 10</b> | 41005.5  | blue  | 100        |

Additional colors available. See page 114.

### Ratings:

|               | UL         | CSA   | DIN-VDE | IEC   |
|---------------|------------|-------|---------|-------|
| Rated Voltage | 600 V      | 600 V | 750 V   | 800 V |
| Rated Current | 65 A AWG 8 | 55 A  | 61 A    | 57 A  |

### Max Rated Cross Section

|                          |                        |
|--------------------------|------------------------|
| Single Wire (solid)      | 0.2-10 mm <sup>2</sup> |
| Stranded Wire (flexible) | 0.2-10 mm <sup>2</sup> |
| Wire Size                | AWG 22-8               |

| Dimensions      | TS 32   | TS 35   |
|-----------------|---------|---------|
| Lx B x H (mm)   | 48x8x52 | 48x8x47 |
| Stripped Length | 12 mm   |         |

| Type:          | Cat.-No.                    | Qty.p.pck. | Terminal accessories                        | Type:          | Cat.-No.                    | Qty.p.pck. |
|----------------|-----------------------------|------------|---|----------------|-----------------------------|------------|
| AP 2.5 RL      | 2575.2 beige<br>2575.5 blue | 50         | End plate                                   | AP 2.5-10      | 2001.2 beige<br>2001.5 blue | 50         |
|                |                             |            | Isolation partition                         | TW 2.5-10      | 2002.2 beige<br>2002.5 blue | 50         |
| TRS 1          | 2003.2 beige                | 100        | Separator                                   | TRS 1          | 2003.2 beige                | 100        |
| ES 32/35 Combi | 1424.2 beige                |            | End bracket                                 | ES 32/35 Combi | 1424.2 beige                |            |
| ES 32/K/ST     | 2827.0                      | 50         |   | ES 32/K/ST     | 2827.0                      | 50         |
| ES 35/2/K      | 2826.2 beige                |            | End bracket                                 | ES 35/2/K      | 2826.2 beige                |            |
| ES 35/K/ST     | 2828.0                      | 50         |   | ES 35/K/ST     | 2828.0                      | 50         |
| STB 14/2.3     | 2006.0                      | 50         | Test socket                                 | STB 14/4       | 2050.0                      | 50         |
| PS 2.3         | 2007.0                      | 20         | Test plug                                   | PS 4           | 2051.0                      | 20         |
| QL 2           | 2008.0                      | 50         | Switchable link                             | QL 2           | 2053.0                      | 50         |
| VH 19          | 2009.0                      | 100        | Connection sleeve                           | VH 19          | 2009.0                      | 100        |
| BS M 3x25      | 2010.0                      | 100        | Screw                                       | BS M 3x25      | 2010.0                      | 100        |
| AD 4           | 2011.0                      | 50         | Warning tag (German)                        | AD 4           | 2054.0                      | 50         |
| AD 4 E         | 2494.0                      | 50         | Warning tag (English)                       | AD 4 E         | 2495.0                      | 50         |
| BSK M 3x22     | 2012.0                      | 100        | Plastic screw for warning tag               | BSK M 3x22     | 2012.0                      | 100        |
| Q2/Q1 2        | 2019.0/2740.2               | 50         | Cross-connection/Insulated cross-connection | Q2/Q1 2        | 2060.0/2750.2               | 50         |
| Q3/Q1 3        | 2020.0/2741.2               | 50         | Cross-connection/Insulated cross-connection | Q3/Q1 3        | 2061.0/2751.2               | 50         |
| Q4/Q1 4        | 2021.0/2742.2               | 20         | Cross-connection/Insulated cross-connection | Q4/Q1 4        | 2062.0/2752.2               | 20         |
| Q10/Q1 10      | 2022.0/2743.2               | 10         | Cross-connection/Insulated cross-connection | Q10/Q1 10      | 2063.0/2753.2               | 10         |