

tightening torque/thread 0.7 Nm/M 2.5 Inspection Test Pattern Size A 3

| Type             | Cat.-No. | beige | Qty.p.pck |
|------------------|----------|-------|-----------|
| <b>SRD 2.5 V</b> | 41209.2  |       | 100       |


### Ratings:

|               | UL          | CSA   | DIN-VDE | IEC   |
|---------------|-------------|-------|---------|-------|
| Rated Voltage | 300 V       | 300 V | 500 V   | 500 V |
| Rated Current | 20 A AWG 14 | 20 A  | 26 A    | 24 A  |

### Max Rated Cross Section

|                          |                         |
|--------------------------|-------------------------|
| Single Wire (solid)      | 0.2-4 mm <sup>2</sup>   |
| Stranded Wire (flexible) | 0.2-2.5 mm <sup>2</sup> |
| Wire Size                | AWG 22-14               |

| Dimensions      | TS 32   | TS 35   |
|-----------------|---------|---------|
| LxBxH (mm)      | 59x5x65 | 59x5x60 |
| Stripped Length | 7 mm    |         |



tightening torque/thread 1.0 Nm/M 3 Inspection Test Pattern Size A 4

| Type         | Cat.-No. | beige | Qty.p.pck |
|--------------|----------|-------|-----------|
| <b>SRD 4</b> | 41020.2  |       | 100       |
| <b>SRD 4</b> | 41020.5  | blue  | 100       |

Additional colors available. See page 114.

### Ratings:

|               | UL          | CSA   | DIN-VDE | IEC   |
|---------------|-------------|-------|---------|-------|
| Rated Voltage | 300 V       | 300 V | 500 V   | 500 V |
| Rated Current | 30 A AWG 12 | 27 A  | 34 A    | 32 A  |

### Max Rated Cross Section

|                          |                       |
|--------------------------|-----------------------|
| Single Wire (solid)      | 0.2-4 mm <sup>2</sup> |
| Stranded Wire (flexible) | 0.2-4 mm <sup>2</sup> |
| Wire Size                | AWG 22-12             |

| Dimensions      | TS 32   | TS 35   |
|-----------------|---------|---------|
| LxBxH (mm)      | 59x6x65 | 59x6x60 |
| Stripped Length | 9 mm    |         |

| Type:          | Cat.-No.                    | Qty.p.pck. | Terminal accessories          | Type:          | Cat.-No.                    | Qty.p.pck. |
|----------------|-----------------------------|------------|-------------------------------|----------------|-----------------------------|------------|
| AP 4           | 2101.2 beige<br>2101.5 blue | 20         | End plate                     | AP 4           | 2101.2 beige<br>2101.5 blue | 20         |
|                |                             |            | Isolation partition           |                |                             |            |
| TRS 3          | 2566.2 beige                | 100        | Separator                     | TRS 3          | 2566.2 beige                | 100        |
| ES 32/35 Combi | 1424.2 beige                |            | End bracket                   | ES 32/35 Combi | 1424.2 beige                |            |
| ES 32/K/ST     | 2827.0                      | 50         |                               | ES 32/K/ST     | 2827.0                      | 50         |
| ES 35/2/K      | 2826.2 beige                |            | End bracket                   | ES 35/2/K      | 2826.2 beige                |            |
| ES 35/K/ST     | 2828.0                      | 50         |                               | ES 35/K/ST     | 2828.0                      | 50         |
| STB 8.5/2.3    | 2075.0                      | 50         | Test socket                   | STB 8.5/2.3    | 2075.0                      | 50         |
| PS 2.3         | 2007.0                      | 20         | Test plug                     | PS 2.3         | 2007.0                      | 20         |
|                |                             |            | Switchable link               |                |                             |            |
|                |                             |            | Connection sleeve             |                |                             |            |
|                |                             |            | Screw                         |                |                             |            |
|                |                             |            | Warning tag (German)          | AD 4           | 2079.0                      | 50         |
|                |                             |            | Warning tag (English)         | AD 4 E         | 2493.0                      | 50         |
|                |                             |            | Plastic screw for warning tag | BSK M 2.5x20   | 2080.0                      | 100        |
| Q2             | 2567.0                      | 50         | Cross-Connection              | Q2             | 2087.0                      | 50         |
| Q3             | 2568.0                      | 50         | Cross-Connection              | Q3             | 2088.0                      | 50         |
| Q4             | 2569.0                      | 20         | Cross-Connection              | Q4             | 2089.0                      | 20         |
| Q10            | 2570.0                      | 10         | Cross-Connection              | Q10            | 2090.0                      | 10         |