

GSTB 3/ 3-ST-7,62

Order No.: 1750171

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1750171>Plug, nominal current: 20 A, rated voltage: 500 V, pitch: 7.62 mm, no.
of positions: 3**Commercial data**

EAN	4017918028275
Pack	50 Pcs.
Customs tariff	85369010
Weight/Piece	0.01058 KG

Product notesWEEE/RoHS-compliant since:
01/01/2003

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Certificates / Approvals

Approval logo

**UL**

Nominal voltage U_N	300 V
Nominal current I_N	10 A
AWG/kcmil	30-14
Certification	UL

Accessories		
Item	Designation	Description
General		
1750142	CS-STB	Coding profile, for plugging into the coding ribs of the plug at a later date, insulating material, color: Red
Marking		
1051993	B-STIFT	Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm
1401844	BN-ZB 7,5/WH:UNBEDRUCKT	BN Zack strip, unprinted: 10-section, for individual labeling with M-PEN or CMS system, sufficient for labeling 100 terminal blocks
1400052	BNB-ZB 7,5,LGS:FORTL.ZAHLEN	BNB Zack strip, printed horizontally: 10-section, divisible, with consecutive numbers, 1-10, 11-20 etc. up to 991-1000
1400036	BNB-ZB 7,5,LGS:L1-N,PE	BNB Zack strip, printed horizontally: 10-section, divisible, L1, L2, L3, N, PE, L1, L2, L3, N, PE
1400049	BNB-ZB 7,5,LGS:U-N	BNB Zack strip, printed horizontally: 10-section, divisible, U, V, W, N, U, V, W, N
Plug/Adapter		
0201731	MPS-IH BK	Insulating sleeve (black), for MPS metal part to be ordered separately (0201744)
0201702	MPS-IH GN	Insulating sleeve (green), for MPS metal part to be ordered separately (0201744)
0201676	MPS-IH RD	Insulating sleeve (red), for MPS metal part to be ordered separately (0201744)
0201663	MPS-IH WH	Insulating sleeve (white), for MPS metal part to be ordered separately (0201744)
0201744	MPS-MT	Test plug, consisting of: Metal part for 2.3 mm diameter socket hole
0201647	RPS	Reducing plug, for transition from 4 mm diameter test plug socket, insulation: gray

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>



© 2008 Phoenix Contact
Technical modifications reserved;