

## KDS 3-SILA 250

Order No.: 1780170

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1780170>

Printed circuit terminal block, nominal current: 6.3 A, rated voltage: 320 V, pitch: 10.16 mm, no. of positions: 1, mounting: Soldering, type of connection: Screw connection, connection direction from the conductor to the PCB: 0°

### Commercial data

EAN	4017918040758
Pack	50 Pcs.
Customs tariff	85369010
Weight/Piece	0.01339 KG

### Product notes

WEEE/RoHS-compliant since:  
01/01/2003



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Certificates / Approvals

#### Approval logo



#### UL

Nominal voltage $U_N$	300 V
Nominal current $I_N$	10 A

---

AWG/kcmil	28-12
Certification	UL

**Accessories**

Item	Designation	Description
<b>General</b>		
1780125	EB 8- KDS 3-SI	
<b>Marking</b>		
1400201	BNB-ZB 5,LGS:FORTL.ZAHLEN	BNB Zack marker strip, labeled horizontally: 10-section, divisible, with consecutive numbers, 1-10, 11-20 etc. up to 491-500
<b>Plug/Adapter</b>		
0201744	MPS-MT	Test plug, consisting of: Metal part for 2.3 mm diameter socket hole
0201647	RPS	Reducing plug, for transition from 4 mm diameter test plug socket, insulation: gray
<b>Tools</b>		
1205121	SZG 0,6X3,5	Screwdriver, bladed. with stepped blade, matches all screw terminal blocks with 2.3 mm diameter test socket screws and test plug sockets, blade width: 3.5 mm

**Address**

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 00  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2008 Phoenix Contact  
Technical modifications reserved;