



#### General ordering data

|                  |   |
|------------------|---|
| Order No.        | 1715300000  |
| Part designation | LM5.00/3/135 SW   |
| Version          | PCB terminal, Clamping yoke connection,<br>Soldered connection, Clamping range, max.: 2.5<br>mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 3, 135°, Box |
| EAN              | 4008190365189   |
| Qty.             | 500 pc(s).  |

#### System parameters

|                                 |                          |
|---------------------------------|--------------------------|
| Product family                  | System LM                |
| Conductor connection system     | Clamping yoke connection |
| Fitted to PCB                   | Soldered connection      |
| Outgoing direction of conductor | 135°                     |
| Pitch                           | 5 mm                     |
| Pitch in inch                   | 0.197 inch               |
| No. of poles                    | 3                        |
| Fitted by customer              | yes                      |
| Max. adjacent poles per row     | 24                       |
| No. of rows                     | 1                        |
| Solder pin length               | 3.5 mm                   |
| Dia. of fitting hole            | 1.3 mm                   |
| Fitting hole tolerance          | + 0.1 mm                 |
| No. of solder pins per pole     | 1                        |

#### System parameters

|   |                        |
|---|------------------------|
| Screwdriver blade                         | 0.6 x 3.5              |
| Screwdriver blade standard                | DIN 5264               |
| Tightening torque, min.                   | 0.4 Nm                 |
| Tightening torque, max.                   | 0.5 Nm                 |
| Clamping screw                            | M 2.5                  |
| Stripping length                          | 6 mm                   |
| L1 in mm                                  | 10 mm                  |
| L1 in inch                                | 0.394 inch             |
| Electric shock protection to DIN VDE 0470 | IP 20                  |
| Electric shock protection to DIN VDE 0470 | Safe from finger touch |

#### Material data

|                               |                     |
|-------------------------------|---------------------|
| Insulating material           | Wemid (PA)          |
| Colour                        | black               |
| colour chart                  | Similar to RAL 9011 |
| Insulating material group     | I                   |
| Flammability class UL 94      | V-0                 |
| CTI                           | >= 600              |
| Temperature of glow-wire test | 750 °C              |
| Duration of glow-wire test    | 30 S                |
| Contact base material         | Copper alloy        |
| Contact surface               | tinned              |
| Storage temperature, min.     | -25 °C              |
| Storage temperature, max.     | 55 °C               |

#### Connectable conductors

|   |                        |
|---|------------------------|
| Clamping range, min.                              | 0.2 mm <sup>2</sup>    |
| Clamping range, max.                              | 2.5 mm <sup>2</sup>    |
| AWG, min.   | 24                     |
| AWG, max.   | 14                     |
| O.D. of conductor insulation, max.                | 2.9 mm                 |
| Solid, min. H05(07) V-U                           | 0.2 mm <sup>2</sup>    |
| Solid, max. H05(07) V-U                           | 2.5 mm <sup>2</sup>    |
| Flexible, min. H05(07) V-K                        | 0.2 mm <sup>2</sup>    |
| Flexible, max. H05(07) V-K                        | 1.5 mm <sup>2</sup>    |
| With wire end ferrule, acc. to DIN 46 228/1, min. | 0.25 mm <sup>2</sup>   |
| With wire end ferrule, acc. to DIN 46 228/1, max. | 1.5 mm <sup>2</sup>    |
| w. plastic collar ferrule, DIN 46228 pt 4, min.   | 0.25 mm <sup>2</sup>   |
| w. plastic collar ferrule, DIN 46228 pt 4, max.   | 1.5 mm <sup>2</sup>    |
| Gauge to EN 60999 a x b; ø                        | 2.4 mm x 1.5 mm; 1.9mm |

#### DIN IEC rating data

|  |        |
|--|--------|
| Rated current, min. No. pins (Tu=20°C)                       | 17.5 A |
| Rated current, max. No. pins (Tu=20°C)                       | 16 A   |
| Rated current, min. No. pins (Tu=40°C)                       | 17.5 A |
| Rated current, max. No. pins (Tu=40°C)                       | 14.2 A |
| Rated voltage for overvoltage class/pollution severity II/2  | 630 V  |
| Rated voltage for overvoltage class/pollution severity III/2 | 320 V  |

#### DIN IEC rating data

|  |                   |
|--|-------------------|
| Rated voltage for overvoltage class/pollution severity III/3                   | 250 V             |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2  | 4 kV              |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV              |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV              |
| Short-time withstand current resistance  | 3 x 1s with 120 A |

#### CSA rating data

|                                    |       |
|------------------------------------|-------|
| Rated voltage, user group D        | 300 V |
| Rated current, user group D        | 10 A  |
| AWG conductor (field wiring), min. | 24    |
| AWG conductor (field wiring), max. | 14    |

#### UL 1059 rating data

|                             |       |
|-----------------------------|-------|
| Rated voltage, user group D | 300 V |
| Rated current, user group D | 10 A  |
| AWG conductor, min.         | 24    |
| AWG conductor, max.         | 14    |

#### Approvals

Approvals institutes



#### Downloads

|                                       |        |
|---------------------------------------|--------|
| CAD Library (P-CAD Format - Standard) | LM.lib |
|---------------------------------------|--------|

#### Classifications

|            |          |
|------------|----------|
| ETIM 2.0   | NK       |
| ETIM 3.0   | EC001284 |
| eClass 4.1 | NK       |
| eClass 5.0 | NK       |
| eClass 5.1 | NK       |

### Similar products

| Order No.  | Part designation    | Version   |
|------------|---------------------|---|
| 1715350000 | LM5.00/2/135 OR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 2, 135°, Box |
| 1715290000 | LM5.00/2/135 SW     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 2, 135°, Box |
| 1913440000 | LM 5.00/2/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 2, 135°, Box |
| 1715410000 | LM5.00/2/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 2, 135°, Box |
| 1715360000 | LM5.00/3/135 OR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 3, 135°, Box |
| 1913450000 | LM 5.00/3/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 3, 135°, Box |
| 1715420000 | LM5.00/3/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 3, 135°, Box |
| 1845390000 | LM5.00/4/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 4, 135°, Box |
| 9993510000 | LM5.00/4/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 4, 135°, Box |
| 1913460000 | LM 5.00/4/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 4, 135°, Box |
| 1913330000 | LM 5.00/4/135 GN    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 4, 135°, Box |
| 1845400000 | LM5.00/5/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 5, 135°, Box |
| 9993520000 | LM5.00/5/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 5, 135°, Box |
| 1913470000 | LM 5.00/5/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 5, 135°, Box |
| 1913340000 | LM 5.00/5/135 GN    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 5, 135°, Box |
| 1845410000 | LM5.00/6/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 6, 135°, Box |

|            |                      |  |
|------------|----------------------|--|
| 9993530000 | LM5.00/6/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 6, 135°, Box  |
| 1913480000 | LM 5.00/6/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 6, 135°, Box  |
| 1913350000 | LM 5.00/6/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 6, 135°, Box  |
| 1845420000 | LM5.00/7/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 7, 135°, Box  |
| 9993540000 | LM5.00/7/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 7, 135°, Box  |
| 1913360000 | LM 5.00/7/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 7, 135°, Box  |
| 1913490000 | LM 5.00/7/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 7, 135°, Box  |
| 1845430000 | LM5.00/8/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 8, 135°, Box  |
| 9993550000 | LM5.00/8/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 8, 135°, Box  |
| 1913500000 | LM 5.00/8/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 8, 135°, Box  |
| 1913370000 | LM 5.00/8/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 8, 135°, Box  |
| 1845440000 | LM5.00/9/135 3.5OR   | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 9, 135°, Box  |
| 9993560000 | LM5.00/9/135 3.5 SW  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 9, 135°, Box  |
| 1913510000 | LM 5.00/9/135 GR     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 9, 135°, Box  |
| 1913400000 | LM 5.00/9/135 GN     | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 9, 135°, Box  |
| 1845450000 | LM5.00/10/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 10, 135°, Box |
| 9993570000 | LM5.00/10/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 10, 135°, Box |

|            |                      |  |
|------------|----------------------|--|
| 1913520000 | LM 5.00/10/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 10, 135°, Box |
| 1913410000 | LM 5.00/10/135 GN    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 10, 135°, Box |
| 1845460000 | LM5.00/11/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 11, 135°, Box |
| 9993580000 | LM5.00/11/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 11, 135°, Box |
| 1913530000 | LM 5.00/11/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 11, 135°, Box |
| 1913420000 | LM 5.00/11/135 GN    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 11, 135°, Box |
| 1845470000 | LM5.00/12/135 3.5OR  | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 12, 135°, Box |
| 9993590000 | LM5.00/12/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 12, 135°, Box |
| 1913540000 | LM 5.00/12/135 GR    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 12, 135°, Box |
| 1913430000 | LM 5.00/12/135 GN    | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 12, 135°, Box |
| 9993600000 | LM5.00/13/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 13, 135°, Box |
| 9993610000 | LM5.00/14/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 14, 135°, Box |
| 9993620000 | LM5.00/15/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 15, 135°, Box |
| 9993630000 | LM5.00/16/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 16, 135°, Box |
| 9993640000 | LM5.00/17/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 17, 135°, Box |
| 9993650000 | LM5.00/18/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 18, 135°, Box |
| 9993660000 | LM5.00/19/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 19, 135°, Box |

|            |                      |  |
|------------|----------------------|--|
| 9993670000 | LM5.00/20/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 20, 135°, Box |
| 9993680000 | LM5.00/21/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 21, 135°, Box |
| 9993690000 | LM5.00/22/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 22, 135°, Box |
| 9993700000 | LM5.00/23/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 23, 135°, Box |
| 9993710000 | LM5.00/24/135 3.5 SW | PCB terminal, Clamping yoke connection, Soldered connection, Clamping range, max.: 2.5 mm <sup>2</sup> , Pitch: 5.00 mm, No. of poles: 24, 135°, Box |