



**Größe 6,3  
FASTON-Flachstecker**  
(Fortsetzung)




**Size 6.3  
FASTON Tabs**  
(continued)

Typ Type	Anzahl Einheiten No. of Pieces	Bohrungs- durchmesser Bore Hole Diameter mm	Abmessungen Dimensions mm				Bestell-Nummern/Part Numbers				Mit Rastloch With Hole		
			B	W	L	E	T	CuZn Brass	CuZn, verzinkt Brass, tin plated	Sonstige Oberfläche Other Finish			
K	1	3,3	—	6,3	6,3	—	8,0	—	41477-0	CuZn, vern./Brass, nickel plated	151385-1	—	
		3,3	—	6,3	6,3	—	8,0	—	—	Stahl, verz./Steel, tin plated	42784-2	—	
		3,3	—	6,3	6,3	—	8,0	—	—	—	—	—	
		3,7	—	6,3	12,0	—	8,0	140757-1	140757-2	—	—	—	
		4,1	—	6,3	12,0	—	8,0	—	140608-0	—	—	—	
		4,1	—	6,3	10,5	—	8,0	142241-1	142241-2	—	—	—	
		4,1	—	6,3	12,0	—	8,0	181951-1	—	—	—	x	
		4,4	—	6,3	10,5	—	8,0	41616-0	42577-1	—	—	—	
		5,2	—	6,3	10,5	—	8,0	140758-0	140758-2	—	—	—	
	2	3,3	—	6,3	6,3	—	17,5	41288-0	41478-0	—	—	—	
		4,1	—	6,3	12,0	—	17,5	140609-0	140610-0	CuZn, vern./Brass, nickel plated	150636-0	—	
		4,1	—	6,3	12,0	—	17,5	181956-1	—	—	—	x	
		4,4	—	6,3	8,0	—	17,5	41617-0	—	—	—	—	
		3	3,3	—	6,3	6,3	—	27,1	41289-0	—	—	—	—
			4,1	—	6,3	10,5	—	27,1	140611-0	140612-0	—	—	—
			4,4	—	6,3	6,3	—	36,6	41369-0	41484-0	—	—	—
		4	3,3	—	6,3	6,3	—	36,6	41623-0	—	—	—	—
			4,1	—	6,3	12,0	—	—	280275-1*	—	—	—	—
Streifen/Strip	4,1	—	6,3	10,5	—	—	—	280275-2	—	—	—		

**zum Anschrauben**



**K**



**L**

**Screw-Type**

Lochmittenabstand  $9,52 \pm 0,07$   
Center Hole Distance  $9,52 \pm 0,07$

Typ Type	Anzahl Einheiten No. of Pieces	Bohrungs- durchmesser Bore Hole Diameter mm	Abmessungen Dimensions mm				Bestell-Nummern/Part Numbers				Mit Rastloch With Hole		
			W	L	E	T	CuZn Brass	CuZn, verzinkt Brass, tin plated	Sonstige Oberfläche Other Finish				
K	1	2,5	6,3	6,3	2,4	8,0	41339-0	41204-0	CuZn, vern./Brass, silver plated	60565-1	x		
		3,1	6,3	10,3	4,0	8,0	182936-1*	182936-2*	—	—	—		
		3,1	6,3	10,3	4,0	8,0	140732-1	140732-2	—	—	—		
		3,7	6,3	10,3	4,0	8,0	181952-1	181952-2	—	—	x		
		4,1	6,3	10,1	4,0	8,0	141879-1	141879-2*	—	—	—		
		4,2	6,3	10,3	4,0	8,0	181953-1*	181953-2*	—	—	—		
		4,2	6,3	10,3	4,0	8,0	140793-1	140793-2	—	—	x		
		4,4	6,3	8,5	4,3	8,0	42214-1	42214-2	—	—	—		
		—	6,3	16,0	—	7,4	—	—	—	Stahl/Steel	151393-1	—	
	Streifen/Strip	4,1	6,3	10,5	4,0	—	280272-1*	—	Stahl, vern./Steel, nickel plated	151393-2	—		
	L	1	3,0	6,3	10,5	—	8,0	140773-0	—	—	—	x	
			3,3	6,3	7,0	—	8,0	41290-0	41480-0	—	—	—	
			4,1	6,3	10,5	—	8,0	182937-1*	182937-2*	—	—	—	
			4,1	6,3	10,5	—	8,0	141878-1	141878-2	—	—	x	
			4,3	6,3	7,0	—	8,0	41619-0	42802-1	—	—	—	
			3,3	6,3	7,0	—	17,5	41291-0	41481-0	—	—	—	
			2	4,1	6,3	10,5	—	17,5	140615-0	140616-0	—	—	—
				4,1	6,3	10,5	—	17,5	144185-1	—	—	—	x
4,3				6,3	7,0	—	17,5	41620-0	—	—	—	—	
3		3,3		6,3	7,0	—	27,1	41292-0	41482-0	—	—	—	
		4		3,3	6,3	7,0	—	36,6	41370-0	41485-0	—	—	
		4,3		6,3	7,0	—	36,6	—	60171-1	—	—	—	
6		3,3		6,3	7,0	—	46,1	—	42115-3	—	—	—	
		3,3		6,3	7,0	—	55,6	—	42115-5	—	—	—	
		6,7		6,3	19,1	—	55,6	150738-1	150738-2	—	—	—	
		7	3,3	6,3	7,0	—	65,2	—	42115-2	—	—		
		9	3,3	6,3	7,0	—	84,2	41708-0	—	—	—		
		12	3,3	6,3	7,0	—	112,8	—	42115-1	—	—		
	Streifen/Strip	3,1	6,3	10,5	—	—	281251-1*	—	—	—	—		
	4,1	6,3	10,5	—	—	282054-1*	—	—	—	—			
	4,1	6,3	10,5	—	—	140722-1	140722-2	CuZn, vern./Brass, nickel plated	150637	—			

Für Positive Lock werden Flachstecker mit Rastloch benötigt  
\* Mit Rastloch für Positive Lock Flachsteckhülse

Tabs with hole are required for Positive Lock  
\* With hole for Positive Lock Receptacle