


# Female Disconnects - Non-Insulated Butted Seam Flag



Product Number <sup>†</sup>	UPC (054007-)	Wire Range (AWG)	Mates with Male Tab Width(W') x Thickness	L	Barrel Length	Barrel I.D.	Terminals per:	
							Carton	Case
MU18-187DF/FLAGX*	22138	22-18	0.187 x 0.020	0.46	0.20	0.075	100	500
MU18-187DF/FLAGK*	01302	22-18	0.187 x 0.020	0.46	0.20	0.075	—	1000
MU18-250DF/FLAGX	22146	22-18	0.250 x 0.032	0.50	0.25	0.075	100	500
MU18-250DF/FLAGK	01303	22-18	0.250 x 0.032	0.50	0.25	0.075	—	1000
MU14-187DF/FLAGX*	22948	16-14	0.187 x 0.020	0.47	0.20	0.095	100	500
MU14-187DF/FLAGK*	01778	16-14	0.187 x 0.020	0.47	0.20	0.095	—	1000
MU14-250DF/FLAGX	22955	16-14	0.250 x 0.032	0.51	0.26	0.095	100	500
MU14-250DF/FLAGK	01779	16-14	0.250 x 0.032	0.51	0.26	0.095	—	1000
MU10-250DF/FLAGK	02245	12-10	0.250 x 0.032	0.63	0.25	0.175	—	500


\* Not ULListed or CSACertified



**MU18-187DF/FLAG**


Wire Range  
Suggested Mate

22-18  
0.187 Male Tab




**MU18-250DF/FLAG**

22-18  
0.250 Male Tab




**MU14-187DF/FLAG**

16-14  
0.187 Male Tab



**MU14-250DF/FLAG**

16-14  
0.250 Male Tab



**MU10-250DF/FLAG**

12-10  
0.250 Male Tab