



型番	スタッド	H* ±0.2φ	マキソク
C-170737-1	8MM	8.6	38-8
C-170737-2	10MM	10.7	38-10
C-170737-3	2MM	13.2	38-12

DIMENSIONS IN MM DO NOT SCALE PRINT

G	REVISED (P-DWG RET-A)	S.O	3/17/70
F	REVISED (P-DWG REV. A)	T.K	4/1/70
E	REVISED (P-DWG REV. D)	Y.I	3/11/70
D	REVISED (P-DWG REV. A)	J.A	11/23/72
C	ADD JIS マ (P-DWG REV. A)	K.K	3/24/71
B	REVISED (P-DWG REV. A)	K.K R.S	10/21/72
A	DELETES MARK * (P-DWG REV. D)	K.K	4/1/70
0	RELEASED (P-DWG REV. 0)	K.K	3/4/70
4	LTR REVISION RECORD	DR	OK DATE
CR	K. Kobayashi 3/17/70 M. Kobayashi 3/17/70 H. Kobayashi 3/17/70		

G1. DELETE MARK @ JSA-T160 J.J 4/3/70

1970 JSA USA, INC. ALL RIGHTS RESERVED. AMP PRODUCTS COVERED BY PATENTS AND/OR PATENT PENDING.

MATERIAL: 電気銅

FINISH: 丸孔, 錫めっき

WIRE RANGE: 26-22 AWG 2

INSULATION DIA: —

TRADE MARK:

TOKYO, JAPAN

CLASS: —

TYPE: ヴィストラント

TOLERANCE: ±0.1 EXCEPT AS NOTED

SCALE: 2-1

LOC: J A

REV: C-170737 G1

NAME: 丸型端子