



LOC	DIST	REV	DATE	APPD
G	14	A	REVISED PER 0720-0230-93	J. HECKLEY

METPRIO
DIMENSIONS LISTED IN mm [INCHES]

AMP WIRE RANGE 12-10 AWG STRAINED	UL E13288 Listed
• LR7189 Certified	MILITARY P/N AND CLASS
NOT CERTIFIED	NOT APPLICABLE

△ STAMP AMP 12-10* APPROX AS SHOWN

AMP INCORPORATED
CUSTOMER SERVICE SYSTEMS

FOR ADDITIONAL
PRODUCT INFORMATION OR
COPIES OF DRAWINGS
AND TECHNICAL DOCUMENTS
1-800-522-6752

FOR APPLICATION
TOOLING INFORMATION
1-800-722-1111

FOR ORDER ENTRY
1-800-526-5142

PRODUCT INFORMATION CENTER
TOOLING ASSISTANCE CENTER

MAX RECOMMENDED OPERATING
TEMPERATURE: 170°C MAX

VOLTAGE RATING:
NOT APPLICABLE

WIRE CROSS SECTIONAL AREA RANGE:
2.62-6.64mm² [5.180-13.100] CIR MILS
STRAINED

FINISH: TIN PLATE
0.00254L.0001001 MIN
THK PER MIL-T-10727

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN - - - - - INCHES - - TOLERANCES ON - - 2 PLG DEC ± - - 3 PLG DEC ± - - ANGLES ± - - PATTERNAL	DR 2-9-93 TA BRINKMAN	AMP Incorporated Harrisburg, PA 17105-3608
APPRO 2-9-93 DE MILLER	CHK 2-9-93 DA PATTERSON	
APPRO 2-9-93 J. HECKLEY	APPRO 2-9-93 J. HECKLEY	
APPLICATION SPEC	WEIGHT	NAME: TERMINAL, RING TONGUE, BUDGET SIZE: C CAGE CODE: 00779 DRAWING NO: G-32882 SCALE: 10:1 SHEET: 1 OF 1

CUSTOMER DRAWING