




SNAP SPADE TERMINALS



Material: Copper




Krimptite®



Insulkrimp®
(PVC Insulation)

| Wire Range AWG (mm ²) | Stud Size S | Maximum Width W | Minimum Clearance C | Loose Piece Order No. | Mylar Tape Order No. | Maximum Length L | Loose Piece Order No. | Mylar Tape Order No. | Maximum Length L |
|-----------------------------------|-------------|-----------------|---------------------|-----------------------|----------------------|------------------|-----------------------|----------------------|------------------|
| 18-22 (0.80-0.35) | 5 (3) | 6.60 (.260) | 5.80 (.230) | 19098-0017 | 19098-0077 | 14.80 (.585) | 19099-0007 | 19099-0008 | 20.60 (.810) |
| | 5-6 (3-3.5) | 6.60 (.260) | 5.80 (.230) | 19098-0018 | 19098-0019 | 14.80 (.585) | 19099-0009 | 19099-0010 | 20.60 (.810) |
| | | 6.80 (.270) | 6.00 (.235) | 19098-0011 | 19098-0012 | 16.40 (.645) | 19099-0001 | 19099-0002 | 22.10 (.870) |
| | 8 (4) | 7.60 (.300) | 6.00 (.235) | 19098-0013 | 19098-0014 | 16.60 (.655) | 19099-0003 | 19099-0004 | 22.40 (.880) |
| | | 8.10 (.320) | 6.60 (.261) | 19098-0023 | 19098-0080 | 16.40 (.646) | 19099-0013 | 19099-0014 | 22.10 (.871) |
| | 10 (-) | 8.60 (.338) | 6.00 (.235) | 19098-0015 | 19098-0016 | 17.90 (.705) | 19099-0005 | 19099-0006 | 23.60 (.930) |
| 14-16 (2.00-1.30) | 5 (3) | 6.60 (.260) | 5.80 (.230) | 19098-0041 | 19098-0042 | 14.80 (.585) | 19099-0025 | 19099-0026 | 20.60 (.810) |
| | 5-6 (3-3.5) | 6.60 (.260) | 5.80 (.230) | 19098-0043 | 19098-0044 | 14.80 (.585) | 19099-0027 | 19099-0028 | 20.60 (.810) |
| | | 6.80 (.270) | 6.00 (.235) | 19098-0034 | 19098-0035 | 16.40 (.645) | 19099-0017 | 19099-0018 | 22.10 (.870) |
| | 8 (4) | 7.60 (.300) | 6.00 (.235) | 19098-0036 | 19098-0037 | 16.60 (.655) | 19099-0019 | 19099-0020 | 22.40 (.880) |
| | | 8.10 (.320) | 6.60 (.261) | 19098-0047 | 19098-0048 | 16.40 (.646) | 19099-0032 | 19099-0033 | 22.10 (.871) |
| | 10 (-) | 8.60 (.338) | 6.00 (.235) | 19098-0038 | 19098-0040 | 17.90 (.705) | 19099-0022 | 19099-0024 | 23.60 (.930) |
| 10-12 (5.00-3.30) | 5-6 (3-3.5) | 8.60 (.340) | 6.60 (.261) | 19098-0024 | 19098-0081 | 17.60 (.694) | 19099-0015 | 19099-0016 | 23.30 (.919) |
| | | 8.60 (.340) | 6.60 (.261) | 19098-0049 | 19098-0050 | 17.60 (.694) | 19099-0034 | 19099-0035 | 23.30 (.919) |
| | 8 (4) | 6.60 (.260) | 5.80 (.230) | 19098-0069 | 19098-0070 | 16.90 (.664) | 19099-0044 | 19099-0045 | 24.30 (.995) |
| | | 7.60 (.300) | 7.80 (.305) | 19098-0061 | 19098-0062 | 20.50 (.806) | 19099-0036 | 19099-0037 | 27.90 (1.097) |
| | 10 (-) | 8.40 (.330) | 7.80 (.305) | 19098-0063 | 19098-0064 | 21.20 (.834) | 19099-0038 | 19099-0039 | 28.50 (1.125) |
| | | 8.10 (.320) | 6.60 (.261) | | | | 19099-0048 | 19099-0049 | 25.70 (1.016) |
| 1/4 (6) | 8.40 (.330) | 7.80 (.305) | 19098-0065 | 19098-0066 | 21.70 (.854) | 19099-0040 | 19099-0041 | 29.10 (1.145) | |
| | | 8.60 (.340) | 6.60 (.261) | 19098-0074 | 19098-0075 | 19.60 (.773) | 19099-0050 | 19099-0051 | 27.00 (1.064) |
| | | 10.80 (.425) | 9.50 (.375) | 19098-0067 | 19098-0086 | 24.90 (.980) | 19099-0042 | 19099-0063 | 32.30 (1.271) |



Avikrimp®
(Nylon Insulation)

Material: Copper

| Wire Range AWG (mm ²) | Stud Size S | Maximum Width W | Minimum Clearance C | Loose Piece Order No. | Mylar Tape Order No. | Maximum Length L |
|-----------------------------------|-------------|-----------------|---------------------|-----------------------|----------------------|------------------|
| 18-22 (0.80-0.35) | 5 (3) | 6.60 (.260) | 5.80 (.230) | 19115-0007 | 19115-0008 | 20.60 (.810) |
| | 5-6 (3-3.5) | 6.60 (.260) | 5.80 (.230) | 19115-0009 | 19115-0010 | 20.60 (.810) |
| | | 6.80 (.270) | 6.00 (.235) | 19115-0001 | 19115-0002 | 22.10 (.870) |
| | 8 (4) | 7.60 (.300) | 6.00 (.235) | 19115-0003 | 19115-0004 | 22.40 (.880) |
| | | 8.10 (.320) | 6.60 (.261) | 19115-0012 | 19115-0013 | 22.10 (.871) |
| | 10 (-) | 8.60 (.338) | 6.00 (.235) | 19115-0005 | 19115-0006 | 23.60 (.930) |
| 14-16 (2.00-1.30) | 5 (3) | 6.60 (.260) | 5.80 (.230) | 19115-0022 | 19115-0023 | 21.00 (.825) |
| | 5-6 (3-3.5) | 6.60 (.260) | 5.80 (.230) | 19115-0024 | 19115-0025 | 21.00 (.825) |
| | | 6.80 (.270) | 6.00 (.235) | 19115-0016 | 19115-0017 | 22.50 (.885) |
| | 8 (4) | 7.60 (.300) | 6.00 (.235) | 19115-0018 | 19115-0019 | 22.70 (.895) |
| | | 8.10 (.320) | 6.60 (.261) | 19115-0079 | 19115-0030 | 22.50 (.886) |
| | 10 (-) | 8.60 (.338) | 6.00 (.235) | 19115-0020 | 19115-0021 | 24.00 (.945) |
| 10-12 (5.00-3.30) | 5 (3) | 8.60 (.340) | 6.60 (.261) | 19115-0031 | 19115-0032 | 23.70 (.934) |
| | | 6.60 (.260) | 5.80 (.230) | 19115-0041 | 19115-0057 | 24.60 (.970) |
| | 5-6 (3-3.5) | 6.60 (.260) | 5.80 (.230) | 19115-0042 | 19115-0043 | 24.60 (.970) |
| | | 7.60 (.300) | 7.80 (.305) | 19115-0033 | 19115-0034 | 28.20 (1.112) |
| | 8 (4) | 8.40 (.330) | 7.80 (.305) | 19115-0035 | 19115-0036 | 29.00 (1.140) |
| | | 8.10 (.320) | 6.60 (.261) | 19115-0046 | 19115-0047 | 26.20 (1.031) |
| 10 (-) | 8.40 (.330) | 7.80 (.305) | 19115-0037 | 19115-0038 | 29.50 (1.160) | |
| 1/4 (6) | | 8.60 (.340) | 6.60 (.261) | 19115-0048 | 19115-0049 | 27.40 (1.079) |
| | | 10.80 (.425) | 9.50 (.375) | 19115-0039 | 19115-0040 | 32.30 (1.286) |

Product Specifications

| Wire Range AWG | Barrel Length | Material Thickness | Insulation Color | Maximum Wire Insulation Diameter | | Circular Mil Area |
|-------------------|---------------|--------------------|------------------|----------------------------------|-------------|-------------------|
| | | | | Insulkrimp | Avikrimp | |
| 18-22 (0.80-0.35) | 4.40 (.175) | 0.80 (.032) | Red | 3.70 (.145) | 3.60 (.140) | 509-2600 |
| 14-16 (2.00-1.30) | 4.40 (.175) | 0.80 (.032) | Blue | 4.40 (.175) | 4.30 (.170) | 2050-5180 |
| 10-12 (5.00-3.30) | 6.40 (.250) | 1.00 (.040) | Yellow | 6.40 (.250) | 5.70 (.225) | 5180-13,100 |