



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19 .
 © COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
G	14	N	REV / REDRAWN / 0720-0482-95 & 0720-0002-95	14FEB95	LO ME



1. USE FOR AN UNSTRIPPED (SINGLE) WIRE END ONLY
2. WIRE INSUL DIA, 2.03-2.92 [0.080-.115]



SPARE WIRE CAPS ON TAPE
(SCALE 1:1)

QTY	PACKAGE TYPE	PART NO
100	LOOSE PIECE, BOX	8-324485-1
4000	ON TAPE, REEL	2-324485-1
1000	LOOSE PIECE	324485

AMP INCORPORATED
CUSTOMER SERVICE SYSTEM

FOR ADDITIONAL PRODUCT INFORMATION OR COPIES OF DRAWINGS AND TECHNICAL DOCUMENTS	PRODUCT INFORMATION CENTER 1-800-522-6752
FOR APPLICATION TOOLING INFORMATION	TOOLING ASSISTANCE CENTER 1-800-722-1111
FOR ORDER ENTRY	1-800-526-5142

MAX RECOMMENDED OPERATING TEMPERATURE:
105°C [221°F]

VOLTAGE RATING:
-

CIRCULAR MIL AREA:
-

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

DIMENSIONS, mm [in]	TOLERANCES UNLESS OTHERWISE SPECIFIED.
	0 PLC ±-
	1 PLC ±-
	2 PLC ±0.20 [0.008]
	3 PLC ±-
	4 PLC ±-
	ANGLES ±-

MATERIAL BODY, CU PER ASTM B152
INSUL, NYLON, COLOR, RED

FINISH BODY, TIN PLATE PER MIL-T-10727

DWN L OLMEDA 14FEB95	AMP AMP Incorporated Harrisburg, PA 17105-3608
CHK M ELLIS 14FEB95	
APVD T MICHIELUTTI 14FEB95	
NAME	
PRODUCT SPEC	SPARE WIRE CAP, RED
APPLICATION SPEC	
WEIGHT -	SIZE A3 CAGE CODE 00779 DRAWING NO C-324485
CUSTOMER DRAWING	SCALE 8:1 SHEET 1 OF 1 REV N