



RECOMMENDED PCB LAYOUT

NOTE:
 MATERIAL:
 HOUSING: THERMOPLASTIC (PBT+GF)
 COLOR: BLACK/WHITE/BROWN/BEIGE ----
 CONTACT: PHOSPHOR BRONZE
 SHELL: BRASS
 PLATING:
 CONTACT: GOLD PLATING CORD: 5u"
 SHELL: NICKEL PLATING
 SPECIFICATION:
 VOLTAGE RATING: 30V
 CURRENT RATING: 1.5A
 CONTACT RESISTANCE TERMINAL: 30mΩ MAX
 DIELECTRIC WITHSTANDING VOLTAGE: 750V AC
 INSULATION RESISTANCE: 1000MΩ MIN

RoHS
Compliant

<i>ITEM NO</i>	AU-Y1005-R (1.1 Version, 5μ" Gold) AU-Y1005-2-R (2.0 Version, 30μ" Gold)
<i>TITLE</i>	USB, for PCB mounting, Type A

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283
Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
 © Copyright 2008 by Assmann Electronic Components
 All International Rights Reserved