



RECOMMENDED P.C.B. PATTERN LAYOUT

MATERIAL  
 INSULATOR:PBT+30%G.F  
 COLOR:BLACK/WHITE/BROWN/BEIGE-----  
 CONTACT:BRASS  
 SHELL:BRASS  
 MECHANICAL  
 MATING:35N MAX.  
 WITHDRAWAL FORCE:10N MIN.  
 DURAL LITY:1500 CYCLES MIN.  
 ELECTRICAL  
 CURENT-MAX[AMPS]:1.0A  
 VOLTAGE-MAX[VOLTS]:30V  
 WITHSTANDING VOLTAGE:100V AC.  
 CONTACT RESISTANCE [OHMS]:50mΩ MAX.  
 INSULATION RESISTANCE [OHMS]:1000MΩ MIN.  
 PLATING  
 CONTACT: GOLD PLATING CORD: 5u"  
 SHELL:Nickel(Tin) OVER ALL PLATING  
 ENVIRONMENTAL  
 TEMPERATURE RANGE:-55°C to +85°C



ITEM NO	AU-Y1008-R (Version 1.1, 5μ" Gold) AU-Y1008-2-R (Version 2.0, 30μ" Gold)
---------	---

TITLE	USB, Version A, 2 Port
-------	------------------------

**ASSMANN**  
 Electronics, Inc.

1840 W. Drake Drive, Suite 101 - Tempe, AZ 85283

Toll Free: 1-877-277-6266 Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
 ©Copyright 2008 by Assmann Electronic Components  
 All International Rights Reserved