

LOW FREQUENCY CYLINDRICAL WATCH CRYSTAL

AB15T

AB15T



RoHS
Compliant

5.1 x 1.5 mm

FEATURES:

- Watch frequency
- Excellent heat resistance

APPLICATIONS:


- Real time clock, Measuring instruments
- Clock source for communication or A/V equipment

STANDARD SPECIFICATIONS:

PARAMETERS

ABRACON P/N	AB15T Series
Frequency Range	32.768 kHz
Operating Temperature	- 20°C to + 70°C
Storage Temperature	-40°C to + 85°C
Turn-over Temperature	+25°C to ± 5°C
Frequency Tolerance	± 20 ppm max.
Temperature Coefficient	-0.034 ± 0.006 ppm/ T ²
Equivalent Series Resistance	40 kohms max.
Shunt Capacitance C ₀	1.00 pF typ.
Load Capacitance C _L	12.5 pF
Quality factor	85,000 typ.
Drive Level	1 µW max.
Aging at 25°C First Year	± 3 ppm max.
Insulation Resistance	500 Mohms min. at 100 Vdc ± 15V

OUTLINE DRAWING:




PART IDENTIFICATION: (ORDERING PART NUMBER)

AB15T-32.768KHz




TUNING FORK CRYSTAL TEMPERATURE CURVE



HANDLING INSTRUCTIONS

Mounting:

(1) Soldering on the body of the cylinder type crystal unit must be strictly avoided due to deteriorate the characteristics or damage the products. Rubber adhesive is recommended.



(2) When the leads need to be bent by hand, follow the instructions below.

- Hold the body of the Cylinder type crystal unit in fingers.
- Pick at the part with tweezers, which you intend to bend. There should be more than 1.5mm (3.0mm is recommendable) from the body case.
- Bend the lead 90° by tweezers without pulling the lead strongly. Pulling the leads forcefully may cause cracks in the glass hermetic seal resulting in component failure.

