

Crystal Oscillator


Model Name NT3225SA Temperature-Compensated Crystal Oscillator (TCXO) NT3225S Series

Main Application

For mobile phones, etc.

Features

- Supports low power supply voltage. (Supports DC +2.4±0.1 V to +3.4 V±5%.)
- Ultra-compact and light with a height, cubic volume, and weight of 1.0 mm max., 0.007 cm³, and 0.024g, respectively.
- Low power consumption.
- A surface-mount crystal oscillator. (Reflow soldering is possible.)
- Lead-free. Meets the requirements for re-flow profiling using lead-free solder.



Pb Free

RoHS Compliant
Directive 2002/95/EC

Specifications


Item	Model	NT3225SA
Standard nominal frequency (MHz)		10 to 26 MHz
Power supply voltage		+3.0V DC
Load		10kΩ//10pF
Consumption current		1.5mA max
Output level		0.8V(P-P) min (DC superimposition *1)
Frequency / temperature characteristic		±2.5×10 ⁻⁶ max
		-30 to +75°C
Power supply variation characteristics		±0.3×10 ⁻⁶ max/+3.0V±5%
Load variation characteristics		±0.2×10 ⁻⁶ max /(10kΩ//10pF)±10%
Aging		±1.0×10 ⁻⁶ max/year

Frequency setting conditions

1. Frequencies are set at normal temperatures (+25±2°C).
 2. Frequencies are set with a printed board that has a ground pattern attached to the underside of an oscillator.
- If you require a product with a different frequency, power supply voltage, frequency control characteristic, etc. to the standard specifications, please contact us with your enquiries.

*1. A DC-cut capacitor is not embedded in this crystal oscillator. Connect a DC-cut capacitor (1,000 pF) to the line-out terminal of the oscillator.

Dimensions



List of Ordering Codes

Frequency (MHz)	Ordering Code
10	NT3225SA-10M-NSA0322A
12.8	NT3225SA-12.8M-NSA0322A
16.3676	NT3225SA-16.3676M-NSA0322A
16.37	NT3225SA-16.37M-NSA0322A
19.2	NT3225SA-19.2M-NSA0322B
19.68	NT3225SA-19.68M-NSA0322B
26	NT3225SA-26M-NSA0322B

The above frequencies are NDK's standard frequencies. Frequencies other than the above are available. Feel free to contact our sales representatives.