


Diode Full Bridge Power Module

$V_{RRM} = 1200V$
 $I_C = 100A @ T_c = 60^\circ C$




Application

- Uninterruptible Power Supply (UPS)
- Induction heating
- Welding equipment
- High speed rectifiers

Features

- Ultra fast recovery times
- Soft recovery characteristics
- High blocking voltage
- High current
- Low leakage current
- Very low stray inductance
 - Symmetrical design
 - Lead frames for power connections
- High level of integration



Benefits

- Outstanding performance at high frequency operation
- Low losses
- Low noise switching
- Solderable terminals for easy PCB mounting
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- RoHS Compliant

Absolute maximum ratings

| Symbol | Parameter | Max ratings | Unit | | |
|--------------|---|------------------|--------------------|-----|---|
| V_R | Maximum DC reverse Voltage | 1200 | V | | |
| V_{RRM} | Maximum Peak Repetitive Reverse Voltage | | | | |
| $I_{F(AV)}$ | Maximum Average Forward Current | Duty cycle = 50% | $T_C = 25^\circ C$ | 120 | A |
| | | | $T_C = 60^\circ C$ | 100 | |
| $I_{F(RMS)}$ | RMS Forward Current | Duty cycle = 50% | $T_C = 45^\circ C$ | 135 | |
| I_{FSM} | Non-Repetitive Forward Surge Current | 8.3ms | $T_C = 45^\circ C$ | 500 | |

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Electrical Characteristics

| <i>Symbol</i> | <i>Characteristic</i> | <i>Test Conditions</i> | | <i>Min</i> | <i>Typ</i> | <i>Max</i> | <i>Unit</i> |
|---------------|---------------------------------|------------------------|---------------------------|------------|------------|------------|---------------|
| V_F | Diode Forward Voltage | $I_F = 100\text{A}$ | | | 2.4 | 3 | V |
| | | $I_F = 150\text{A}$ | | | 2.7 | | |
| | | $I_F = 100\text{A}$ | $T_j = 125^\circ\text{C}$ | | 1.8 | | |
| I_{RM} | Maximum Reverse Leakage Current | $V_R = 1200\text{V}$ | $T_j = 25^\circ\text{C}$ | | | 100 | μA |
| | | | $T_j = 125^\circ\text{C}$ | | | 500 | |
| C_T | Junction Capacitance | $V_R = 1200\text{V}$ | | | 110 | | pF |

Dynamic Characteristics

| <i>Symbol</i> | <i>Characteristic</i> | <i>Test Conditions</i> | | <i>Min</i> | <i>Typ</i> | <i>Max</i> | <i>Unit</i> |
|---------------|--------------------------|--|---------------------------|------------|------------|------------|---------------|
| t_{rr} | Reverse Recovery Time | $I_F = 1\text{A}, V_R = 30\text{V}$ $di/dt = 100\text{A}/\mu\text{s}$ | $T_j = 25^\circ\text{C}$ | | 45 | | ns |
| t_{rr} | Reverse Recovery Time | $I_F = 100\text{A}$ $V_R = 800\text{V}$ $di/dt = 200\text{A}/\mu\text{s}$ | $T_j = 25^\circ\text{C}$ | | 385 | | ns |
| | | | $T_j = 125^\circ\text{C}$ | | 480 | | |
| Q_{rr} | Reverse Recovery Charge | | $T_j = 25^\circ\text{C}$ | | 1055 | | nC |
| | | | $T_j = 125^\circ\text{C}$ | | 5240 | | |
| I_{RRM} | Reverse Recovery Current | | $T_j = 25^\circ\text{C}$ | | 6 | | A |
| | | | $T_j = 125^\circ\text{C}$ | | 19 | | |
| t_{rr} | Reverse Recovery Time | $I_F = 100\text{A}$ $V_R = 800\text{V}$ $di/dt = 1000\text{A}/\mu\text{s}$ | $T_j = 125^\circ\text{C}$ | | 210 | | ns |
| Q_{rr} | Reverse Recovery Charge | | | | 9.4 | | μC |
| I_{RRM} | Reverse Recovery Current | | | | 70 | | A |

Thermal and package characteristics

| <i>Symbol</i> | <i>Characteristic</i> | <i>Min</i> | <i>Typ</i> | <i>Max</i> | <i>Unit</i> | |
|---------------|---|-------------|------------|------------|---------------------------|-----|
| R_{thJC} | Junction to Case Thermal Resistance | | | 0.55 | $^\circ\text{C}/\text{W}$ | |
| V_{ISOL} | RMS Isolation Voltage, any terminal to case $t = 1\text{ min}$, $I_{iso} < 1\text{mA}$, 50/60Hz | 2500 | | | V | |
| T_j | Operating junction temperature range | -40 | | 175 | $^\circ\text{C}$ | |
| T_{STG} | Storage Temperature Range | -40 | | 125 | | |
| T_C | Operating Case Temperature | -40 | | 100 | | |
| Torque | Mounting torque | To Heatsink | M5 | 2.5 | 4.7 | N.m |
| Wt | Package Weight | | | | 160 | g |

Typical Performance Curve

