

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

## Features

- The three layer, two terminal, axial lead, hermetically sealed diacs are designed specifically for triggering thyristors.
- Lead Free Finish/Rohs Compliant (Note1) ("P"Suffix designates Compliant. See ordering information)
- Moisture Sensitivity: Level 1 per J-STD-020C
- These diacs are intended for use in thyrisitors phase control, circuits for lamp dimming, universal motor speed control, and heat control. Type number is marked.

# Maximum Ratings

- Operating Temperature: -40°C to +110°C
- Storage Temperature: -40°C to +125°C

Electrical Characteristics @ 25°C Unless Otherwise Specified


Power dissipation on Printed Circuit(I=10mm)	Pc	150mW	T <sub>A</sub> =50°C
Repetitive Peak on-state Current DB3,DC34,DB4 DB6	I <sub>trm</sub>	2.0A 16A	t <sub>p</sub> =10us,f=100Hz
Breakover Voltage DB3 DC34 DB4 DB6	V <sub>BO</sub>	Min Typ Max 28 32 36V 30 34 38V 35 40 45V 56 60 70V	C=22nF(Note 3)
Breakover Voltage Symmetry DB3, DC34, DB4 DB6	+V <sub>BO</sub>   - -V <sub>BO</sub>	±3∨ ±4∨	C=22nF(Note 3)
Output Voltage(Note 2)	$V_{o(min)}$	5V	
Breakover Current(Note 2)	I <sub>BO(max)</sub>	100uA	C=22nF
Rise Time(Note 2)	T <sub>r</sub>	1.5us	
Leakage Current(Note 2)	I <sub>B(max)</sub>	10uA	$V_B=0.5V_{BO(max)}$



**DB3/DC34** 

AND

**DB4/DB6** 



Note: 1. Lead in Glass Exemption Applied, see EU Directive Annex 5.

2. Electrical characteristics applicable in both forward and

reverse directions.
Connected in parallel with the devices.

www.mccsemi.com

#### **Revision: 6**



## RATINGS AND CHARACTERISTIC CURVES DB3/DC34/DB4/DB6

DIAGRAM 1: Current-voltage characteristics




FIG.1-Power dissipation versus ambient temperature (maximum values)







FIG.3-Peak pulse current versus pulse duration (maximum values)



DLAGR AM 2: T est circuit for output voltage











FIG.2-Relative variation of VBO versus junction temperature(typical values)



# www.mccsemi.com



Micro Commercial Components

### **Ordering Information**

Device	Packing	
(Part Number)-TP	Tape&Reel 10Kpcs/Reel	
(Part Number)-AP	Ammo Packing;5Kpcs/AmmoBox	
(Part Number)-BP	Bulk;500pcs/Bag	

### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp . reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .
Micro Commercial Components Corp . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp . and all the companies whose products are represented on our website, harmless against all damages.

### **\*\*\*APPLICATIONS DISCLAIMER\*\*\***

Products offer by Micro Commercial Components Corp. are not intended for use in Medical,

Aerospace or Military Applications.