


EMG 22-DIO 7M

Order No.: 2950077

The illustration shows a combination of versions EMG 22-DIO 7 P, EMG 45-DIO14 P and EMG 90-DIO 32 P

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2950077>Diode module with 7 diodes with M-poles (common anode), diode type
1N 4007

Commercial data

EAN	4017918083946
Pack	10 Pcs.
Customs tariff	85411000
Weight/Piece	0.04603 KG
Catalog page information	Page 562 (IF-2007)

Product notes

WEEE/RoHS-compliant since:
05/16/2006

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data

General data

Diode type	1 N 4007
Max. operating voltage	250 V AC
Peak reverse voltage per diode	1300 V
Reverse current per diode	5 μ A

Conducting state voltage per diode	Approx. 0.8 V
Conducting state current per diode	0.5 A (with simultaneous loads)
	0.7 A (with single load)
Length	75 mm
Width	22.5 mm
Height	55 mm
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Standards/regulations	IEC 664
	IEC 664 A
	DIN VDE 0110-1
	DIN VDE 0160
Pollution degree	2
Surge voltage category	III
Mounting position	Any
Assembly instructions	In rows with zero spacing

Connection data

Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	4 mm ²
Conductor cross section stranded min.	0.2 mm ²
Conductor cross section stranded max.	2.5 mm ²
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M 3
Type of connection	Screw connection

Certificates / Approvals

Approval logo

**requested approbations**


Certification	GOST
---------------	------

Accessories

Item	Designation	Description
Marking		
2947035	EMG-GKS 12	Equipment marker, width 12 mm

Drawings

Circuit diagram



Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2008 Phoenix Contact
Technical modifications reserved;