



# STTH120L06TV

## TURBO 2 ULTRAFAST HIGH VOLTAGE RECTIFIER

**Table 1: Main Product Characteristics**

$I_{F(AV)}$	<b>2 x 60 A</b>
$V_{RRM}$	<b>600 V</b>
$T_j$	<b>150°C</b>
$V_F$ (typ)	<b>0.95 V</b>
$t_{rr}$ (max)	<b>70 ns</b>

### FEATURES AND BENEFITS

- Ultrafast switching
- Low reverse current
- Low thermal resistance
- Reduces switching & conduction losses

### DESCRIPTION


The STTH120L06TV, which is using ST Turbo 2 600V technology, is specially suited for use in switching power supplies, and industrial applications, as rectification and free-wheeling diode.

**Table 2: Order Codes**

<b>Part Number</b>	<b>Marking</b>
STTH120L06TV1	STTH120L06TV1

**Table 3: Absolute Ratings** (limiting values, per diode)

Symbol	Parameter		Value	Unit
$V_{RRM}$	Repetitive peak reverse voltage		600	V
$I_{F(RMS)}$	RMS forward voltage		120	A
$I_{F(AV)}$	Average forward current $\delta = 0.5$	$T_c = 65^\circ\text{C}$ Per diode	60	A
$I_{FSM}$	Surge non repetitive forward current	$t_p = 10\text{ms}$ sinusoidal	500	A
$T_{stg}$	Storage temperature range		-55 to + 150	°C
$T_j$	Maximum operating junction temperature		150	°C



**Table 4: Thermal Resistance**

Symbol	Parameter		Value (max.)	Unit
$R_{th(j-c)}$	Junction to case	Per diode	0.98	°C/W
		Total	0.54	
$R_{th(c)}$	Coupling		0.1	°C/W

When the diodes 1 and 2 are used simultaneously:  
 $\Delta T_{j(\text{diode } 1)} = P(\text{diode } 1) \times R_{th(j-c)}(\text{Per diode}) + P(\text{diode } 2) \times R_{th(c)}$

**Table 5: Static Electrical Characteristics (per diode)**

Symbol	Parameter	Test conditions		Min.	Typ	Max.	Unit
$I_R^*$	Reverse leakage current	$T_j = 25^\circ\text{C}$	$V_R = V_{RRM}$			50	$\mu\text{A}$
		$T_j = 125^\circ\text{C}$			50	500	
$V_F^{**}$	Forward voltage drop	$T_j = 25^\circ\text{C}$	$I_F = 60\text{A}$			1.55	V
		$T_j = 150^\circ\text{C}$			0.95	1.2	

Pulse test: \*  $t_p = 5 \text{ ms}$ ,  $\delta < 2\%$   
 \*\*  $t_p = 380 \mu\text{s}$ ,  $\delta < 2\%$

To evaluate the conduction losses use the following equation:  $P = 0.93 \times I_{F(AV)} + 0.0045 I_F^2(\text{RMS})$

**Table 6: Dynamic Characteristics (per diode)**

Symbol	Parameter	Test conditions		Min.	Typ	Max.	Unit
$t_{rr}$	Reverse recovery time	$T_j = 25^\circ\text{C}$	$I_F = 0.5\text{A}$ $I_{rr} = 0.25\text{A}$ $I_R = 1\text{A}$			70	ns
			$I_F = 1\text{A}$ $di_F/dt = 50 \text{ A}/\mu\text{s}$ $V_R = 30\text{V}$		75	105	
$I_{RM}$	Reverse recovery current	$T_j = 125^\circ\text{C}$	$I_F = 60\text{A}$ $V_R = 400\text{V}$ $di_F/dt = 100 \text{ A}/\mu\text{s}$		14	19	A
$t_{fr}$	Forward recovery time	$T_j = 25^\circ\text{C}$	$I_F = 60\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$ $V_{FR} = 1.1 \times V_{Fmax}$			500	ns
$V_{FP}$	Forward recovery voltage	$T_j = 25^\circ\text{C}$	$I_F = 60\text{A}$ $di_F/dt = 200 \text{ A}/\mu\text{s}$ $V_{FR} = 1.1 \times V_{Fmax}$		3		V

Figure 1: Conduction losses versus average forward current (per diode)




Figure 2: Forward voltage drop versus forward current (per diode)




Figure 3: Relative variation of thermal impedance junction to case versus pulse duration




Figure 4: Peak reverse recovery current versus di/dt (typical values, per diode)




Figure 5: Reverse recovery time versus di/dt (typical values, per diode)




Figure 6: Reverse recovery charges versus di/dt (typical values, per diode)




Figure 7: Reverse recovery softness factor versus  $di_F/dt$  (typical values, per diode)




Figure 8: Relative variations of dynamic parameters versus junction temperature




Figure 9: Transient peak forward voltage versus  $di_F/dt$  (typical values, per diode)




Figure 10: Forward recovery time versus  $di_F/dt$  (typical values, per diode)




Figure 11: Junction capacitance versus reverse voltage applied (typical values, per diode)




Figure 12: ISOTOP Package Mechanical Data

REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	11.80	12.20	0.465	0.480
A1	8.90	9.10	0.350	0.358
B	7.8	8.20	0.307	0.323
C	0.75	0.85	0.030	0.033
C2	1.95	2.05	0.077	0.081
D	37.80	38.20	1.488	1.504
D1	31.50	31.70	1.240	1.248
E	25.15	25.50	0.990	1.004
E1	23.85	24.15	0.939	0.951
E2	24.80 typ.		0.976 typ.	
G	14.90	15.10	0.587	0.594
G1	12.60	12.80	0.496	0.504
G2	3.50	4.30	0.138	0.169
F	4.10	4.30	0.161	0.169
F1	4.60	5.00	0.181	0.197
P	4.00	4.30	0.157	0.69
P1	4.00	4.40	0.157	0.173
S	30.10	30.30	1.185	1.193

Table 7: Ordering Information

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STTH120L06TV1	STTH120L06TV1	ISOTOP	27 g (without screws)	10 (with screws)	Tube

- Epoxy meets UL94, V0
- Cooling method: by conduction (C)

Table 8: Revision History

Date	Revision	Description of Changes
07-Sep-2004	1	First issue

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics.  
All other names are the property of their respective owners

© 2004 STMicroelectronics - All rights reserved

**STMicroelectronics group of companies**

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan -  
Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America  
[www.st.com](http://www.st.com)