

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311


Phone: (818) 701-4933 Fax: (818) 701-4939

## **BAV99DW**

#### **Features**

- Low Current Leakage
- Low Cost
- Small Outline Surface Mount Package
- Case Material:Molded Plastic. UL Flammability Classificatio Rating 94-0 and MSL Rating 1


MAKING:KJG





# Plastic-Encapsulate Diode

200mW 75Volt

## SOT-363







DIMENSIONS								
	INCHES		MM					
DIM	MIN	MAX	MIN	MAX	NOTE			
Α	.004	.012	0.10	0.30				
В	.045	.053	1.15	1.35				
С	.079	.087	2.00	2.20				
D	.026		0.65Nominal					
F	.012	.016	0.30	0.40				
Н	.071	.087	1.80	2.20				
J		.004		0.10				
K	.035	.039	0.90	1.00				
Ĺ	.010	.016	0.25	0.40				
M	.004	.016	0.10	0.25				

## **Maximum Ratings**

Operating Temperature: -55°C to +150°C


Storage Temperature: -55°C to +150°C


#### Electrical Characteristics @ 25°C Unless Otherwise Specified

Reverse Voltage	$V_R$	75V	
Average Rectified	Ιο	150mA	
Output Current			
Power Dissipation	P <sub>TOT</sub>	200mW	
Maximum Instantaneous Forward Voltage	$V_{F}$	715mV 855mV 1000mV 1250mV	I <sub>FM</sub> = 1mA; I <sub>FM</sub> = 10mA; I <sub>FM</sub> = 50mA; I <sub>FM</sub> = 150mA;
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	2.5uA 0.025uA	VR=75V VR=20V
Typical Junction Capacitance	C <sub>J</sub>	2.0pF	Measured at 1.0MHz, V <sub>R</sub> =0V
Reverse Recovery Time	T <sub>rr</sub>	4nS	$I_F=I_R=10$ mA $I_{rr}=0.1^*I_R$ $R_c=100\Omega$

## BAV99DW







T<sub>j</sub>, JUNCTION TEMPERATURE (°C) Fig. 2 Leakage Current vs Junction Temperature



#### **Ordering Information**

Device	Packing
(Part Number)-TP	Tape&Reel3Kpcs/Reel

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.