

# DATA SHEET



## **BYD77 series** Ultra fast low-loss controlled avalanche rectifiers

Product specification  
Supersedes data of 1996 May 24

1999 Nov 15

## Ultra fast low-loss controlled avalanche rectifiers

## BYD77 series

### FEATURES

- Glass passivated
- High maximum operating temperature
- Low leakage current
- Excellent stability
- Guaranteed avalanche energy absorption capability
- Shipped in 8 mm embossed tape
- Smallest surface mount rectifier outline.

### DESCRIPTION

Cavity free cylindrical glass SOD87 package through Implotec™<sup>(1)</sup> technology. This package is

hermetically sealed and fatigue free as coefficients of expansion of all used parts are matched.

(1) Implotec is a trademark of Philips.




Fig.1 Simplified outline (SOD87) and symbol.

### LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

| SYMBOL             | PARAMETER                       | CONDITIONS   | MIN. | MAX. | UNIT |
|--------------------|---------------------------------|--|------|------|------|
| V <sub>RRM</sub>   | repetitive peak reverse voltage |  |      |      |      |
|                    | BYD77A                          |  | –    | 50   | V    |
|                    | BYD77B                          |  | –    | 100  | V    |
|                    | BYD77C                          |  | –    | 150  | V    |
|                    | BYD77D                          |  | –    | 200  | V    |
|                    | BYD77E                          |  | –    | 250  | V    |
|                    | BYD77F                          |  | –    | 300  | V    |
|                    | BYD77G                          |  | –    | 400  | V    |
| V <sub>R</sub>     | continuous reverse voltage      |  |      |      |      |
|                    | BYD77A                          |  | –    | 50   | V    |
|                    | BYD77B                          |  | –    | 100  | V    |
|                    | BYD77C                          |  | –    | 150  | V    |
|                    | BYD77D                          |  | –    | 200  | V    |
|                    | BYD77E                          |  | –    | 250  | V    |
|                    | BYD77F                          |  | –    | 300  | V    |
|                    | BYD77G                          |  | –    | 400  | V    |
| I <sub>F(AV)</sub> | average forward current         | T <sub>tp</sub> = 105 °C; see Figs 2 and 3; averaged over any 20 ms period; see also Figs 10 and 11                            | –    | 2.00 | A    |
|                    | BYD77A to D                     |  | –    | 1.85 | A    |
| I <sub>F(AV)</sub> | average forward current         | T <sub>amb</sub> = 60 °C; PCB mounting (see Fig.16); see Figs 4 and 5; averaged over any 20 ms period; see also Figs 10 and 11 | –    | 0.85 | A    |
|                    | BYD77A to D                     |  | –    | 0.80 | A    |
|                    | BYD77E to G                     |  |      |      |      |

# Ultra fast low-loss controlled avalanche rectifiers

## BYD77 series

| SYMBOL    | PARAMETER                                    | CONDITIONS   | MIN. | MAX. | UNIT |
|-----------|--|--|------|------|------|
| $I_{FRM}$ | repetitive peak forward current              | $T_{tp} = 105\text{ °C}$ ; see Figs 6 and 7  | –    | 15   | A    |
|           | BYD77A to D                                  |  |      | 13   | A    |
| $I_{FRM}$ | repetitive peak forward current              | $T_{amb} = 60\text{ °C}$ ; see Figs 8 and 9  | –    | 8.5  | A    |
|           | BYD77E to G                                  |  |      | 8.0  | A    |
| $I_{FSM}$ | non-repetitive peak forward current          | $t = 10\text{ ms}$ half sine wave; $T_j = T_{j\text{ max}}$ prior to surge; $V_R = V_{RRM\text{ max}}$ | –    | 25   | A    |
| $E_{RSM}$ | non-repetitive peak reverse avalanche energy | $L = 120\text{ mH}$ ; $T_j = 25\text{ °C}$ prior to surge; inductive load switched off                 | –    | 10   | mJ   |
| $T_{stg}$ | storage temperature                          |  | –65  | +175 | °C   |
| $T_j$     | junction temperature                         |  | –65  | +175 | °C   |

### ELECTRICAL CHARACTERISTICS

$T_j = 25\text{ °C}$  unless otherwise specified.

| SYMBOL      | PARAMETER                           | CONDITIONS   | MIN. | TYP. | MAX. | UNIT |   |   |   |
|-------------|-------------------------------------|--|------|------|------|------|---|---|---|
| $V_F$       | forward voltage                     | $I_F = 1\text{ A}$ ; $T_j = T_{j\text{ max}}$ ; see Figs 12 and 13   | –    | –    | 0.75 | V    |   |   |   |
|             | BYD77A to D                         |  |      |      | 0.83 | V    |   |   |   |
| $V_F$       | forward voltage                     | $I_F = 1\text{ A}$ ; see Figs 12 and 13  | –    | –    | 0.98 | V    |   |   |   |
|             | BYD77E to G                         |  |      |      | 1.05 | V    |   |   |   |
| $V_{(BR)R}$ | reverse avalanche breakdown voltage | $I_R = 0.1\text{ mA}$  |      |      |      |      |   |   |   |
|             | BYD77A                              |  |      |      |      | 55   | – | – | V |
|             | BYD77B                              |  |      |      |      | 110  | – | – | V |
|             | BYD77C                              |  |      |      |      | 165  | – | – | V |
|             | BYD77D                              |  |      |      |      | 220  | – | – | V |
|             | BYD77E                              |  |      |      |      | 275  | – | – | V |
|             | BYD77F                              |  |      |      |      | 330  | – | – | V |
| BYD77G      | 440                                 | –  | –    | V    |      |      |   |   |   |
| $I_R$       | reverse current                     | $V_R = V_{RRM\text{ max}}$ ; see Fig.14  | –    | –    | 1    | μA   |   |   |   |
|             |                                     | $V_R = V_{RRM\text{ max}}$ ; $T_j = 165\text{ °C}$ ; see Fig.14  | –    | –    | 100  | μA   |   |   |   |
| $t_{rr}$    | reverse recovery time               | when switched from $I_F = 0.5\text{ A}$ to $I_R = 1\text{ A}$ ; measured at $I_R = 0.25\text{ A}$ ; see Fig.18 | –    | –    | 25   | ns   |   |   |   |
|             | BYD77A to D                         |  |      |      | 50   | ns   |   |   |   |
|             | BYD77E to G                         |  |      |      |      |      |   |   |   |

## Ultra fast low-loss controlled avalanche rectifiers

## BYD77 series

| SYMBOL                           | PARAMETER                                 | CONDITIONS  | MIN. | TYP. | MAX. | UNIT |
|----------------------------------|---|---|------|------|------|------|
| C <sub>d</sub>                   | diode capacitance                         | f = 1 MHz; V <sub>R</sub> = 0 V;<br>see Fig.15  | –    | 50   | –    | pF   |
|                                  | BYD77A to D                               |   |      |      |      |      |
|                                  | BYD77E to G                               |   | –    | 40   | –    | pF   |
| $\left  \frac{dI_R}{dt} \right $ | maximum slope of reverse recovery current | when switched from<br>I <sub>F</sub> = 1 A to V <sub>R</sub> ≥ 30 V and<br>dI <sub>F</sub> /dt = –1 A/μs;<br>see Fig.17 | –    | –    | 4    | A/μs |
|                                  | BYD77A to D                               |   |      |      |      |      |
|                                  | BYD77E to G                               |   | –    | –    | 5    | A/μs |

### THERMAL CHARACTERISTICS

| SYMBOL               | PARAMETER                                     | CONDITIONS | VALUE | UNIT |
|----------------------|---|------------|-------|------|
| R <sub>th j-tp</sub> | thermal resistance from junction to tie-point |            | 30    | K/W  |
| R <sub>th j-a</sub>  | thermal resistance from junction to ambient   | note 1     | 150   | K/W  |





#### Note

1. Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-layer ≥40 μm, see Fig.16. For more information please refer to the "General Part of associated Handbook".

Ultra fast low-loss  
controlled avalanche rectifiers



BYD77 series

GRAPHICAL DATA





Ultra fast low-loss  
controlled avalanche rectifiers

BYD77 series







Ultra fast low-loss  
controlled avalanche rectifiers

BYD77 series



Ultra fast low-loss  
controlled avalanche rectifiers





BYD77 series







Ultra fast low-loss  
controlled avalanche rectifiers

BYD77 series



# Ultra fast low-loss controlled avalanche rectifiers

## BYD77 series



Input impedance oscilloscope: 1 MΩ, 22 pF;  $t_r \leq 7$  ns.  
Source impedance: 50 Ω;  $t_r \leq 15$  ns.

Fig.18 Test circuit and reverse recovery time waveform and definition.

Ultra fast low-loss  
controlled avalanche rectifiers

BYD77 series

PACKAGE OUTLINE

Hermetically sealed glass surface mounted package;  
Implotec™(1) technology; 2 connectors

SOD87

**DIMENSIONS (mm are the original dimensions)**

| UNIT | D          | D1         | H          | L   |
|------|------------|------------|------------|-----|
| mm   | 2.1<br>2.0 | 2.0<br>1.8 | 3.7<br>3.3 | 0.3 |

**Notes**  
 1. Implotec is a trademark of Philips.  
 2. The marking indicates the cathode.

| OUTLINE VERSION | REFERENCES |       |      | EUROPEAN PROJECTION | ISSUE DATE           |
|-----------------|------------|-------|------|---------------------|----------------------|
|                 | IEC        | JEDEC | EIAJ |                     |                      |
| SOD87           | 100H03     |       |      |                     | 99-03-31<br>99-06-04 |

DEFINITIONS

| Data Sheet Status   |   |
|---|---|
| Objective specification   | This data sheet contains target or goal specifications for product development.       |
| Preliminary specification   | This data sheet contains preliminary data; supplementary data may be published later. |
| Product specification   | This data sheet contains final product specifications.                                |
| Limiting values   |   |
| Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability. |   |
| Application information   |   |
| Where application information is given, it is advisory and does not form part of the specification.   |   |

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

# Philips Semiconductors – a worldwide company

**Argentina:** see South America

**Australia:** 3 Figtree Drive, HOME BUSH, NSW 2140,  
Tel. +61 2 9704 8141, Fax. +61 2 9704 8139

**Austria:** Computerstr. 6, A-1101 WIEN, P.O. Box 213,  
Tel. +43 1 60 101 1248, Fax. +43 1 60 101 1210

**Belarus:** Hotel Minsk Business Center, Bld. 3, r. 1211, Volodarski Str. 6,  
220050 MINSK, Tel. +375 172 20 0733, Fax. +375 172 20 0773

**Belgium:** see The Netherlands

**Brazil:** see South America

**Bulgaria:** Philips Bulgaria Ltd., Energoproject, 15th floor,  
51 James Bourchier Blvd., 1407 SOFIA,  
Tel. +359 2 68 9211, Fax. +359 2 68 9102

**Canada:** PHILIPS SEMICONDUCTORS/COMPONENTS,  
Tel. +1 800 234 7381, Fax. +1 800 943 0087

**China/Hong Kong:** 501 Hong Kong Industrial Technology Centre,  
72 Tat Chee Avenue, Kowloon Tong, HONG KONG,  
Tel. +852 2319 7888, Fax. +852 2319 7700

**Colombia:** see South America

**Czech Republic:** see Austria

**Denmark:** Sydhavnsgade 23, 1780 COPENHAGEN V,  
Tel. +45 33 29 3333, Fax. +45 33 29 3905

**Finland:** Sinikalliontie 3, FIN-02630 ESPOO,  
Tel. +358 9 615 800, Fax. +358 9 6158 0920

**France:** 51 Rue Carnot, BP317, 92156 SURESNES Cedex,  
Tel. +33 1 4099 6161, Fax. +33 1 4099 6427

**Germany:** Hammerbrookstraße 69, D-20097 HAMBURG,  
Tel. +49 40 2353 60, Fax. +49 40 2353 6300

**Hungary:** see Austria

**India:** Philips INDIA Ltd, Band Box Building, 2nd floor,  
254-D, Dr. Annie Besant Road, Worli, MUMBAI 400 025,  
Tel. +91 22 493 8541, Fax. +91 22 493 0966

**Indonesia:** PT Philips Development Corporation, Semiconductors Division,  
Gedung Philips, Jl. Buncit Raya Kav.99-100, JAKARTA 12510,  
Tel. +62 21 794 0040 ext. 2501, Fax. +62 21 794 0080

**Ireland:** Newstead, Clonskeagh, DUBLIN 14,  
Tel. +353 1 7640 000, Fax. +353 1 7640 200

**Israel:** RAPAC Electronics, 7 Kehilat Saloniki St, PO Box 18053,  
TEL AVIV 61180, Tel. +972 3 645 0444, Fax. +972 3 649 1007

**Italy:** PHILIPS SEMICONDUCTORS, Via Casati, 23 - 20052 MONZA (MI),  
Tel. +39 039 203 6838, Fax +39 039 203 6800

**Japan:** Philips Bldg 13-37, Kohnan 2-chome, Minato-ku,  
TOKYO 108-8507, Tel. +81 3 3740 5130, Fax. +81 3 3740 5057

**Korea:** Philips House, 260-199 Itaewon-dong, Yongsan-ku, SEOUL,  
Tel. +82 2 709 1412, Fax. +82 2 709 1415

**Malaysia:** No. 76 Jalan Universiti, 46200 PETALING JAYA, SELANGOR,  
Tel. +60 3 750 5214, Fax. +60 3 757 4880

**Mexico:** 5900 Gateway East, Suite 200, EL PASO, TEXAS 79905,  
Tel. +9-5 800 234 7381, Fax +9-5 800 943 0087

**Middle East:** see Italy

**Netherlands:** Postbus 90050, 5600 PB EINDHOVEN, Bldg. VB,  
Tel. +31 40 27 82785, Fax. +31 40 27 88399

**New Zealand:** 2 Wagener Place, C.P.O. Box 1041, AUCKLAND,  
Tel. +64 9 849 4160, Fax. +64 9 849 7811

**Norway:** Box 1, Manglerud 0612, OSLO,  
Tel. +47 22 74 8000, Fax. +47 22 74 8341

**Pakistan:** see Singapore

**Philippines:** Philips Semiconductors Philippines Inc.,  
106 Valero St. Salcedo Village, P.O. Box 2108 MCC, MAKATI,  
Metro MANILA, Tel. +63 2 816 6380, Fax. +63 2 817 3474

**Poland:** Al.Jerozolimskie 195 B, 02-222 WARSAW,  
Tel. +48 22 5710 000, Fax. +48 22 5710 001

**Portugal:** see Spain

**Romania:** see Italy

**Russia:** Philips Russia, Ul. Usatcheva 35A, 119048 MOSCOW,  
Tel. +7 095 755 6918, Fax. +7 095 755 6919

**Singapore:** Lorong 1, Toa Payoh, SINGAPORE 319762,  
Tel. +65 350 2538, Fax. +65 251 6500

**Slovakia:** see Austria

**Slovenia:** see Italy

**South Africa:** S.A. PHILIPS Pty Ltd., 195-215 Main Road Martindale,  
2092 JOHANNESBURG, P.O. Box 58088 Newville 2114,  
Tel. +27 11 471 5401, Fax. +27 11 471 5398

**South America:** Al. Vicente Pinzon, 173, 6th floor,  
04547-130 SÃO PAULO, SP, Brazil,  
Tel. +55 11 821 2333, Fax. +55 11 821 2382

**Spain:** Balmes 22, 08007 BARCELONA,  
Tel. +34 93 301 6312, Fax. +34 93 301 4107

**Sweden:** Kottbygatan 7, Akalla, S-16485 STOCKHOLM,  
Tel. +46 8 5985 2000, Fax. +46 8 5985 2745

**Switzerland:** Allmendstrasse 140, CH-8027 ZÜRICH,  
Tel. +41 1 488 2741 Fax. +41 1 488 3263

**Taiwan:** Philips Semiconductors, 6F, No. 96, Chien Kuo N. Rd., Sec. 1,  
TAIPEI, Taiwan Tel. +886 2 2134 2886, Fax. +886 2 2134 2874

**Thailand:** PHILIPS ELECTRONICS (THAILAND) Ltd.,  
209/2 Sanpavuth-Bangna Road Prakanong, BANGKOK 10260,  
Tel. +66 2 745 4090, Fax. +66 2 398 0793

**Turkey:** Yukari Dudullu, Org. San. Blg., 2.Cad. Nr. 28 81260 Umraniye,  
ISTANBUL, Tel. +90 216 522 1500, Fax. +90 216 522 1813

**Ukraine:** PHILIPS UKRAINE, 4 Patrice Lumumba str., Building B, Floor 7,  
252042 KIEV, Tel. +380 44 264 2776, Fax. +380 44 268 0461

**United Kingdom:** Philips Semiconductors Ltd., 276 Bath Road, Hayes,  
MIDDLESEX UB3 5BX, Tel. +44 208 730 5000, Fax. +44 208 754 8421

**United States:** 811 East Arques Avenue, SUNNYVALE, CA 94088-3409,  
Tel. +1 800 234 7381, Fax. +1 800 943 0087

**Uruguay:** see South America

**Vietnam:** see Singapore

**Yugoslavia:** PHILIPS, Trg N. Pasica 5/v, 11000 BEOGRAD,  
Tel. +381 11 62 5344, Fax.+381 11 63 5777

**For all other countries apply to:** Philips Semiconductors,  
International Marketing & Sales Communications, Building BE-p, P.O. Box 218,  
5600 MD EINDHOVEN, The Netherlands, Fax. +31 40 27 24825

**Internet:** <http://www.semiconductors.philips.com>

© Philips Electronics N.V. 1999

SCA 68

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

135002/03/pp12

Date of release: 1999 Nov 15

Document order number: 9397 750 06272

*Let's make things better.*

**Philips  
Semiconductors**



**PHILIPS**