


1.0A HIGH VOLTAGE SCHOTTKY BARRIER RECTIFIER
Features


- Guard Ring Die Construction for Transient Protection
- Ideally Suited for Automated Assembly
- Low Power Loss, High Efficiency
- Surge Overload Rating to 30A Peak
- For Use in Low Voltage, High Frequency Inverters, Free Wheeling, and Polarity Protection Application
- High Temperature Soldering: 260°C/10 Second at Terminal
- **Lead Free Finish/RoHS Compliant (Note 1)**

Mechanical Data

- Case: SMA / SMB
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Lead Free Plating (Matte Tin Finish). Solderable per MIL-STD-202, Method 208 **(e3)**
- Polarity: Cathode Band or Cathode Notch
- Marking Information: See Page 2
- Ordering Information: See Page 2
- Weight: SMA 0.064 grams (approximate)
SMB 0.093 grams (approximate)



Top View



Bottom View

Maximum Ratings @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.
For capacitance load, derate current by 20%.

| Characteristic | Symbol | B170/B | B180/B | B190/B | B1100/B | Unit |
|--|--------------|--------|--------|--------|---------|------|
| Peak Repetitive Reverse Voltage | V_{RRM} | 70 | 80 | 90 | 100 | V |
| Working Peak Reverse Voltage | V_{RWM} | | | | | |
| DC Blocking Voltage | V_R | | | | | |
| RMS Reverse Voltage | $V_{R(RMS)}$ | 49 | 56 | 63 | 70 | V |
| Average Rectified Output Current @ $T_T = 125^\circ\text{C}$ | I_O | 1.0 | | | | A |
| Non-Repetitive Peak Forward Surge Current 8.3ms Single Half Sine-Wave Superimposed on Rated Load | I_{FSM} | 30 | | | | A |

Thermal Characteristics

| Characteristic | Symbol | B170/B | B180/B | B190/B | B1100/B | Unit |
|--|-----------------|-------------|--------|--------|---------|--------------------|
| Typical Thermal Resistance Junction to Terminal (Note 2) | $R_{\theta JT}$ | 25 | | | | $^\circ\text{C/W}$ |
| Operating and Storage Temperature Range | T_J, T_{STG} | -65 to +150 | | | | $^\circ\text{C}$ |

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|--------------------------|--------|-----|-----|--------------|------|---|
| Forward Voltage Drop | V_F | - | - | 0.79 0.69 | V | $I_F = 1.0\text{A}, T_A = 25^\circ\text{C}$ $I_F = 1.0\text{A}, T_A = 100^\circ\text{C}$ |
| Leakage Current (Note 3) | I_R | - | - | 0.5 5.0 | mA | @ Rated $V_R, T_A = 25^\circ\text{C}$ @ Rated $V_R, T_A = 100^\circ\text{C}$ |
| Total Capacitance | C_T | - | - | 80 | pF | $V_R = 4\text{V}, f = 1\text{MHz}$ |

- Notes:
1. EU Directive 2002/95/EC (RoHS). All applicable RoHS exemptions applied, see *EU Directive 2002/95/EC Annex Notes*.
 2. Valid provided that terminals are kept at ambient temperature.
 3. Short duration pulse test used to minimize self-heating effect.




Fig. 1 Typical Forward Characteristics




Fig. 2 Total Capacitance vs. Reverse Voltage




Fig. 3 Forward Current Derating Curve




Fig. 4 Max Non-Repetitive Peak Forward Surge Current


Ordering Information (Note 4)

| Part Number | Case | Packaging |
|-------------|------|------------------|
| B1x-13-F | SMA | 5000/Tape & Reel |
| B1xB-13-F | SMB | 3000/Tape & Reel |

*x = Device type, e.g. B180-13-F (SMA package); B1100B-13-F (SMB package).


Notes: 4. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



XXX = Product type marking code, ex: B170 (SMA package)
 XXXX = Product type marking code, ex: B190B (SMB package)
 YWW = Date code marking
 Y = Last digit of year ex: 2 for 2002
 WW = Week code 01 to 52

Package Outline Dimensions




| SMA | | |
|-----|------|------|
| Dim | Min | Max |
| A | 2.29 | 2.92 |
| B | 4.00 | 4.60 |
| C | 1.27 | 1.63 |
| D | 0.15 | 0.31 |
| E | 4.80 | 5.59 |
| G | 0.05 | 0.20 |
| H | 0.76 | 1.52 |
| J | 2.01 | 2.30 |

All Dimensions in mm

| SMB | | |
|-----|------|------|
| Dim | Min | Max |
| A | 3.30 | 3.94 |
| B | 4.06 | 4.57 |
| C | 1.96 | 2.21 |
| D | 0.15 | 0.31 |
| E | 5.00 | 5.59 |
| G | 0.05 | 0.20 |
| H | 0.76 | 1.52 |
| J | 2.00 | 2.62 |

All Dimensions in mm

Suggested Pad Layout



| SMA Dimensions | Value (in mm) |
|----------------|---------------|
| Z | 6.5 |
| G | 1.5 |
| X | 1.7 |
| Y | 2.5 |
| C | 4.0 |

| SMB Dimensions | Value (in mm) |
|----------------|---------------|
| Z | 6.7 |
| G | 1.8 |
| X | 2.3 |
| Y | 2.5 |
| C | 4.3 |

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.