

**Micro Commercial Components** 

Micro Commercial Components 20736 Marilla Street Chatsworth


CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

# BAS19WT BAS20WT BAS21WT

## **Features**

- Power dissipation: 200mW (T<sub>amb</sub>=25 °C)
- Collector current: 200mA



Marking: BAS19W KA8 BAS20W KT2

BAS21W KT3


# 200mW Switching Diode

## **Maximum Ratings**

- Operating Temperature: -55<sup>o</sup>C to +150<sup>o</sup>C
- Storage Temperature: -55°C to +150°C
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1

#### Electrical Characteristics @ 25°C Unless Otherwise Specified

| Reverse Voltage       |                |       |                                   |
|-----------------------|----------------|-------|-----------------------------------|
| BAS19WT               |                | 100V  |                                   |
| BAS20WT               | $V_R$          | 150V  | I <sub>R</sub> =100 μ A           |
| BAS21WT               |                | 200V  |                                   |
| Peak Forward Current  | I <sub>F</sub> | 200mA |                                   |
| Maximum               |                |       |                                   |
| Instantaneous Forward | $V_{F}$        | 1.0V  | I <sub>FM</sub> =100mA;           |
| Voltage               |                | 1.25V | I <sub>FM</sub> =200mA;           |
| Maximum DC Reverse    |                |       | V <sub>R</sub> =100Volts(BAS19WT) |
| Current At Rated DC   | $I_R$          | 0.1μΑ | V <sub>R</sub> =150Volts(BAS20WT) |
| Blocking Voltage      |                | •     | V <sub>R</sub> =200Volts(BAS21WT) |
| Diode Capacitance     | $C_D$          | 5pF   | Measured at 1.0MHz,               |
|                       |                |       | V <sub>R</sub> =0V                |
| Reverse Recovery      | $T_{rr}$       | 50ns  | $I_F=I_R=30mA$                    |
| Time                  |                |       | Irr=0.1I <sub>R</sub>             |



| DIMENSIONS |              |      |             |      |      |
|------------|--------------|------|-------------|------|------|
|            | INCHES       |      | ММ          |      |      |
| DIM        | MIN          | MAX  | MIN         | MAX  | NOTE |
| Α          | .071         | .087 | 1.80        | 2.20 |      |
| В          | .045         | .053 | 1.15        | 1.35 |      |
| O          | .079         | .087 | 2.00        | 2.20 |      |
| D          | .026 Nominal |      | 0.65Nominal |      |      |
| П          | .047         | .055 | 1.20        | 1.40 |      |
| F          | .012         | .016 | .30         | .40  |      |
| Ð          | .000         | .004 | .000        | .100 |      |
| Ι          | .035         | .039 | .90         | 1.00 |      |
| J          | .004         | .010 | .100        | .250 |      |
| K          | .012         | .016 | .30         | .40  |      |

Suggested Solder
Pad Layout

0.70

1.90

1.90



### **Ordering Information**

| Device           | Packing             |
|------------------|---------------------|
| (Part Number)-TP | Tape&Reel3Kpcs/Reel |

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*APPLICATIONS DISCLAIMER\*\*\*

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.