

Discrete POWER & Signal Technologies

FDH / FDLL 600





THE PLACEMENT OF THE EXPANSION GAP HAS NO RELATIONSHIP TO THE LOCATION OF THE CATHODE TERMINAL

COLOR BAND MARKING DEVICE 1ST BAND 2ND BAND WHITE FDLL600 RED

High Conductance Ultra Fast Diode

Sourced from Process 1R. See MMBD1201-1205 for characteristics.

Absolute Maximum Ratings*

TA = 25°C unless otherwise noted

| Symbol | Parameter | Value | Units |
|------------------------|---|-------------|--------|
| W _{IV} | Working Inverse Voltage | 50 | V |
| Io | Average Rectified Current | 200 | mA |
| I _F | DC Forward Current | 400 | mA |
| İf | Recurrent Peak Forward Current | 600 | mA |
| İ _f (surge) | Peak Forward Surge Current Pulse width = 1.0 second Pulse width = 1.0 microsecond | 1.0 4.0 | A A |
| T _{stg} | Storage Temperature Range | -65 to +200 | °C |
| T _J | Operating Junction Temperature | 175 | °C |

^{*}These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

- These ratings are based on a maximum junction temperature of 200 degrees C.
 These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics

TA = 25°C unless otherwise noted

| Symbol | Characteristic | Max | Units |
|-----------------|---|--------------|-------|
| | | FDH/FDLL 600 | |
| P _D | Total Device Dissipation | 500 | mW |
| | Derate above 25°C | 3.33 | mW/°C |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient | 300 | °C/W |

High Conductance Ultra Fast Diode (continued)

Electrical Characteristics

TA = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Max | Units |
|----------------|-----------------------|--|-----|---------------------------------|----------------------|
| B _V | Breakdown Voltage | $I_R = 5.0 \mu A$ | 75 | | V |
| I _R | Reverse Current | V _R = 50 V V _R = 50 V, T _A = 150°C | | 100 100 | nA μA |
| V _F | Forward Voltage | $I_{F} = 1.0 \text{ mA}$ $I_{F} = 10 \text{ mA}$ $I_{F} = 50 \text{ mA}$ $I_{F} = 100 \text{ mA}$ $I_{F} = 200 \text{ mA}$ | | 650 790 860 920 1.0 | mV mV mV mV |
| Co | Diode Capacitance | V _R = 0, f = 1.0 MHz | | 2.5 | pF |
| T_RR | Reverse Recovery Time | $\begin{split} I_F &= I_R = 10 \text{ mA}, \ I_{rr} = 1.0 \text{ mA}, \\ R_L &= 100 \ \Omega \\ I_F &= I_R = 200 \text{ mA}, \ I_{rr} = 20 \text{ mA}, \\ R_L &= 100 \ \Omega \end{split}$ | | 4.0 6.0 | nS nS |

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEXTM ISOPLANARTM
CoolFETTM MICROWIRETM

CROSSVOLTTM POPTM

E²CMOS[™] PowerTrench[™]

FACTTM QSTM

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

 A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|---------------------------|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |