

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

RB521S-30

Features

- Case Material:Molded Plastic. UL Flammability Classificatio Rating 94-0 and MSL Rating 1
- High Reliability
- Low Reverse Current and Low Forward Voltage.
- Small Surface Mount Type
- · Marking:C
- Lead Free Finish/RoHS Compliant("P" Suffix designates RoHS Compliant. See ordering information)


Maximum Ratings

Symbol	Rating	Rating	Unit
V_R	DC Reverse Voltage	30	V
Ιο	Mean Rectifying Current	200	mA
I _{FSM}	Peak Forward Surge Current*	1	Α
T_J	Junction Temperature	125	$^{\circ}\mathbb{C}$
T _{STG}	Storage Temperature	-40 to +125	$^{\circ}\mathbb{C}$

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	тур	wax	Units
V _F	Forward Voltage (I _F =200mAdc)			0.5	Vdc
I _R	Reverse Current (V _R =10Vdc)			30	uAdc

200 mA Schottky Barrier Diode 30 Volts



DIMENSIONS				
	INCHES	MM		
DIM	Type	Туре	NOTE	
Α	.063	1.60		
В	.472	1.20		
С	.032	0.80		
D	.026	0.65		
Е	.012	0.30		
F	.004	0.10		



Ordering Information

Device	Packing
(Part Number)-TP	Tape&Reel3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.