


**OptiMOS® 2 Power-Transistor**
**Features**


- Fast switching MOSFET for SMPS
- Optimized technology for notebook DC/DC converters
- Qualified according to JEDEC<sup>1)</sup> for target applications
- N-channel
- Logic level
- Excellent gate charge  $\times R_{DS(on)}$  product (FOM)
- Very low on-resistance  $R_{DS(on)}$
- Superior thermal resistance
- Avalanche rated
- Pb-free plating; RoHS compliant

**Product Summary**

|                  |     |            |
|------------------|-----|------------|
| $V_{DS}$         | 30  | V          |
| $R_{DS(on),max}$ | 15  | m $\Omega$ |
| $I_D$            | 9.1 | A          |

**PG-DSO-8**


| Type      | Package  | Marking |
|-----------|----------|---------|
| BSO150N03 | PG-DSO-8 | 150N3   |


**Maximum ratings, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified**

| Parameter                           | Symbol         | Conditions  | Value       |              | Unit              |
|-------------------------------------|----------------|---|-------------|--------------|-------------------|
|                                     |                |   | 10 secs     | steady state |                   |
| Continuous drain current            | $I_D$          | $T_A=25\text{ }^\circ\text{C}^{2)}$   | 9.1         | 7.6          | A                 |
|                                     |                | $T_A=70\text{ }^\circ\text{C}^{2)}$   | 7.3         | 6.1          |                   |
| Pulsed drain current                | $I_{D,pulse}$  | $T_A=25\text{ }^\circ\text{C}^{3)}$   | 36          |              |                   |
| Avalanche energy, single pulse      | $E_{AS}$       | $I_D=9.1\text{ A}, R_{GS}=25\text{ }\Omega$   | 82          |              | mJ                |
| Reverse diode $dv/dt$               | $dv/dt$        | $I_D=9.1\text{ A}, V_{DS}=20\text{ V}, di/dt=200\text{ A}/\mu\text{s}, T_{j,max}=150\text{ }^\circ\text{C}$ | 6           |              | kV/ $\mu\text{s}$ |
| Gate source voltage                 | $V_{GS}$       |   | $\pm 20$    |              | V                 |
| Power dissipation                   | $P_{tot}$      | $T_A=25\text{ }^\circ\text{C}^{2)}$   | 2.0         | 1.4          | W                 |
| Operating and storage temperature   | $T_j, T_{stg}$ |   | -55 ... 150 |              | $^\circ\text{C}$  |
| IEC climatic category; DIN IEC 68-1 |                |   | 55/150/56   |              |                   |

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

**Thermal characteristics**

|  |            |  |   |   |     |     |
|--|------------|--|---|---|-----|-----|
| Thermal resistance, junction - soldering point | $R_{thJS}$ |  | - | - | 50  | K/W |
| Thermal resistance, junction - ambient         | $R_{thJA}$ | minimal footprint, $t_p \leq 10$ s                             | - | - | 110 |     |
|  |            | minimal footprint, steady state                                | - | - | 150 |     |
|  |            | 6 cm <sup>2</sup> cooling area <sup>2)</sup> , $t_p \leq 10$ s | - | - | 63  |     |
|  |            | 6 cm <sup>2</sup> cooling area <sup>2)</sup> , steady state    | - | - | 90  |     |

**Electrical characteristics, at  $T_j=25$  °C, unless otherwise specified**
**Static characteristics**

|                                  |               |  |     |      |     |            |
|----------------------------------|---------------|--|-----|------|-----|------------|
| Drain-source breakdown voltage   | $V_{(BR)DSS}$ | $V_{GS}=0$ V, $I_D=1$ mA                       | 30  | -    | -   | V          |
| Gate threshold voltage           | $V_{GS(th)}$  | $V_{DS}=V_{GS}$ , $I_D=25$ $\mu$ A             | 1.2 | 1.6  | 2   |            |
| Zero gate voltage drain current  | $I_{DSS}$     | $V_{DS}=30$ V, $V_{GS}=0$ V, $T_j=25$ °C       | -   | 0.1  | 1   | $\mu$ A    |
|                                  |               | $V_{DS}=30$ V, $V_{GS}=0$ V, $T_j=125$ °C      | -   | 10   | 100 |            |
| Gate-source leakage current      | $I_{GSS}$     | $V_{GS}=20$ V, $V_{DS}=0$ V                    | -   | 10   | 100 | nA         |
| Drain-source on-state resistance | $R_{DS(on)}$  | $V_{GS}=4.5$ V, $I_D=8.4$ A                    | -   | 15.2 | 19  | m $\Omega$ |
|                                  |               | $V_{GS}=10$ V, $I_D=9.1$ A                     | -   | 12.5 | 15  |            |
| Gate resistance                  | $R_G$         |  | -   | 1.5  | -   | $\Omega$   |
| Transconductance                 | $g_{fs}$      | $ V_{DS}  > 2 I_D R_{DS(on)max}$ , $I_D=9.1$ A | 13  | 26   | -   | S          |

<sup>1)</sup>J-STD20 and JESD22

<sup>2)</sup> Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm<sup>2</sup> (one layer, 70  $\mu$ m thick) copper area for drain connection. PCB is vertical in still air.

<sup>3)</sup> See figure 3

| Parameter | Symbol | Conditions | Values |      |      | Unit |
|-----------|--------|------------|--------|------|------|------|
|           |        |            | min.   | typ. | max. |      |

**Dynamic characteristics**

|                              |              |  |   |      |      |    |
|------------------------------|--------------|--|---|------|------|----|
| Input capacitance            | $C_{iss}$    | $V_{GS}=0\text{ V}, V_{DS}=15\text{ V},$<br>$f=1\text{ MHz}$                     | - | 1420 | 1890 | pF |
| Output capacitance           | $C_{oss}$    |  | - | 510  | 680  |    |
| Reverse transfer capacitance | $C_{rss}$    |  | - | 67   | 100  |    |
| Turn-on delay time           | $t_{d(on)}$  | $V_{DD}=15\text{ V}, V_{GS}=10\text{ V},$<br>$I_D=4.5\text{ A}, R_G=2.7\ \Omega$ | - | 5.3  | 7.9  | ns |
| Rise time                    | $t_r$        |  | - | 4.0  | 6.0  |    |
| Turn-off delay time          | $t_{d(off)}$ |  | - | 21   | 31   |    |
| Fall time                    | $t_f$        |  | - | 3.0  | 4.5  |    |

**Gate Charge Characteristics<sup>4)</sup>**

|                              |               |  |   |     |     |    |
|------------------------------|---------------|--|---|-----|-----|----|
| Gate to source charge        | $Q_{gs}$      | $V_{DD}=15\text{ V}, I_D=4.5\text{ A},$<br>$V_{GS}=0\text{ to }5\text{ V}$ | - | 3.9 | 5.2 | nC |
| Gate charge at threshold     | $Q_{g(th)}$   |  | - | 2.3 | 3.0 |    |
| Gate to drain charge         | $Q_{gd}$      |  | - | 2.6 | 4.0 |    |
| Switching charge             | $Q_{sw}$      |  | - | 4.3 | 6.1 |    |
| Gate charge total            | $Q_g$         |  | - | 11  | 15  |    |
| Gate plateau voltage         | $V_{plateau}$ |  | - | 2.8 | -   |    |
| Gate charge total, sync. FET | $Q_{g(sync)}$ | $V_{DS}=0.1\text{ V},$<br>$V_{GS}=0\text{ to }5\text{ V}$                  | - | 9.6 | 13  | nC |
| Output charge                | $Q_{oss}$     | $V_{DD}=15\text{ V}, V_{GS}=0\text{ V}$                                    | - | 12  | 16  |    |


**Reverse Diode**

|                                  |               |  |   |      |    |    |
|----------------------------------|---------------|--|---|------|----|----|
| Diode continuous forward current | $I_S$         | $T_A=25\text{ }^\circ\text{C}$   | - | -    | 2  | A  |
| Diode pulse current              | $I_{S,pulse}$ |  | - | -    | 36 |    |
| Diode forward voltage            | $V_{SD}$      | $V_{GS}=0\text{ V}, I_F=2\text{ A},$<br>$T_j=25\text{ }^\circ\text{C}$ | - | 0.75 | 1  | V  |
| Reverse recovery charge          | $Q_{rr}$      | $V_R=12\text{ V}, I_F=I_S,$<br>$di_F/dt=400\text{ A}/\mu\text{s}$      | - | -    | 10 | nC |

<sup>4)</sup> See figure 16 for gate charge parameter definition


**1 Power dissipation**

$P_{tot}=f(T_A); t_p \leq 10 \text{ s}$



**2 Drain current**


$I_D=f(T_A); V_{GS} \geq 10 \text{ V}; t_p \leq 10 \text{ s}$



**3 Safe operating area**

$I_D=f(V_{DS}); T_A=25 \text{ °C}^1; D=0$


parameter:  $t_p$



**4 Max. transient thermal impedance**

$Z_{thJS}=f(t_p)$


parameter:  $D=t_p/T$



**5 Typ. output characteristics**

$I_D = f(V_{DS}); T_j = 25\text{ °C}$


parameter:  $V_{GS}$



**6 Typ. drain-source on resistance**

$R_{DS(on)} = f(I_D); T_j = 25\text{ °C}$


parameter:  $V_{GS}$



**7 Typ. transfer characteristics**


$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$

parameter:  $T_j$




**8 Typ. forward transconductance**

$g_{fs} = f(I_D); T_j = 25\text{ °C}$



**9 Drain-source on-state resistance**


$R_{DS(on)} = f(T_j); I_D = 9.1 \text{ A}; V_{GS} = 10 \text{ V}$



**10 Typ. gate threshold voltage**


$V_{GS(th)} = f(T_j); V_{GS} = V_{DS}$

parameter:  $I_D$



**11 Typ. capacitances**


$C = f(V_{DS}); V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$



**12 Forward characteristics of reverse diode**

$I_F = f(V_{SD})$


parameter:  $T_j$



**13 Avalanche characteristics**

$I_{AS}=f(t_{AV}); R_{GS}=25 \Omega$


parameter:  $T_{j(start)}$



**14 Typ. gate charge**


$V_{GS}=f(Q_{gate}); I_D=4.5 \text{ A pulsed}$

parameter:  $V_{DD}$



**15 Drain-source breakdown voltage**

$V_{BR(DSS)}=f(T_j); I_D=1 \text{ mA}$






**16 Gate charge waveforms**




Package Outline

PG-DSO-8



FOOTPRINT



1) DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS.

| DIM            | MILLIMETERS |      | INCHES |       |
|----------------|-------------|------|--------|-------|
|                | MIN         | MAX  | MIN    | MAX   |
| A              | -           | 1.75 | -      | 0.069 |
| A1             | 0.10        | -    | 0.004  | -     |
| A2             | 1.25        | 1.65 | 0.049  | 0.065 |
| b              | 0.35        | 0.51 | 0.014  | 0.020 |
| c              | 0.17        | 0.25 | 0.007  | 0.010 |
| D              | 4.80        | 5.00 | 0.189  | 0.197 |
| E              | 5.80        | 6.20 | 0.228  | 0.244 |
| E1             | 3.80        | 4.00 | 0.150  | 0.157 |
| e              | 1.27        |      | 0.050  |       |
| N              | 8           |      | 8      |       |
| L              | 0.39        | 0.89 | 0.015  | 0.035 |
| h              | 0.23        | 0.50 | 0.009  | 0.020 |
| Θ              | 0°          | 8°   | 0°     | 8°    |
| Θ <sub>1</sub> | -           | 19°  | -      | 19°   |
| ccc            | 0.10        |      | 0.004  |       |
| ddd            | 0.25        |      | 0.010  |       |
| F1             | 5.59        | 5.79 | 0.220  | 0.228 |
| F2             | 0.55        | 0.75 | 0.022  | 0.030 |
| F3             | 1.21        | 1.41 | 0.048  | 0.056 |

DOCUMENT NO.  
Z8B00003333

SCALE

EUROPEAN PROJECTION

ISSUE DATE  
09.01.2008

REVISION  
02



**Published by**  
**Infineon Technologies AG**  
**81726 Munich, Germany**  
**© 2007 Infineon Technologies AG**  
**All Rights Reserved.**

**Legal Disclaimer**

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

**Information**

For further information on technology, delivery terms and conditions and prices, please [contact the nearest Infineon Technologies Office \(www.infineon.com\)](http://www.infineon.com).

**Warnings**

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office. Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user