



ALPHA & OMEGA
SEMICONDUCTOR

AO4706

**N-Channel Enhancement Mode Field Effect Transistor
*SRFET™***



General Description

SRFET™ The AO4706/L uses advanced trench technology with a monolithically integrated Schottky diode to provide excellent $R_{DS(ON)}$ and low gate charge. This device is suitable for use as a low side FET in SMPS, load switching and general purpose applications. AO4706 and AO4706L are electrically identical.

-RoHS Compliant

-AO4706L is Halogen Free

Features

V_{DS} (V) = 30V



I_D = 16.5A (V_{GS} = 10V)

$R_{DS(ON)}$ < 6.8mΩ (V_{GS} = 10V)

$R_{DS(ON)}$ < 8.2mΩ (V_{GS} = 4.5V)

UIS TESTED!

R_g, C_{iss}, C_{oss}, C_{rss} Tested



SRFET™

Soft Recovery MOSFET:
Integrated Schottky Diode

Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	V_{DS}	30	V
Gate-Source Voltage	V_{GS}	± 12	V
Continuous Drain Current ^{AF}	I_{DSM}	16.5	A
	I_{DSM}	13.2	
Pulsed Drain Current ^B	I_{DM}	100	A
Avalanche Current ^B	I_{AR}	30	A
Repetitive avalanche energy L=0.3mH ^B	E_{AR}	135	mJ
Power Dissipation	P_{DSM}	3.1	W
	P_{DSM}	2.0	
Junction and Storage Temperature Range	T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient ^A	$R_{\theta JA}$	31	40	°C/W
		59	75	°C/W
Maximum Junction-to-Lead ^C	$R_{\theta JL}$	16	24	°C/W

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	$I_D=1\text{mA}, V_{GS}=0\text{V}$	30			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{DS}=30\text{V}, V_{GS}=0\text{V}$ $T_J=125^\circ\text{C}$	0.02	0.1		mA
			10	20		
I_{GSS}	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS} = \pm 12\text{V}$			0.1	μA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	1.5	1.85	2.4	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=10\text{V}, V_{DS}=5\text{V}$	100			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=16.5\text{A}$ $T_J=125^\circ\text{C}$	5.6	6.8		$\text{m}\Omega$
			8.4	10.5		
V_{SD}	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.37	0.5	V
I_S	Maximum Body-Diode + Schottky Continuous Current				5	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$		4000	5000	pF
C_{oss}	Output Capacitance		520			pF
C_{rss}	Reverse Transfer Capacitance		217			pF
R_g	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		0.6	0.9	Ω
SWITCHING PARAMETERS						
$Q_g(10\text{V})$	Total Gate Charge	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, I_D=17\text{A}$		59	77	nC
$Q_g(4.5\text{V})$	Total Gate Charge		27	35		nC
Q_{gs}	Gate Source Charge		12			nC
Q_{gd}	Gate Drain Charge		11			nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, R_L=0.9\Omega, R_{\text{GEN}}=3\Omega$		9		ns
t_r	Turn-On Rise Time		9			ns
$t_{\text{D(off)}}$	Turn-Off Delay Time		37			ns
t_f	Turn-Off Fall Time		8			ns
t_{rr}	Body Diode Reverse Recovery Time	$I_F=16.5\text{A}, dI/dt=300\text{A}/\mu\text{s}$		17	20	ns
Q_{rr}	Body Diode Reverse Recovery Charge	$I_F=16.5\text{A}, dI/dt=300\text{A}/\mu\text{s}$		21		nC

A: The value of $R_{\theta JA}$ is measured with the device mounted on 1in² FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The value in any given application depends on the user's specific board design.

B: Repetitive rating, pulse width limited by junction temperature $T_{J(\text{MAX})}=150^\circ\text{C}$.

C. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to lead $R_{\theta JL}$ and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using <300 us pulses, duty cycle 0.5% max.







E. These tests are performed with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with $T_A=25^\circ\text{C}$. The SOA curve provides a single pulse rating.

F. The current rating is based on the $t \leq 10\text{s}$ thermal resistance rating.

Rev3: July 2008

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)












Figure 11: Normalized Maximum Transient Thermal Impedance (Note E)



TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS





Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms

