



### OptiMOS<sup>®</sup>-P Small-Signal-Transistor Feature

- P-Channel
- Enhancement mode
- Super Logic Level (2.5 V rated)
- 150°C operating temperature
- Avalanche rated
- dv/dt rated

### Product Summary

$V_{DS}$	-20	V
$R_{DS(on)}$	550	mΩ
$I_D$	-0.58	A

SOT-323



Type	Package	Ordering Code	Marking
BSS 209PW	SOT-323	Q67042-S4074	X3s

### Maximum Ratings, at $T_j = 25\text{ °C}$ , unless otherwise specified

Parameter	Symbol	Value	Unit
Continuous drain current	$I_D$		A
$T_A=25\text{ °C}$		-0.58	
$T_A=70\text{ °C}$		-0.46	
Pulsed drain current	$I_{D\text{ puls}}$	-2.3	
$T_A=25\text{ °C}$			
Avalanche energy, single pulse	$E_{AS}$	3.5	mJ
$I_D=-0.58\text{ A}$ , $V_{DD}=-10\text{ V}$ , $R_{GS}=25\text{ }\Omega$			
Reverse diode dv/dt	dv/dt	-6	kV/ $\mu$ s
$I_S=-0.58\text{ A}$ , $V_{DS}=-16\text{ V}$ , $di/dt=200\text{ A}/\mu\text{s}$ , $T_{jmax}=150\text{ °C}$			
Gate source voltage	$V_{GS}$	$\pm 12$	V
Power dissipation	$P_{tot}$	0.52	W
$T_A=25\text{ °C}$			
Operating and storage temperature	$T_j, T_{stg}$	-55... +150	°C
IEC climatic category; DIN IEC 68-1		55/150/56	

**Thermal Characteristics**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Characteristics</b>					
Thermal resistance, junction - soldering point	$R_{thJS}$	-	-	120	K/W
SMD version, device on PCB:	$R_{thJA}$				
@ min. footprint		-	-	240	
@ 6 cm <sup>2</sup> cooling area <sup>1)</sup>		-	-	160	

**Electrical Characteristics**, at  $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Static Characteristics</b>					
Drain-source breakdown voltage $V_{GS}=0V, I_D=-250\mu A$	$V_{(BR)DSS}$	-20	-	-	V
Gate threshold voltage, $V_{GS} = V_{DS}$ $I_D=-3.5\mu A$	$V_{GS(th)}$	-0.6	-0.9	-1.2	
Zero gate voltage drain current $V_{DS}=-20V, V_{GS}=0, T_j=25^\circ C$ $V_{DS}=-20V, V_{GS}=0, T_j=150^\circ C$	$I_{DSS}$	-	-0.1	-1	$\mu A$
Gate-source leakage current $V_{GS}=-12V, V_{DS}=0$	$I_{GSS}$	-	-10	-100	
Drain-source on-state resistance $V_{GS}=-2.5V, I_D=-0.46A$	$R_{DS(on)}$	-	563	900	$m\Omega$
Drain-source on-state resistance $V_{GS}=-4.5, I_D=-0.58A$	$R_{DS(on)}$	-	369	550	

<sup>1)</sup> Device on 40mm\*40mm\*1.5mm epoxy PCB FR4 with 6cm<sup>2</sup> (one layer, 70  $\mu m$  thick) copper area for drain connection. PCB is vertical without blown air;  $t \leq 10$  sec.

Electrical Characteristics, at  $T_j = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

### Dynamic Characteristics

Transconductance	$g_{fs}$	$ V_{DS}  \geq 2 *  I_D  * R_{DS(on)max}$ $I_D = -0.46\text{A}$	0.87	1.74	-	S
Input capacitance	$C_{iss}$	$V_{GS} = 0, V_{DS} = -15\text{V},$ $f = 1\text{MHz}$	-	89.9	-	pF
Output capacitance	$C_{oss}$		-	40.1	-	
Reverse transfer capacitance	$C_{rss}$		-	31.5	-	
Turn-on delay time	$t_{d(on)}$	$V_{DD} = -10\text{V}, V_{GS} = -4.5\text{V},$ $I_D = -0.58\text{A}, R_G = 6\Omega$	-	4.4	6.6	ns
Rise time	$t_r$		-	5.8	8.7	
Turn-off delay time	$t_{d(off)}$		-	7.6	11.4	
Fall time	$t_f$		-	4.5	6.7	

### Gate Charge Characteristics


Gate to source charge	$Q_{gs}$	$V_{DD} = -10\text{V}, I_D = -0.58\text{A}$	-	-0.12	-0.17	nC
Gate to drain charge	$Q_{gd}$		-	-0.74	-1.1	
Gate charge total	$Q_g$	$V_{DD} = -10\text{V}, I_D = -0.58\text{A},$ $V_{GS} = 0 \text{ to } -4.5\text{V}$	-	-0.92	-1.38	
Gate plateau voltage	$V_{(plateau)}$	$V_{DD} = -10\text{V}, I_D = -0.58\text{A}$	-	-1.7	-	V

### Reverse Diode

Inverse diode continuous forward current	$I_S$	$T_A = 25\text{ }^\circ\text{C}$	-	-	-0.5	A
Inverse diode direct current, pulsed	$I_{SM}$		-	-	-2.3	
Inverse diode forward voltage	$V_{SD}$	$V_{GS} = 0,  I_F  =  I_D $	-	-1.3	-0.88	V
Reverse recovery time	$t_{rr}$	$V_R = -10\text{V},  I_F  =  I_D ,$ $di_F/dt = 100\text{A}/\mu\text{s}$	-	9	11.2	ns
Reverse recovery charge	$Q_{rr}$		-	1.27	1.59	nC

### 1 Power dissipation


$$P_{tot} = f(T_A)$$



### 2 Drain current

$$I_D = f(T_A)$$


parameter:  $|V_{GS}| \geq 4.5 \text{ V}$



### 3 Safe operating area

$$I_D = f(V_{DS})$$


parameter:  $D = 0, T_A = 25 \text{ °C}$



### 4 Transient thermal impedance

$$Z_{thJS} = f(t_p)$$


parameter:  $D = t_p/T$



**5 Typ. output characteristic**

$I_D = f(V_{DS}); T_j = 25^\circ\text{C}$


parameter:  $t_p = 80 \mu\text{s}$



**6 Typ. drain-source on resistance**

$R_{DS(on)} = f(I_D)$


parameter:  $V_{GS}$



**7 Typ. transfer characteristics**

$I_D = f(V_{GS}); |V_{DS}| \geq 2 \times |I_D| \times R_{DS(on)max}$


parameter:  $t_p = 80 \mu\text{s}$



**8 Typ. forward transconductance**

$g_{fs} = f(I_D); T_j = 25^\circ\text{C}$


parameter:  $t_p = 80 \mu\text{s}$



**9 Drain-source on-resistance**

$$R_{DS(on)} = f(T_j)$$


parameter:  $I_D = -0.58 \text{ A}$ ,  $V_{GS} = -4.5 \text{ V}$



**10 Gate threshold voltage**

$$V_{GS(th)} = f(T_j)$$


parameter:  $V_{GS} = V_{DS}$ ,  $I_D = -3.5 \mu\text{A}$



**11 Typ. capacitances**

$$C = f(V_{DS})$$


parameter:  $V_{GS}=0$ ,  $f=1 \text{ MHz}$



**12 Forward character. of reverse diode**

$$I_F = f(V_{SD})$$


parameter:  $T_j$ ,  $t_p = 80 \mu\text{s}$



**13 Typ. avalanche energy**

$$E_{AS} = f(T_j), \text{ par.: } I_D = -0.58 \text{ A}$$


$$V_{DD} = -10 \text{ V}, R_{GS} = 25 \Omega$$



**14 Typ. gate charge**


$$|V_{GS}| = f(Q_{Gate})$$

parameter:  $I_D = -0.58 \text{ A}$  pulsed



**15 Drain-source breakdown voltage**

$$V_{(BR)DSS} = f(T_j)$$



**Published by**  
**Infineon Technologies AG,**  
**Bereichs Kommunikation**  
**St.-Martin-Strasse 53,**  
**D-81541 München**  
**© Infineon Technologies AG 1999**  
**All Rights Reserved.**

**Attention please!**

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

**Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office in Germany or our Infineon Technologies Representatives worldwide (see address list).

**Warnings**

Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.