



## P-Channel 1.5-V (G-S) MOSFET



PRODUCT SUMMARY			
V <sub>DS</sub> (V)	r <sub>DS(on)</sub> (Ω)	I <sub>D</sub> (A)	Q <sub>g</sub> (Typ)
-8	0.023 @ V <sub>GS</sub> = -4.5 V	-7	28
	0.029 @ V <sub>GS</sub> = -2.5 V	-6.2	
	0.036 @ V <sub>GS</sub> = -1.8 V	-5.2	
	0.048 @ V <sub>GS</sub> = -1.5 V	-5.0	

### FEATURES

- TrenchFET® Power MOSFET: 1.5-V Rated
- Ultra-Low On-Resistance
- 100% R<sub>g</sub> Tested

### APPLICATIONS

- Load Switch for Portable Devices



P-Channel MOSFET

Ordering Information: Si3499DV-T1—E3  
Marking Code: B3xxx

ABSOLUTE MAXIMUM RATINGS (T <sub>A</sub> = 25 °C UNLESS OTHERWISE NOTED)					
Parameter		Symbol	5 secs	Steady State	Unit
Drain-Source Voltage		V <sub>DS</sub>	-8		V
Gate-Source Voltage		V <sub>GS</sub>	± 5		
Continuous Drain Current (T <sub>J</sub> = 150 °C) <sup>a</sup>	T <sub>A</sub> = 25 °C	I <sub>D</sub>	-7	-5.3	A
	T <sub>A</sub> = 85 °C		-3.6	-3.9	
Pulsed Drain Current		I <sub>DM</sub>	-20		
Continuous Diode Current (Diode Conduction) <sup>a</sup>		I <sub>S</sub>	-1.7	-0.9	
Maximum Power Dissipation <sup>a</sup>	T <sub>A</sub> = 25 °C	P <sub>D</sub>	2.0	1.1	W
	T <sub>A</sub> = 85 °C		1.0	0.6	
Operating Junction and Storage Temperature Range		T <sub>J</sub> , T <sub>stg</sub>	-55 to 150		°C

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient <sup>a</sup>	t ≤ 5 sec	R <sub>thJA</sub>	45	62.5	°C/W
	Steady State		90	110	
Maximum Junction-to-Foot (Drain)	Steady State	R <sub>thJF</sub>	25	30	

Notes  
a. Surface Mounted on 1" x 1" FR4 Board.





SPECIFICATIONS (T <sub>J</sub> = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static</b>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250 μA	-0.35		-0.75	V
Gate-Body Leakage	I <sub>GSS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±5 V			±100	nA
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>DS</sub> = -8 V, V <sub>GS</sub> = 0 V			-1	μA
		V <sub>DS</sub> = -8 V, V <sub>GS</sub> = 0 V, T <sub>J</sub> = 85 °C			-10	
On-State Drain Current <sup>a</sup>	I <sub>D(on)</sub>	V <sub>DS</sub> = -5 V, V <sub>GS</sub> = -4.5 V	-20			A
Drain-Source On-State Resistance <sup>a</sup>	r <sub>DS(on)</sub>	V <sub>GS</sub> = -4.5 V, I <sub>D</sub> = -7 A		0.019	0.023	Ω
		V <sub>GS</sub> = -2.5 V, I <sub>D</sub> = -6.2 A		0.024	0.029	
		V <sub>GS</sub> = -1.8 V, I <sub>D</sub> = -5.2 A		0.028	0.036	
		V <sub>GS</sub> = -1.5 V, I <sub>D</sub> = -3 A		0.035	0.048	
Forward Transconductance <sup>a</sup>	g <sub>fs</sub>	V <sub>DS</sub> = -5 V, I <sub>D</sub> = -7 A		28		S
Diode Forward Voltage <sup>a</sup>	V <sub>SD</sub>	I <sub>S</sub> = -1.7 A, V <sub>GS</sub> = 0 V		-0.63	-1.1	V
<b>Dynamic<sup>b</sup></b>						
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> = -4 V, V <sub>GS</sub> = -4.5 V, I <sub>D</sub> = -7 A		28	42	nC
Gate-Source Charge	Q <sub>gs</sub>			2.9		
Gate-Drain Charge	Q <sub>gd</sub>			5.8		
Gate Resistance	R <sub>g</sub>		4	8.5	13	Ω
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> = -4 V, R <sub>L</sub> = 4 Ω I <sub>D</sub> ≅ -1 A, V <sub>GEN</sub> = -4.5 V, R <sub>g</sub> = 6 Ω		27	40	ns
Rise Time	t <sub>r</sub>			65	100	
Turn-Off Delay Time	t <sub>d(off)</sub>			210	315	
Fall Time	t <sub>f</sub>			110	165	
Source-Drain Reverse Recovery Time	t <sub>rr</sub>		I <sub>F</sub> = -1.7 A, di/dt = 100 A/μs		40	

Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**






**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**


**On-Resistance vs. Drain Current**




**Capacitance**




**Gate Charge**




**On-Resistance vs. Junction Temperature**



**Source-Drain Diode Forward Voltage**







**On-Resistance vs. Gate-to-Source Voltage**






**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**





**TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)**



Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73138>.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.