

P-Channel 30-V (D-S) MOSFET with Schottky Diode

MOSFET PRODUCT SUMMARY			
V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A) ^a	Q _g (Typ)
- 30	0.072 at V _{GS} = - 10 V	- 4.6	- 4.6
	0.110 at V _{GS} = - 4.5 V	- 3.4	



FEATURES

- LITTLE FOOT® Plus Power MOSFET



RoHS
COMPLIANT

SCHOTTKY PRODUCT SUMMARY		
V _{KA} (V)	V _f (V) Diode Forward Voltage	I _D (A) ^a
30	0.50 V at 1 A	2.4



Ordering Information: Si4833ADY-T1-E3 (Lead (Pb)-free)

P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted				
Parameter	Symbol	Limit	Unit	
Drain-Source Voltage (MOSFET)	V _{DS}	- 30	V	
Reverse Voltage (Schottky)	V _{KA}	- 30		
Gate-Source Voltage (MOSFET)	V _{GS}	± 20		
Continuous Drain Current (T _J = 150 °C) (MOSFET)	I _D	T _C = 25 °C T _C = 70 °C T _A = 25 °C T _A = 70 °C	- 4.6 - 3.6 - 3.85 ^{b, c} - 3.08 ^{b, c}	A
Pulsed Drain Current (MOSFET)		I _{DM}	- 20	
Continuous Source Current (MOSFET Diode Conduction)		I _S	- 2.3 - 1.4 ^{b, c}	
Average Forward Current (Schottky)	I _F	- 1.4 ^b		
Pulsed Forward Current (Schottky)	I _{FM}	- 20		
Maximum Power Dissipation (MOSFET and Schottky)	P _D	T _C = 25 °C T _C = 70 °C T _A = 25 °C T _A = 70 °C	2.75 1.75 1.93 ^{b, c} 1.23 ^{b, c}	W
Operating Junction and Storage Temperature Range		T _J , T _{stg}	- 55 to 150	
			°C	

THERMAL RESISTANCE RATINGS				
Parameter	Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient (MOSFET and Schottky) ^{b, c, d}	R _{thJA}	60	65	°C/W
Maximum Junction-to-Foot (Drain) (MOSFET and Schottky)	R _{thJF}	35	45	

Notes:

- a. Based on T_C = 25 °C.
- b. Surface Mounted on FR4 Board.
- c. t ≤ 10 sec.
- d. Maximum under Steady State conditions is 120 °C/W.

MOSFET SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V_{DS}	$V_{DS} = 0 \text{ V}, I_D = -250 \mu\text{A}$	-30			V
V_{DS} Temperature Coefficient	$\Delta V_{DS/TJ}$	$I_D = 250 \mu\text{A}$		-28		mV/°C
$V_{GS(\text{th})}$ Temperature Coefficient	$\Delta V_{GS(\text{th})/TJ}$			3.5		
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	-1		-2.5	V
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 20 \text{ V}$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -30 \text{ V}, V_{GS} = 0 \text{ V}$			-1	μA
		$V_{DS} = -30 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 75^\circ\text{C}$			-10	
On-State Drain Current ^a	$I_{D(\text{on})}$	$V_{DS} \geq -5 \text{ V}, V_{GS} = -10 \text{ V}$	-5			A
Drain-Source On-State Resistance ^a	$r_{DS(\text{on})}$	$V_{GS} = -10 \text{ V}, I_D = -3.6 \text{ A}$		0.059	0.072	Ω
		$V_{GS} = -4.5 \text{ V}, I_D = -2.8 \text{ A}$		0.090	0.110	
Forward Transconductance ^a	g_{fs}	$V_{DS} = -15 \text{ V}, I_D = -3.6 \text{ A}$		7		S
Dynamic^b						
Input Capacitance	C_{iss}	$V_{DS} = -15 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$		380	750	pF
Output Capacitance	C_{oss}			100		
Reverse Transfer Capacitance	C_{rss}			75		
Total Gate Charge	Q_g	$V_{DS} = -15 \text{ V}, V_{GS} = -10 \text{ V}, I_D = -3 \text{ A}$		9.8	15	nC
Gate-Source Charge	Q_{gs}			4.6	7.0	
Gate-Drain Charge	Q_{gd}			1.4		
Gate Resistance	R_g		$f = 1 \text{ MHz}$	8	16	Ω
Turn-On Delay Time	$t_{d(\text{on})}$	$V_{DD} = -15 \text{ V}, R_L = 7.5 \Omega$ $I_D \equiv -2 \text{ A}, V_{GEN} = -4.5 \text{ V}, R_G = 1 \Omega$		20	30	ns
Rise Time	t_r			59	90	
Turn-Off Delay Time	$t_{d(\text{off})}$			26	40	
Fall Time	t_f			19	30	
Turn-On Delay Time	$t_{d(\text{on})}$			7	14	
Rise Time	t_r	$V_{DD} = -15 \text{ V}, R_L = 7.5 \Omega$ $I_D \equiv -2 \text{ A}, V_{GEN} = -10 \text{ V}, R_G = 1 \Omega$		11	17	ns
Turn-Off Delay Time	$t_{d(\text{off})}$			19	30	
Fall Time	t_f			8	15	
Drain-Source Body Diode Characteristics						
Continuous Source-Drain Diode Current	I_S	$T_C = 25^\circ\text{C}$			-4.6	A
Pulse Diode Forward Current ^a	I_{SM}				-20	
Body Diode Voltage	V_{SD}	$I_S = -1.4 \text{ A}, V_{GS} = 0 \text{ V}$		-0.8	-1.2	V
Body Diode Reverse Recovery Time	t_{rr}	$I_F = -2 \text{ A}, di/dt = 100 \text{ A}/\mu\text{s}, T_J = 25^\circ\text{C}$		23	40	ns
Body Diode Reverse Recovery Charge	Q_{rr}			12	20	nC
Reverse Recovery Fall Time	t_a			10		ns
Reverse Recovery Rise Time	t_b			13		

Notes:







- a. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.
b. Guaranteed by design, not subject to production testing.






**SCHOTTKY SPECIFICATIONS** $T_J = 25 \text{ }^{\circ}\text{C}$, unless otherwise noted


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Forward Voltage Drop	V_F	$I_F = 1 \text{ A}$		0.45	0.50	V
		$I_F = 1 \text{ A}, T_J = 125 \text{ }^{\circ}\text{C}$		0.36	0.42	
Maximum Reverse Leakage Current	I_{rm}	$V_r = 30 \text{ V}$		0.004	0.1	mA
		$V_r = 30 \text{ V}, T_J = 75 \text{ }^{\circ}\text{C}$		0.1	2	
		$V_r = 30 \text{ V}, T_J = 125 \text{ }^{\circ}\text{C}$		3	20	
Junction Capacitance	C_T	$V_r = 10 \text{ V}$		62		pF

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power, Junction-to-Ambient

*** $V_{GS} >$ minimum V_{GS} at which $r_{DS(on)}$ is specified**
Safe Operating Area, Junction-to-Case

MOSFET TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted T_C – Case Temperature (°C)

Current Derating*



 T_C – Case Temperature (°C)

Power Derating, Junction-to-Foot


 T_C – Case Temperature (°C)

Power Derating, Junction-to-Ambient


*The power dissipation P_D is based on $T_{J(\max)} = 175$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

MOSFETS TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Normalized Thermal Transient Impedance, Junction-to-Ambient

Normalized Thermal Transient Impedance, Junction-to-Foot


*The power dissipation PD is based on $T_{J(max)} = 175 \text{ }^{\circ}\text{C}$, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

SCHOTTKY TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Reverse Current vs. Junction Temperature



Forward Voltage Drop



Capacitance

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?73627>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.