

P-Channel 20-V (D-S) MOSFET

PRODUCT SUMMARY		
V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)
- 20	0.027 at V _{GS} = - 4.5 V	- 8.2
	0.032 at V _{GS} = - 2.5 V	- 7.5
	0.045 at V _{GS} = - 1.8 V	- 6.6

FEATURES

- TrenchFET[®] Power MOSFET
- MICRO FOOT[®] Chipscale Packaging
Reduces Ultra-Low Footprint Area Profile (0.62 mm) and On-Resistance




RoHS
COMPLIANT

APPLICATIONS


- Portable Devices
 - PA Switch
 - Battery Switch
 - Load Switch

MICRO FOOT



Device Marking: 8407
xxx = Date/Lot Traceability Code

Ordering Information: Si8407DB-T2-E1 (Lead (Pb)-free)



P-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS T _A = 25 °C, unless otherwise noted				
Parameter	Symbol	5 s	Steady State	Unit
Drain-Source Voltage	V _{DS}	- 20		V
Gate-Source Voltage	V _{GS}	± 8		
Continuous Drain Current (T _J = 150 °C) ^a	T _A = 25 °C	- 8.2	- 5.8	A
	T _A = 70 °C	- 6.5	- 4.6	
Pulsed Drain Current	I _{DM}	- 15		
Continuous Source Current (Diode Conduction) ^a	I _S	- 2.6	- 1.34	
Maximum Power Dissipation ^a	T _A = 25 °C	2.9	1.47	W
	T _A = 70 °C	1.86	0.94	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 150		°C
Package Reflow Conditions ^b	IR/Convection	260		

THERMAL RESISTANCE RATINGS					
Parameter		Symbol	Typical	Maximum	Unit
Maximum Junction-to-Ambient ^a	t ≤ 5 s	R _{thJA}	33	43	°C/W
	Steady State		72	85	
Maximum Junction-to-Foot (drain)	Steady State	R _{thJF}	15	19	

Notes:

a. Surface Mounted on 1" x 1" FR4 board.

b. Refer to IPC/JEDEC (J-STD-020C), no manual or hand soldering.





SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted						
Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static						
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = -350\ \mu\text{A}$	-0.4		-0.9	V
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0\ \text{V}, V_{GS} = \pm 8\ \text{V}$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = -20\ \text{V}, V_{GS} = 0\ \text{V}$			-1	μA
		$V_{DS} = -20\ \text{V}, V_{GS} = 0\ \text{V}, T_J = 70^\circ\text{C}$			-5	
On-State Drain Current ^a	$I_{D(on)}$	$V_{DS} \leq -5\ \text{V}, V_{GS} = -4.5\ \text{V}$	-5			A
Drain-Source On-State Resistance ^a	$R_{DS(on)}$	$V_{GS} = -4.5\ \text{V}, I_D = -1\ \text{A}$		0.022	0.027	Ω
		$V_{GS} = -2.5\ \text{V}, I_D = -1\ \text{A}$		0.026	0.032	
		$V_{GS} = -1.8\ \text{V}, I_D = -1\ \text{A}$		0.033	0.045	
Forward Transconductance ^a	g_{fs}	$V_{DS} = -10\ \text{V}, I_D = -1\ \text{A}$		10		S
Diode Forward Voltage ^a	V_{SD}	$I_S = -1\ \text{A}, V_{GS} = 0\ \text{V}$		-0.6	-1.1	V
Dynamic^b						
Total Gate Charge	Q_g	$V_{DS} = -10\ \text{V}, V_{GS} = -4.5\ \text{V}, I_D = -1\ \text{A}$		32	50	nC
Gate-Source Charge	Q_{gs}			3.6		
Gate-Drain Charge	Q_{gd}			8.5		
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = -10\ \text{V}, R_L = 10\ \Omega$ $I_D \cong -1\ \text{A}, V_{GEN} = -4.5\ \text{V}, R_g = 6\ \Omega$		30	45	ns
Rise Time	t_r			45	70	
Turn-Off Delay Time	$t_{d(off)}$			550	825	
Fall Time	t_f			220	330	
Source-Drain Reverse Recovery Time	t_{rr}	$I_F = -1\ \text{A}, di/dt = 100\ \text{A}/\mu\text{s}$		265	500	

Notes:


- a. Pulse test; pulse width $\leq 300\ \mu\text{s}$, duty cycle $\leq 2\%$.
- b. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


TYPICAL CHARACTERISTICS 25°C , unless otherwise noted




TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




On-Resistance vs. Drain Current




Capacitance




Gate Charge



On-Resistance vs. Junction Temperature







Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage

TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



PACKAGE OUTLINE

MICRO FOOT: 6-BUMP (2.4 x 2.0, 8 mm PITCH)



- Notes (Unless Otherwise Specified):
1. All dimensions are in millimeters.
 2. Bumps are 95.5/3.8/0.7 Sn/Ag/Cu with diameter ϕ 0.38 - 0.40 mm.
 3. Backside surface is coated with a Ti/Ni/Ag layer.
 4. Non-solder mask defined copper landing pad.
 5. The flat side of wafers is oriented at the bottom.
 6. • is location of Pin 1P.

Dim.	Millimeters ^a		Inches	
	Min.	Max.	Min.	Max.
A	0.600	0.650	0.0236	0.0256
A₁	0.260	0.290	0.0102	0.0114
A₂	0.340	0.360	0.0134	0.0142
b	0.370	0.410	0.0146	0.0161
D	1.920	2.000	0.0756	0.0787
E	2.320	2.400	0.0913	0.0945
e	0.750	0.400	0.0150	0.0335
S	0.370	0.400	0.0150	0.0157
S1	0.580	0.600	0.0228	0.0236

PAD DISTRIBUTION TABLE			
	P	Q	R
1	Drain	Gate	Source
2	Drain	Source	Source

Notes:

a. Use millimeters as the primary measurement.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?72254>.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.