

**OptiMOS® Power-Transistor**
**Features**

- N-channel
- Enhancement mode
- Logic level
- Excellent gate charge x  $R_{DS(on)}$  product (FOM)
- Superior thermal resistance
- 175 °C operating temperature
- Avalanche rated
- $dv/dt$  rated


**Product Summary**

$V_{DS}$	30	V
$R_{DS(on),max}$	12.9	mΩ
$I_D$	42	A


P-TO262-3-1

P-TO263-3-2

P-TO220-3-1



Type	Package	Ordering Code	Marking
SPP42N03S2L-13	P-TO220-3-1	Q67042-S4034	2N03L13
SPB42N03S2L-13	P-TO263-3-2	Q67042-S4035	2N03L13
SPI42N03S2L-13	P-TO262-3-1	Q67042-S4104	2N03L13


**Maximum ratings, at  $T_j=25\text{ °C}$ , unless otherwise specified**

Parameter	Symbol	Conditions	Value	Unit
Continuous drain current <sup>1)</sup>	$I_D$	$T_C=25\text{ °C}$	42	A
		$T_C=100\text{ °C}$	42	
Pulsed drain current	$I_{D,pulse}$	$T_C=25\text{ °C}$	248	
Avalanche energy, single pulse	$E_{AS}$	$I_D=42\text{ A}$ , $R_{GS}=25\text{ Ω}$	110	mJ
Repetitive avalanche energy	$E_{AR}$	limited by $T_{jmax}$ <sup>2)</sup>	8	mJ
Reverse diode $dv/dt$	$dv/dt$	$I_D=42\text{ A}$ , $V_{DS}=24\text{ V}$ , $di/dt=200\text{ A/μs}$ , $T_{j,max}=175\text{ °C}$	6	kV/μs
Gate source voltage	$V_{GS}$		±20	V
Power dissipation	$P_{tot}$	$T_C=25\text{ °C}$	83	W
Operating and storage temperature	$T_j$ , $T_{stg}$		-55 ... 175	°C
IEC climatic category; DIN IEC 68-1			55/175/56	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Thermal characteristics**

Thermal resistance, junction - case	$R_{thJC}$		-	1.2	1.8	K/W
SMD version, device on PCB	$R_{thJA}$	minimal footprint	-	-	62	
		6 cm <sup>2</sup> cooling area <sup>3)</sup>	-	-	40	

**Electrical characteristics, at  $T_j=25\text{ }^\circ\text{C}$ , unless otherwise specified**
**Static characteristics**

Drain-source breakdown voltage	$V_{(BR)DSS}$	$V_{GS}=0\text{ V}, I_D=1\text{ mA}$	30	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=37\text{ }\mu\text{A}$	1.2	1.6	2	
Zero gate voltage drain current	$I_{DSS}$	$V_{DS}=30\text{ V}, V_{GS}=0\text{ V}, T_j=25\text{ }^\circ\text{C}$	-	0.01	1	$\mu\text{A}$
		$V_{DS}=30\text{ V}, V_{GS}=0\text{ V}, T_j=125\text{ }^\circ\text{C}$	-	10	100	
Gate-source leakage current	$I_{GSS}$	$V_{GS}=20\text{ V}, V_{DS}=0\text{ V}$	-	1	100	nA
Drain-source on-state resistance <sup>4)</sup>	$R_{DS(on)}$	$V_{GS}=4.5\text{ V}, I_D=21\text{ A}$	-	14.9	19.9	m $\Omega$
		$V_{GS}=4.5\text{ V}, I_D=21\text{ A},$ SMD version	-	14.5	19.6	
		$V_{GS}=10\text{ V}, I_D=21\text{ A}$	-	10.3	12.9	
		$V_{GS}=10\text{ V}, I_D=21\text{ A},$ SMD version	-	9.9	12.6	
Gate resistance	$R_G$		-	1	-	$\Omega$
Transconductance	$g_{fs}$	$ V_{DS} >2 I_D R_{DS(on)max},$ $I_D=42\text{ A}$	21	42	-	S

<sup>1)</sup> Current is limited by bondwire; with an  $R_{thJC}=1.8\text{ K/W}$  the chip is able to carry 64 A at 25°C, for detailed information see app.-note ANPS071E at [www.infineon.com/optimos](http://www.infineon.com/optimos).

<sup>2)</sup> Defined by design. Not subject to production test.

<sup>3)</sup> Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm<sup>2</sup> (one layer, 70  $\mu\text{m}$  thick) copper area for drain connection. PCB is vertical in still air.

<sup>4)</sup> Diagrams are related to straight lead versions.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	

**Dynamic characteristics**

Input capacitance	$C_{iss}$	$V_{GS}=0\text{ V}, V_{DS}=25\text{ V},$ $f=1\text{ MHz}$	-	850	1130	pF
Output capacitance	$C_{oss}$		-	330	440	
Reverse transfer capacitance	$C_{rss}$		-	90	130	
Turn-on delay time	$t_{d(on)}$	$V_{DD}=15\text{ V}, V_{GS}=10\text{ V},$ $I_D=21\text{ A}, R_G=7.8\ \Omega$	-	6.5	9.8	ns
Rise time	$t_r$		-	12	18	
Turn-off delay time	$t_{d(off)}$		-	24	36	
Fall time	$t_f$		-	14.5	21.8	

**Gate Charge Characteristics**


Gate to source charge	$Q_{gs}$	$V_{DD}=24\text{ V}, I_D=21\text{ A},$ $V_{GS}=0\text{ to }10\text{ V}$	-	2.7	3.6	nC
Gate to drain charge	$Q_{gd}$		-	7.9	11.9	
Gate charge total	$Q_g$		-	22.9	30.5	
Gate plateau voltage	$V_{plateau}$		-	3.5	-	V

**Reverse Diode**

Diode continuous forward current	$I_S$	$T_C=25\text{ }^\circ\text{C}$	-	-	42	A
Diode pulse current	$I_{S,pulse}$		-	-	248	
Diode forward voltage	$V_{SD}$	$V_{GS}=0\text{ V}, I_F=42\text{ A},$ $T_J=25\text{ }^\circ\text{C}$	-	0.95	1.25	V
Reverse recovery time	$t_{rr}$	$V_R=15\text{ V}, I_F=I_S,$ $di_F/dt=100\text{ A}/\mu\text{s}$	-	24	31	ns
Reverse recovery charge	$Q_{rr}$		-	18	23	


**1 Power dissipation**

$P_{tot}=f(T_C)$



**2 Drain current**


$I_D=f(T_C); V_{GS} \geq 10\text{ V}$



**3 Safe operating area**

$I_D=f(V_{DS}); T_C=25\text{ °C}; D=0$


parameter:  $t_p$



**4 Max. transient thermal impedance**

$Z_{thJC}=f(t_p)$


parameter:  $D=t_p/T$



**5 Typ. output characteristics**

$I_D = f(V_{DS}); T_j = 25\text{ °C}$


parameter:  $V_{GS}$



**6 Typ. drain-source on resistance**

$R_{DS(on)} = f(I_D); T_j = 25\text{ °C}$


parameter:  $V_{GS}$



**7 Typ. transfer characteristics**


$I_D = f(V_{GS}); |V_{DS}| > 2|I_D|R_{DS(on)max}$

parameter:  $T_j$




**8 Typ. forward transconductance**

$g_{fs} = f(I_D); T_j = 25\text{ °C}$



**9 Drain-source on-state resistance**


$R_{DS(on)}=f(T_j); I_D=21\text{ A}; V_{GS}=10\text{ V}$



**10 Typ. gate threshold voltage**


$V_{GS(th)}=f(T_j); V_{GS}=V_{DS}$

parameter:  $I_D$



**11 Typ. capacitances**


$C=f(V_{DS}); V_{GS}=0\text{ V}; f=1\text{ MHz}$



**12 Forward characteristics of reverse diode**

$I_F=f(V_{SD})$


parameter:  $T_j$



**13 Avalanche characteristics**

$E_{AS} = f(T_j)$


parameter:  $I_D = 42A, V_{DD} = 25V, R_{GS} = 25\Omega$



**14 Typ. gate charge**


$V_{GS} = f(Q_{gate}); I_D = 21A$  pulsed

parameter:  $V_{DD}$




**15 Drain-source breakdown voltage**

$V_{BR(DSS)} = f(T_j); I_D = 1mA$




**16 Gate charge waveforms**




Package Outline


P-TO263-3-2: Outline



Footprint




Packaging



1) Typical  
All metal surfaces tin plated, except area of cut.

GPT09085

P-TO262-3-1: Outline




1) Typical  
Metal surface min. X = 7.25, Y = 6.9  
All metal surfaces tin plated, except area of cut.

Dimensions in mm




Package Outline

P-TO220-3-1: Outline



Packaging



<sup>1)</sup> Typical

All metal surfaces tin plated, except area of cut.  
Metal surface min.  $x=7.25$ ,  $y=12.3$

Dimensions in mm

**Published by**  
**Infineon Technologies AG**  
**Bereich Kommunikation**  
**St.-Martin-Straße 53**  
**D-81541 München**  
**© Infineon Technologies AG 1999**  
**All Rights Reserved.**

**Attention please!**

The information herein is given to describe certain components and shall not be considered as warranted characteristics.

Terms of delivery and rights to technical change reserved.

We hereby disclaim any and all warranties, including but not limited to warranties of non-infringement, regarding circuits, descriptions and charts stated herein.

Infineon Technologies is an approved CECC manufacturer.

**Information**

For further information on technology, delivery terms and conditions and prices, please contact your nearest Infineon Technologies office in Germany or our Infineon Technologies representatives worldwide (see address list).

**Warnings**

Due to technical requirements, components may contain dangerous substances.  
For information on the types in question, please contact your nearest Infineon Technologies office.

Infineon Technologies' components may only be used in life-support devices or systems with the expressed written approval of Infineon Technologies if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

**Further information**

Please note that the part number is BSPP42N03S2L-13, BSPB42N03S2L-13 and BSPI42N03S2L-13, for simplicity the device is referred to by the term SPP42N03S2L-13, SPB42N03S2L-13, SPI42N03S2L-13 throughout this documentation.