


Main features

| Symbol | Value | Unit |
|------------------------------|---------|------|
| $I_{T(RMS)}$ | 12 | A |
| V_{DRM}/V_{RRM} | 600 | V |
| $I_{GT} \text{ (min / max)}$ | 1.5 / 5 | mA |

Description

The TYN612M SCR is suitable to fit modes of control found in applications such as voltage regulation circuits for motorbikes, overvoltage crowbar protection, motor control circuits in power tools and kitchen aids, inrush current limiting circuits, capacitive discharge ignition.

The insulated fullpack package allows a back to back configuration.



Order codes

| Part Numbers | Marking |
|--------------|-----------|
| TYN612MRG | TYN612M |
| TYN612MFP | TYN612MFP |

Table 1. Absolute ratings (limiting values)

| Symbol | Parameter | Value | Unit | |
|--------------------|--|--|-----------------------|--------------------|
| $I_{T(RMS)}$ | RMS on-state current (180° conduction angle) | TO-220AB $T_c = 105^\circ \text{ C}$ | 12 | A |
| | | TO-220FPAB $T_c = 70^\circ \text{ C}$ | 12 | |
| $I_{T(AV)}$ | Average on-state current (180° conduction angle) | TO-220AB $T_c = 105^\circ \text{ C}$ | 8 | A |
| | | TO-220FPAB $T_c = 70^\circ \text{ C}$ | 8 | |
| I_{TSM} | Non repetitive surge peak on-state current | $t_p = 8.3 \text{ ms}$ $T_j = 25^\circ \text{ C}$ | 125 | A |
| | | | $t_p = 10 \text{ ms}$ | |
| I^2t | I^2t Value for fusing | $t_p = 10 \text{ ms}$ $T_j = 25^\circ \text{ C}$ | 72 | A^2s |
| dI/dt | Critical rate of rise of on-state current $I_G = 2 \times I_{GT}$, $t_r \leq 100 \text{ ns}$ | F = 60 Hz $T_j = 125^\circ \text{ C}$ | 50 | A/ μs |
| I_{GM} | Peak gate current | $t_p = 20 \mu s$ $T_j = 125^\circ \text{ C}$ | 4 | A |
| $P_{G(AV)}$ | Average gate power dissipation | $T_j = 125^\circ \text{ C}$ | 1 | W |
| T_{stg} T_j | Storage junction temperature range | | - 40 to + 150 | $^\circ \text{ C}$ |
| | Operating junction temperature range | | - 40 to + 125 | |
| V_{RGM} | Maximum peak reverse gate voltage | | 5 | V |

1 Characteristics

Table 2. Electrical characteristics ($T_j = 25^\circ\text{C}$, unless otherwise specified)

| Symbol | Test Conditions | | Value | Unit | |
|------------------------|---|---------------------------|-------|------|------------------|
| I_{GT} | $V_D = 12\text{ V}$ $R_L = 140\ \Omega$ | MIN. | 1.5 | mA | |
| | | MAX. | 5 | | |
| V_{GT} | $V_D = 12\text{ V}$ $R_L = 140\ \Omega$ | MIN. | 0.5 | V | |
| | | TYP. | 0.7 | | |
| | | MAX. | 1.3 | | |
| V_{GD} | $V_D = V_{DRM}$ $R_L = 3.3\text{ k}\Omega$ | $T_j = 125^\circ\text{C}$ | MIN. | 0.2 | V |
| I_H | $I_T = 500\text{ mA}$ Gate open | | MAX. | 20 | mA |
| I_L | $I_G = 1.2 I_{GT}$ | | MAX. | 40 | mA |
| dV/dt | $V_D = 67\% V_{DRM}$ Gate open | $T_j = 125^\circ\text{C}$ | MIN. | 50 | V/ μs |
| V_{TM} | $I_{TM} = 24\text{ A}$ $t_p = 380\ \mu\text{s}$ | $T_j = 25^\circ\text{C}$ | MAX. | 1.6 | V |
| V_{t0} | Threshold voltage | $T_j = 125^\circ\text{C}$ | MAX. | 0.85 | V |
| R_d | Dynamic resistance | $T_j = 125^\circ\text{C}$ | MAX. | 30 | m Ω |
| I_{DRM} I_{RRM} | $V_{DRM} = V_{RRM}$ | $T_j = 25^\circ\text{C}$ | MAX. | 5 | μA |
| | | $T_j = 125^\circ\text{C}$ | | 2 | mA |

Table 3. Thermal resistance

| Symbol | Parameter | | Value | Unit |
|---------------|--------------------------|------------|-------|--------------------|
| $R_{th(j-c)}$ | Junction to case (DC) | TO-220AB | 1.3 | $^\circ\text{C/W}$ |
| | | TO-220FPAB | 4.5 | |
| $R_{th(j-a)}$ | Junction to ambient (DC) | TO-220AB | 55 | $^\circ\text{C/W}$ |
| | | TO-220FPAB | 55 | |

Figure 1. Maximum average power dissipation versus average on-state current




Figure 2. Average and D.C. on-state current versus case temperature (TO-220AB)




Figure 3. Average and D.C. on-state current versus case temperature (TO-220FPAB)




Figure 4. Relative variation of thermal impedance versus pulse duration (TO-220AB)




Figure 5. Relative variation of thermal impedance versus pulse duration (TO-220FPAB)




Figure 6. Relative variation of gate trigger current, holding current, latching current and gate trigger voltage versus junction temperature (typical values)




Figure 7. Surge peak on-state current versus number of cycles




Figure 8. Non-repetitive surge peak on-state current for a sinusoidal pulse with width t_p < 10 ms, and corresponding values of I²t






Figure 9. On-state characteristics (maximum values)




2 Ordering information scheme



3 Package information

- Epoxy meets UL94, V0

Table 4. TO-220AB dimensions



| Ref. | Dimensions | | | | | |
|------|-------------|-------|-------|--------|-------|-------|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 15.20 | | 15.90 | 0.598 | | 0.625 |
| a1 | | 3.75 | | | 0.147 | |
| a2 | 13.00 | | 14.00 | 0.511 | | 0.551 |
| B | 10.00 | | 10.40 | 0.393 | | 0.409 |
| b1 | 0.61 | | 0.88 | 0.024 | | 0.034 |
| b2 | 1.23 | | 1.32 | 0.048 | | 0.051 |
| C | 4.40 | | 4.60 | 0.173 | | 0.181 |
| c1 | 0.49 | | 0.70 | 0.019 | | 0.027 |
| c2 | 2.40 | | 2.72 | 0.094 | | 0.107 |
| e | 2.40 | | 2.70 | 0.094 | | 0.106 |
| F | 6.20 | | 6.60 | 0.244 | | 0.259 |
| ØI | 3.75 | | 3.85 | 0.147 | | 0.151 |
| I4 | 15.80 | 16.40 | 16.80 | 0.622 | 0.646 | 0.661 |
| L | 2.65 | | 2.95 | 0.104 | | 0.116 |
| I2 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| I3 | 1.14 | | 1.70 | 0.044 | | 0.066 |
| M | | 2.60 | | | 0.102 | |

Table 5. TO-220FPAB Dimensions

| Ref. | Dimensions | | | |
|------|-------------|------|-----------|-------|
| | Millimeters | | Inches | |
| | Min. | Max. | Min. | Max. |
| A | 4.4 | 4.6 | 0.173 | 0.181 |
| B | 2.5 | 2.7 | 0.098 | 0.106 |
| D | 2.5 | 2.75 | 0.098 | 0.108 |
| E | 0.45 | 0.70 | 0.018 | 0.027 |
| F | 0.75 | 1 | 0.030 | 0.039 |
| F1 | 1.15 | 1.70 | 0.045 | 0.067 |
| F2 | 1.15 | 1.70 | 0.045 | 0.067 |
| G | 4.95 | 5.20 | 0.195 | 0.205 |
| G1 | 2.4 | 2.7 | 0.094 | 0.106 |
| H | 10 | 10.4 | 0.393 | 0.409 |
| L2 | 16 Typ. | | 0.63 Typ. | |
| L3 | 28.6 | 30.6 | 1.126 | 1.205 |
| L4 | 9.8 | 10.6 | 0.386 | 0.417 |
| L5 | 2.9 | 3.6 | 0.114 | 0.142 |
| L6 | 15.9 | 16.4 | 0.626 | 0.646 |
| L7 | 9.00 | 9.30 | 0.354 | 0.366 |
| Dia. | 3.00 | 3.20 | 0.118 | 0.126 |

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a lead-free second level interconnect. The category of second level interconnect is marked on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com.

4 Ordering information

| Ordering type | Marking | Package | Weight | Base qty | Delivery mode |
|---------------|-----------|----------|--------|----------|---------------|
| TYN612MRG | TYN612M | TO-220AB | 2.3 g | 50 | Tube |
| TYN612MFP | TYN612MFP | TO-220AB | 2.0 g | 50 | Tube |

5 Revision history

| Date | Revision | Description of Changes |
|-------------|----------|--|
| Sep-2002 | 1A | Last update. |
| 10-Fev-2005 | 2 | TO-220FPAB package added. |
| 11-Apr-2007 | 3 | Reformatted to current standards. Added typical and minimum values for V_{GT} in Table 2 . |
| 17-Apr-2007 | 4 | Added V_{GT} curve in Figure 6 . |

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com