



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

2N4403

PNP General Purpose Amplifier

Features

- Through Hole Package
- Capable of 600mWatts of Power Dissipation
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL rating 1
- Marking: Type number
- Lead Free Finish/Rohs Compliant ("P" Suffix designates Compliant. See ordering information)

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Units
OFF CHARACTERISTICS				
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage* ($I_C = -1.0mA$, $I_B = 0$)	-40		Vdc
$V_{(BR)CBO}$	Collector-Base Breakdown Voltage ($I_C = -10\mu A$, $I_E = 0$)	-40		Vdc
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ($I_E = -10\mu A$, $I_C = 0$)	-5.0		Vdc
I_{BL}	Base Cutoff Current ($V_{CE} = -3.0V$, $V_{BE} = -3.0V$)		-0.1	μA
I_{CEX}	Collector Cutoff Current ($V_{CE} = -3.0V$, $V_{BE} = -3.0V$)		-0.1	μA

ON CHARACTERISTICS

h_{FE}	DC Current Gain* ($I_C = -0.1mA$, $V_{CE} = -1.0V$) ($I_C = -1.0mA$, $V_{CE} = -1.0V$) ($I_C = -10mA$, $V_{CE} = -1.0V$) ($I_C = -150mA$, $V_{CE} = -2.0V$) ($I_C = -500mA$, $V_{CE} = -2.0V$)	30 60 100 100 20	300	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage ($I_C = -150mA$, $I_B = -15mA$) ($I_C = -500mA$, $I_B = -50mA$)		-0.4 -0.75	Vdc
$V_{BE(sat)}$	Base-Emitter Saturation Voltage ($I_C = -150mA$, $I_B = -15mA$) ($I_C = -500mA$, $I_B = -50mA$)	-0.75	-0.95 -1.30	Vdc

SMALL-SIGNAL CHARACTERISTICS


f_T	Current Gain-Bandwidth Product ($I_C = -20mA$, $V_{CE} = -10V$, $f = 100MHz$)	200		MHz
C_{cb}	Output Capacitance ($V_{CB} = -10V$, $I_E = 0$, $f = 140kHz$)		8.5	pF
C_{eb}	Input Capacitance ($V_{EB} = -0.5V$, $I_C = 0$, $f = 140kHz$)		30.0	pF

SWITCHING CHARACTERISTICS







t_d	Delay Time	($V_{CC} = -3.0V$, $V_{BE} = -2.0V$)	15	ns
t_r	Rise Time	($I_C = -150mA$, $I_{B1} = -15mA$)	20	ns
t_s	Storage Time	($V_{CC} = -3.0V$, $I_C = -150mA$)	225	ns
t_f	Fall Time	($I_{B1} = I_{B2} = -15mA$)	30	ns

*Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2.0\%$

TO-92







DIM	DIMENSIONS				NOTE
	INCHES		MM		
A	.170	.190	4.33	4.83	
B	.170	.190	4.30	4.83	
C	.550	.590	13.97	14.97	
D	.010	.020	0.36	0.56	
E	.130	.160	3.30	3.96	
G	.010	.104	2.44	2.64	



2N4403



Micro Commercial Components





Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-AP	Ammo Packing;2Kpcs/AmmoBox
(Part Number)-BP	Bulk;1Kpcs/Bag

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.