

### Transistor

#### Silicon PNP Epitaxial Type (PCT Process)


#### For General Purpose Switching and Amplifier Applications

#### Features

- Complementary to 2SC3281
- Recommended for 100W High Fidelity Audio Frequency
  - Amplifier Output Stage

#### Absolute Maximum Ratings (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	$V_{CB0}$	-200	V
Collector-Emitter Voltage	$V_{CE0}$	-200	V
Emitter-Base Voltage	$V_{EB0}$	-5	V
Collector Current	$I_C$	-15	A
Base Current	$I_B$	-1.5	A
Collector Power Dissipation (Tc = 25°C)	$P_C$	150	W
Junction Temperature	$T_j$	150	°C
Storage Temperature Range	$T_{stg}$	-55 ~ 150	°C









Weight : 9.75g

#### Electrical Characteristics (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	$I_{CB0}$	$V_{CB} = -200V, I_E = 0$	-	-	-5.0	$\mu A$
Emitter Cut-off Current	$I_{EB0}$	$V_{EB} = -5V, I_C = 0$	-	-	-5.0	$\mu A$
Collector-Emitter Breakdown Voltage	$V_{(BR)CE0}$	$I_C = -50mA, I_B = 0$	-200	-	-	V
DC Current Gain	$h_{FE(1)}$ (Note)	$V_{CE} = -5V, I_C = -1mA$	55	-	160	
	$h_{FE(2)}$	$V_{CE} = -5V, I_C = -8A$	35	60	-	
Saturation Voltage Collector-Emitter	$V_{CE(sat)}$	$I_C = -10A, I_B = -1A$	-	-1.5	-3.0	V
Base-Emitter Voltage	$V_{BE}$	$V_{CE} = -5V, I_C = -8A$	-	-1.0	-1.5	V
Transition Frequency	$f_T$	$V_{CE} = -5V, I_C = -1A$	-	25	-	MHz
Collector Output Capacitance	$C_{ob}$	$V_{CB} = -10V, I_E = 0, f = 1MHz$	-	470	-	pF

Note:  $h_{FE}$  (1) Classification R : 0 : 55 ~ 110, 0 : 80 ~ 160



The information contained here is subject to change without notice.

The information contained herein is presented only as guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others. These TOSHIBA products are intended for usage in general electronic equipments (office equipment, communication equipment, measuring equipment, domestic electrification, etc.) Please make sure that you consult with us before you use these TOSHIBA products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life (atomic energy control, spaceship, traffic signal, combustion control, all types of safety devices, etc.). TOSHIBA cannot accept liability to any damage which may occur in case these TOSHIBA products were used in the mentioned equipments without prior consultation with TOSHIBA.