


FJAF4310

Audio Power Amplifier

- High Current Capability : I_C=10A
- High Power Dissipation
- Wide S.O.A
- Complement to FJAF4210



NPN Epitaxial Silicon Transistor

Absolute Maximum Ratings $T_C=25^{\circ}C$ unless otherwise noted

Symbol	Parameter	Value	Units
V _{CBO}	Collector-Base Voltage	200	V
V _{CEO}	Collector-Emitter Voltage	140	V
V _{EBO}	Emitter-Base Voltage	6	V
I _C	Collector Current (DC)	10	Α
IB	Base Current (DC)	1.5	Α
P _C	Collector Dissipation (T _C =25°C)	80	W
$R_{\theta JC}$	Junction to Case	1.48	°C/W
TJ	Junction Temperature	150	°C
T _{STG}	Storage Temperature	- 55 ~ 150	°C

Electrical Characteristics $T_C=25$ °C unless otherwise noted

Symbol	Parameter	Test Condition	Min.	Тур.	Max.	Units
BV _{CBO}	Collector-Base Breakdown Voltage	$I_C=5mA$, $I_E=0$	200			V
BV _{CEO}	Collector-Emitter Breakdown Voltage	I _C =50mA, R _{BE} =∞	140			V
BV _{EBO}	Emitter-Base Breakdown Voltage	$I_E=5mA$, $I_C=0$	6			V
I _{CBO}	Collector Cut-off Current	V_{CB} =200V, I_{E} =0			10	μΑ
I _{EBO}	Emitter Cut-off Current	V _{EB} =6V, I _C =0			10	μΑ
h _{FE}	* DC Current Gain	V_{CE} =4V, I_{C} =3A	50		180	
V _{CE} (sat)	Collector-Emitter Saturation Voltage	I _C =5A, I _B =0.5A			0.5	V
C _{ob}	Output Capacitance	V _{CB} =10V, f=1MHz		250		pF
f _T	Current Gain Bandwidth Product	V _{CE} =5V, I _C =1A		30		MHz

^{*} Pulse Test : PW=20µs

h_{FE} Classification

Classification	R	0	Υ	
h _{FE}	50 ~ 100	70 ~ 140	90 ~ 180	

Typical Characteristics




Figure 1. Static Characterstic




Figure 3. $V_{CE}(sat)$ vs. I_B Characteristics




Figure 5. Base-Emitter On Voltage




Figure 2. DC current Gain




Figure 4. Collector-Emitter Saturation Voltage




Figure 6. Forward Bias Safe Operating Area

©2002 Fairchild Semiconductor Corporation

Typical Characteristics (Continued)





Figure 7. Power Derating

Package Dimensions

TO-3PF



TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FACT™	ImpliedDisconnect™	PACMAN™	SPM™
ActiveArray™	FACT Quiet series™	ISOPLANAR™	POP™	Stealth™
Bottomless™	FAST [®]	LittleFET™	Power247™	SuperSOT™-3
CoolFET™	FASTr™	MicroFET™	PowerTrench [®]	SuperSOT™-6
$CROSSVOLT^{TM}$	FRFET™	MicroPak™	QFET™	SuperSOT™-8
DOME™	GlobalOptoisolator™	MICROWIRE™	QS™	SyncFET™
EcoSPARK™	GTO™	MSX™	QT Optoelectronics™	TinyLogic™
E ² CMOS™	HiSeC™	MSXPro™	Quiet Series™	TruTranslation™
EnSigna™	I^2C^{TM}	OCX^{TM}	RapidConfigure™	UHC™
Across the board.	Around the world.™	OCXPro™	RapidConnect™	UltraFET [®]
The Power Franchise™		OPTOLOGIC [®]	SILENT SWITCHER®	VCX TM
Programmable Ad	ctive Droop™	OPTOPLANAR™	SMART START™	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.