

FPN330 FPN330A



NPN Low Saturation Transistor

These devices are designed for high current gain and low saturation voltage with collector currents up to 3.0 A continuous. Sourced from Process NB.

Absolute Maximum Ratings* TA = 25°C unless otherwise noted

Symbol	Parameter	Value	Units
V _{CEO}	Collector-Emitter Voltage	30	V
V _{CBO}	Collector-Base Voltage	50	V
V _{EBO}	Emitter-Base Voltage	5.0	V
I _C	Collector Current - Continuous	3.0	A
T _J , T _{stg}	Operating and Storage Junction Temperature Range	-55 to +150	°C

*These ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

NOTES:

- 1) These ratings are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics TA = 25°C unless otherwise noted

Symbol	Characteristic	Max	Units
		FPN330 / FPN330A	
P _D	Total Device Dissipation	1.0	W
R _{θJC}	Thermal Resistance, Junction to Case	50	°C/W
R _{θJA}	Thermal Resistance, Junction to Ambient	125	°C/W

NPN Low Saturation Transistor

(continued)

Electrical Characteristics

TA = 25°C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Max	Units
--------	-----------	-----------------	-----	-----	-------

OFF CHARACTERISTICS*

BV _{CEO}	Collector-Emitter Breakdown Voltage	I _C = 10 mA, I _B = 0	30		V
BV _{CBO}	Collector-Base Breakdown Voltage	I _C = 100 μA, I _E = 0	50		V
BV _{EBO}	Emitter-Base Breakdown Voltage	I _E = 100 μA, I _C = 0	5.0		V
I _{CB0}	Collector Cutoff Current	V _{CB} = 30 V, I _E = 0		100	nA
		V _{CB} = 30 V, I _E = 0, T _A = 100°C		10	μA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 4.0 V, I _C = 0		100	nA

ON CHARACTERISTICS*

h _{FE}	DC Current Gain	I _C = 100 mA, V _{CE} = 2.0 V	330	100	
		I _C = 1.0 A, V _{CE} = 2.0 V	330A	250	
		I _C = 2.0 A, V _{CE} = 2.0 V		120	
				50	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 1.0 A, I _B = 100 mA	330		500 mV
		I _C = 2.0 A, I _B = 200 mA	330A		450 mV
					1.0 V
V _{BE(sat)}	Base-Emitter Saturation Voltage	I _C = 1.0 A, I _B = 100 mA			1.25 V
V _{BE(on)}	Base-Emitter Saturation Voltage	I _C = 1.0 A, V _{CE} = 2.0 V			1.0 V







SMALL SIGNAL CHARACTERISTICS

C _{obo}	Output Capacitance	V _{CB} = 10 V, I _E = 0, f = 1.0 MHz		30	pF
F _T	Transition Frequency	I _C = 100 mA, V _{CE} = 5.0 V, f = 100 MHz	100		MHz

*Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%

FPN330 / FPN330A

Typical Characteristics



TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE ^x TM	FAST ^r TM	PowerTrench [®]	SyncFET TM
Bottomless TM	GlobalOptoisolator TM	QFET TM	TinyLogic TM
CoolFET TM	GTO TM	QS TM	UHC TM
CROSSVOLT TM	HiSeC TM	QT Optoelectronics TM	VCX TM
DOME TM	ISOPLANAR TM	Quiet Series TM	
E ² CMOS TM	MICROWIRE TM	SILENT SWITCHER [®]	
EnSigna TM	OPTOLOGIC TM	SMART START TM	
FACT TM	OPTOPLANAR TM	SuperSOT TM -3	
FACT Quiet Series TM	PACMAN TM	SuperSOT TM -6	
FAST [®]	POP TM	SuperSOT TM -8	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.